



PRODUCT CATALOGUE | REXNORD® / MCC®
ISSUE 11 | TABLETOP® AND MATTOP® CHAINS

PRODUCT CATALOGUE | REXNORD / MCC TABLETOP AND MATTOP CHAINS ISSUE 11

AUSTRALIA

Rexnord Australia Pty. Ltd.
Picton, New South Wales
Phone: 61-2-4677-3811
Fax: 61-2-4677-3812

BRAZIL

Rexnord Correntes Ltda.
Sao Leopoldo – RS
Phone: 55-51-579-8022
Fax: 55-51-579-8029

CANADA

Rexnord Canada Ltd.
Scarborough, Ontario
Phone: 1-416-297-6868
Fax: 1-416-297-6873

CHINA

Rexnord China
Shanghai
Phone: 86-21-62701942
Fax: 86-21-62701943

FLATTOP EUROPE

Rexnord FlatTop Europe b.v.
's-Gravenzande, The Netherlands
Phone: 31-174-445-111
Fax: 31-174-445-222
Rexnord Marbett S.r.l.
Correggio (RE), Italy
Phone: 39-0522-639333
Fax: 39-0522-637778

RMCC Deutschland Kette GmbH
Phone: 0800-5888083
Fax: 0800-5888084

Rexnord FlatTop France
Phone: 0805 540 444
Fax: 0805 540 555
Rexnord.Marbett@rexnord.com

UNITED STATES

Customer Service
Phone: 1-866-REXNORD
(1-866-739-6673)
Fax: 1-614-675-1898
rexnordcs(state)@rexnord.com
Example: rexnordcs(ohio)@rexnord.com


Rexnord FlatTop North America
Grafton, Wisconsin
Phone: 1-262-376-4700
Fax: 1-262-376-4720

Rexnord International - Power Transmission
Milwaukee, Wisconsin
Phone: 1-414-643-2366
Fax: 1-414-643-3222
international2@rexnord.com

ALL COUNTRIES NOT LISTED

Rexnord FlatTop Europe b.v.
's-Gravenzande,
The Netherlands
Phone: 31-174-445-111
Fax: 31-174-445-222

After Hours/Emergency Phone:
31-174-445-112



www.rexnordflattop.com
flattopeurope@rexnord.com

799.02.95

FlatTop Europe



INDEX

	PAGE
COMPANY PROFILE	4
OVERVIEW TABLETOP CHAINS	6
INTRODUCTION STEEL TABLETOP CHAINS	8
STEEL TABLETOP CHAINS	10
STEEL TABLETOP CHAINS WITH RUBBER TOP	21
INTRODUCTION PLASTIC TABLETOP CHAINS	26
PLASTIC TABLETOP CHAINS	28
PLASTIC TABLETOP CHAINS WITH RUBBER TOP	42
PLASTIC TABLETOP LBP CHAINS	47
PLASTIC CHAINBELTS	52
SPROCKETS FOR TABLETOP CHAINS	55
CORNER DISCS FOR PLASTIC TABLETOP CHAINS	73
INTRODUCTION MULTIFLEX AND CASE CONVEYOR CHAINS	74
MULTIFLEX CHAINS	76
SPROCKETS FOR MULTIFLEX CHAINS	82
CORNER DISCS FOR MULTIFLEX CHAINS	84
CASE CONVEYOR CHAINS	85
SPROCKETS FOR CASE CONVEYOR CHAINS	89
INTRODUCTION PLATE TOP AND GRIPPER CHAINS	90
PLATE TOP CHAINS	92
GRIPPER CHAINS	97
INTRODUCTION CURVES AND STRAIGHT TRACKS	102
MAGNETFLEX COMBI CURVES	104
TAB CURVES	121
BEVEL CURVES	125
STRAIGHT TRACKS	127
OVERVIEW MATTOP MODULAR CONVEYOR BELTS	128
INTRODUCTION MATTOP	130
500 -SERIES	132
510 -SERIES	134
1500-SERIES	136
8500-SERIES	142
5930-SERIES	146
1000-SERIES	150
1005-SERIES	158
1010-SERIES	164
7700-SERIES	166
6300-SERIES	170
2000-SERIES	174
2010-SERIES	180
9200-SERIES FORTREX	184
2500-SERIES	188
6990-SERIES	190
3120-SERIES	193
INTRODUCTION SIDEFLEXING MODULAR BELTS	196
505-SERIES	197
1200-SERIES	199
7956-SERIES	204
BELT CODE NUMBERS	206
MATERIALS	207
PRODUCT INDEX	210



The company

Rexnord is a global company supplying many industries with power transmission and conveying components. The product offering ranges from roller chains, couplings and geared products to conveyor chains, belts and components. The head office is based in the United States, with several divisions all over the world. The Rexnord FlatTop division is manufacturing conveyor chains, belts and components.

Rexnord is fully committed to meet customer expectations; huge knowledge of the business reduces maintenance costs, eliminates redundant inventories and prevents downtime, all in close co-operation with OEMs and end users. This is a result of Rexnord's focus on product development, application engineering, operations and customer service.

Rexnord FlatTop Europe represents 3 strong brands: Rexnord, MCC and Marbett.

With production facilities in 's-Gravenzande and Correggio, sales offices in The Netherlands and Italy, a large sales group for local service in many countries and distributors all over the world, Rexnord is always close to its customers. In this way a fast and reliable delivery is guaranteed.


Rexnord chains and belts are being used to convey a wide variety of products: bottles, cans, boxes, crates, tires, loose food, glass jars, PET containers, trays; shortly every transport in production halls in virtually any industry.

The product range has been split up over two catalogues, one for Rexnord/MCC Table Top/MatTop chains and one for Marbett conveyor components.

The industries served

As the handling specialist in the field of conveying, the Rexnord product portfolio is providing solutions for complete lines in several industries in order to improve productivity.

In beverage industry palletizers, depalletizers, washers, labelers, fillers, pasteurizers, inliners, outfeeds, elevators and accumulation tables are equipped with slatband chains, curves, sprockets, belts, bearings, leveling elements and many more conveyor components.



For the container manufacturing industry special products and materials are available, such as abrasion resistant polyamide for glass plants, vacuum chains for can making and gripper chains for vertical transport.




A wide range of products is also offered for blanchers, cookers, washers, coolers and processing lines in fruit, vegetables, bakery, confectionary etc. And many more products are available for the handling of packed food.



In automotive industry the products are engineered to meet the most demanding applications, such as rubber processing and tire handling.

This is just a short selection of the applications in which Rexnord products are being used. Among others they have also found their way into pharmaceutical production lines, battery manufacture, paper and cardboard production.



Rexnord and MCC TableTop chains and MatTop belts

The product line can be split up into:

- Steel slatband chains

In various materials ranging from carbon steel to special stainless steel with better wear and sliding properties; types straight running, sideflexing tab, bevel and Magnetflex, with

and without rubber top.

- Plastic slatband chains

Wide range of materials and various executions; single hinge, double hinge, heavy duty, vacuum, lbp rollers and rubber top.

- Plate Top and Gripper chains

Based on the Rexnord roller chains in both stainless and carbon steel; Plate Top chains have steel or plastic top plates; Gripper chains have different types of rubber inserts.

- Case conveyor and Multiflex chains

Different types of acetal for both straight running and sideflexing transport of products varying from heavy crates to small juice packs.

- Curves

Magnetflex, Tab and bevel, as well as straight tracks to support the chain in all parts of the line; there are many standard versions besides the ability to make any special curve needed

in your applications with short delivery times.

- Modular belts

Pitches differ from 0.5 to 2.25 inch to suit any application. Most series have both closed and open top executions; some also available with rubber top for inclined conveying.

Marbett conveyor components

The product line can be split up into:

- Chain guide components

Profiles, corner tracks, straight tracks, return rollers, serpentine, plugs for connections.

- Product handling components

Guide rails, roller guides, guide rail clamps, guide rail brackets and connecting clamps in plastic or stainless steel.

- Frame support components

Side mounting top brackets, bearing heads, support bases and connecting joints, stainless steel components.

- Supporting and leveling elements

Different versions in steel and plastic, articulated and fixed, with and without gripper bottom and vibration absorbing feet.



- Self-aligning bearings

Square, oval, pillow block, side flange, take-up, round, and other executions, all with open and closed unit. Lubricated for life versions are also available.

- Miscellaneous components Line control elements, hinges, locks, knobs, modular transfer roller plates, rollers, tensioners, nozzles, cable carriage chains, shaft collars and nose-over bars.

OVERVIEW REXNORD TABLE


S T R A I G H T

Steel	SINGLE HINGE page 10		SINGLE HINGE MAX-LINE page 10, 11		DOUBLE HINGE MAX-LINE page 12		HEAVY DUTY MAX-LINE page 12		SINGLE HINGE TAB MAX-LINE page 13	
Plastic	SINGLE HINGE page 28		SINGLE HINGE SIDEFLEX JOINT HINGE page 29		SINGLE HINGE WITH THICK TOP PLATE page 29		DOUBLE HINGE page 30		HEAVY DUTY page 30	
Rubber Top	STEEL SINGLE HINGE page 21		STEEL SINGLE HINGE TAB page 21		STEEL DOUBLE HINGE MAX-LINE page 22		STEEL HEAVY DUTY MAX-LINE page 23		STEEL HEAVY DUTY TAB MAX-LINE page 23	
LBP	SINGLE HINGE page 47		DOUBLE HINGE page 47		HEAVY DUTY page 48		HEAVY DUTY page 48			
Case Conveyor	WITHOUT TABS page 85		REINFORCED WITHOUT TABS page 87							
Plate Top	STEEL TOP PLATE 3/4" page 92		PLASTIC TOP PLATE 3/4" page 92		PLASTIC TOP PLATE 1/2" page 93					

S I D E F L E X

Steel	MAGNETFLEX SINGLE HINGE MAX-LINE page 16		SINGLE HINGE BEVEL MAX-LINE page 16		SINGLE HINGE BEVEL page 17		SINGLE HINGE TAB page 17		SINGLE HINGE TAB MAX-LINE page 18	
Plastic	MAGNETFLEX page 31		MAGNETFLEX HEAVY DUTY page 32		STANDARD RADIUS BEVEL page 32,33		BEVEL HEAVY DUTY page 33		STANDARD RADIUS SINGLE HINGE TAB page 34, 35	
Rubber Top	STEEL SINGLE HINGE MAGNETFLEX MAX-LINE page 24		STEEL SINGLE HINGE BEVEL MAX-LINE page 24		STEEL SINGLE HINGE TAB MAX-LINE page 25		STEEL MAGNETFLEX HEAVY DUTY MAX-LINE page 25		PLASTIC MAGNETFLEX HEAVY DUTY SUPERGRIP page 44	
LBP	MAGNETFLEX page 49		MAGNETFLEX HEAVY DUTY page 49		STANDARD RADIUS SINGLE HINGE TAB page 50		SMALL RADIUS SINGLE HINGE TAB page 50		HEAVY DUTY TAB page 51	
Chainbelts	FLUSH GRID MAGNETFLEX page 52		FLATTOP MAGNETFLEX page 53		FLATTOP MAGNETFLEX HEAVY DUTY page 53		FLATTOP TAB page 54		FLATTOP TAB HEAVY DUTY page 54	
Multiflex	1765 ZERO GAP page 76		2565 HEAVY DUTY page 76		1757 TAB page 77		1757 TAB WITH RUBBER page 77		1700 (TAB) K page 78	
Case Conveyor	TAB page 85		TAB WITH HIGHER LINK page 86		REINFORCED TAB page 87		REINFORCED TAB WITH HIGHER LINK page 88			
Plate Top	PLASTIC TOP PLATE TAB 1/2" page 93		STEEL TOP PLATE TAB 3/4" page 94		PLASTIC TOP PLATE TAB 3/4" page 95		PLASTIC TOP PLATE TAB CLOSED SURFACE 3/4" page 96		PLASTIC TOP PLATE TAB WITH RUBBER 3/4" page 96	
Gripper	STEEL TAB 3/4" page 97		STEEL TAB HEAVY DUTY 3/4" page 97		PLASTIC TAB 1/2" page 98		PLASTIC TAB SNAP-ON CLOSED 3/4" page 98		PLASTIC TAB SNAP-ON 2-FINGER 3/4" page 99	

TOP CONVEYOR CHAINS

MINI HINGE		SINGLE HINGE 1" MAX-LINE							
page 14		page 14							
VACUUM		MINIATURE							
page 39		page 41							
PLASTIC SINGLE HINGE		PLASTIC DOUBLE HINGE WITH PUSHERS		PLASTIC DOUBLE HINGE SUPERGRIP		PLASTIC DOUBLE HINGE		PLASTIC HEAVY DUTY SUPERGRIP	
page 42		page 42		page 43		page 43		page 44	

SINGLE HINGE SMALL RADIUS TAB page 18		MAGNETFLEX HEAVY DUTY MAX-LINE page 19		SINGLE HINGE 1" MAX-LINE page 19		DOUBLE HINGE 1" 661 MAX-LINE page 15-20					
SMALL RADIUS SINGLE HINGE TAB page 36, 37		TAB HEAVY DUTY page 38		TAB VACUUM page 39		TAB WITH FLIGHTS page 40		TAB WITH FLANGES page 40		ARTICULATED WITH TOP PLATES page 41	
PLASTIC STANDARD RADIUS SINGLE HINGE TAB page 45		PLASTIC STANDARD RADIUS SINGLE HINGE TAB page 45		PLASTIC SMALL RADIUS SINGLE HINGE TAB page 46		PLASTIC SMALL RADIUS SINGLE HINGE TAB page 46					
HEAVY DUTY TAB page 51											

1702 page 79		1720 page 79		1710 page 80		TAB 1710 K page 80		1713 page 81		TAB 1713 K page 81	
---------------------	--	---------------------	---	---------------------	---	---------------------------	---	---------------------	---	---------------------------	---

PLASTIC TAB SNAP-ON 3-FINGER 3/4" page 99		PLASTIC TAB 3/4" page 100		PLASTIC TAB INTEGRATED GRIPPER 3/4" page 101	
--	--	--	---	---	---

STEEL TABLETOP CHAINS

In 1938 Rexnord introduced the worlds first metal TableTop chain with integrated top plate and hinge eyes. Nowadays the Rexnord and MCC product lines of steel slatband chains offer many materials, types and grades, enabling a solution for any application. Steel slatband chains are ideal for handling glass bottles, PET containers, kegs, crates and many other products.

FEATURES

- Surface finish


When products are sliding on a chain, the bottom will affect the surface finish of the chain. Rexnord tests have shown that during the first days after installation the initial surface finish is changing to a lower level that is maintained during the normal life of the chain. Surface finish is a valuable feature, although it is not the determining factor between good and great performance.

- Sliding properties


These depend on the base material and the treatments during the manufacturing process. To ensure superior sliding properties, Rexnord uses a number of patented chain materials, specifically designed for slatband chain applications. You can find more details on these materials on next page.

Series	Ra μm
MCC 10-series	0.5
MCC 60-series	0.3
MCC 60-series HB	0.3
MCC 66-series XHB	0.3
Rexnord SSC OPTI-Plus series	0.5
Rexnord SS-series	0.5
Rexnord SSB-series	0.5
Rexnord S-series	not applicable

MEAN SURFACE FINISH OF TABLETOP SLATBAND CHAIN



FLATNESS IN WIDTH DIRECTION



FLATNESS IN RUNNING DIRECTION

- Flatness

During the entire production process the flatness is measured in running direction (R) and in width direction (W). The flatness in width direction is important when products slide sideways from one chain to the other. For this reason the cross sections of all Rexnord and MCC chains are convex instead of concave, to prevent products to fall. Due to the careful control in production, these chains offer superior lateral flatness values, which can be found in the tables on the page of each chain.

Flatness when a product moves from one link of the chain to the next is also important, as poor flatness will cause products tipping, leading to production loss in the line. MCC and Rexnord steel slatband chains offer an outstanding flatness in running direction.

- Working load

At which load a chain is actually breaking is not relevant to determine if a certain chain is suitable for your application. More important is the maximum working load a chain can handle before permanent deformation occurs. Rexnords chain calculation program will assist in defining the right chain for specified applications, considering conveyor length, chain speed, accumulation level, lubrication, product type and weight.

Series	Flatness mm
MCC Sideline® chains	0.10
MCC standard chains	0.15
Rexnord SSC OPTI-Plus® chains	0.10
Rexnord standard chains	0.15

FLATNESS IN RUNNING DIRECTION

- Polished hinge eyes

The performance of the chain on high-speed side-transfers, such as pressure-less combiners improves with polished hinge eyes, due to the smooth contact with the wearstrips. This prevents pulsating of the chain and improves product handling. Most Rexnord sideflexing chains have polished hinge eyes, because these are always in contact with the curve. The specification table of each chain indicates whether a chain has polished hinge eyes.

- Hardened Pins

Hardened pin material reduces the chain elongation significantly. Patented special hardened pins will give the highest resistance to chain elongation over a long period of time. High quality 60-series HB Stainless Steel TableTop® chain with Hardened Pins with improved wear resistance properties. Special 66-series XHB Stainless Steel TableTop® with special hardened pins to offer superior wear resistance properties.



STEEL TABLETOP CHAINS

PROGRAMME

Steel TableTop chains are available in the following materials:

REXNORD	
SSC/SSR	OPTI-Plus patented alloy of ferritic chrome nickel stainless steel, offering high strength and great wear resistance. These chains feature a ground surface and are fitted with pins in AISI 431 (1.4057) material
SS 805/815/881	Austenitic chrome nickel stainless steel with properties similar to 18/8 material, offering good chemical resistance. These chains are fitted with pins in austenitic stainless steel
SS 802/812	Ferritic chrome stainless steel for general purposes, offering a mix of good wear life and high strength. These chains are fitted with pins in AISI 431(1.4057) material
S/SC	Thorough hardened carbon steel, very suitable for glassworks and other dry, abrasive applications, offering extremely high working loads and superior wear resistance. These chains are fitted with hardened carbon steel pins
SSB	Austenitic stainless steel with a very high chemical resistance for corrosive environments where strong acids or bases are present. As SSB is nearly non-magnetic it is used in applications where magnetism of the chain can cause malfunctioning of the system. It is fitted with austenitic stainless steel pins
Rexnord chain description starts with the material, followed by an 8.. number for the type and finally the width K. For example SSC 8811 TAB-K450 is an Opti-Plus sideflexing TAB 4½" wide chain.	
MCC	
10-Series	Specially treated 17% chrome ferritic stainless steel for general applications, offering a long wear life and high strength, together with good sliding properties. It is fitted with pins in AISI 431(1.4057) material
60-Series	Special chrome nickel ferritic stainless steel for heavy duty and high-speed applications, requiring very smooth transfer of (unstable) products. It is offering superior sliding properties and the highest working loads. These chains are fitted with pins in AISI 431(1.4057) material
60-Series HB	Special chrome nickel ferritic stainless steel for heavy duty and high-speed applications, requiring very smooth transfer of (unstable) products. It is offering superior sliding properties and the highest working loads. These chains are fitted with Hardened pins (HB) in AISI 431(1.4057) material
66-Series XHB	Special chrome nickel ferritic stainless steel for heavy duty and high-speed applications, requiring very smooth transfer of (unstable) products. It is offering superior sliding properties and the highest working loads. Furthermore the 66-series offers ultimate wearlife. These chains are fitted with special alloy process hardened pins.
661-Series	Exclusive 1" pitch design with better product stability, lower noise and lower energy consumption; ideal for mass handling, standard inliners and high speed-inliners.
MCC chain description starts with the material, followed by an S for straight running, M for Magnetflex, B for bevel or T for tab sideflexing chains, followed by the width and finally the execution: S for Slideline, X for X-line, M for Max-Line and R for Rubber. For example 60 S 31 XM is a 60-series straight running 3¼" wide chain with Max-Line and X-Line.	

Slideline chains offer very close tolerances with respect to flatness and surface finish

X-line chains have extreme precision flatness and superior sliding properties

Max-line chains take care of perfect product support, due to maximum plate surface.

	APPLICATION							
CHAIN MATERIAL	Mass handling	Inliner standard	Inliner high-speed	Abrasive wet	Abrasive dry	Chemicals	Incline	Crate handling
10-series								
SS 812/802								
60-series								
60-series HB								
66-series XHB								
SSC Opti-Plus®								
SS 815/805/881								
S/SC 815								
SSB								
Rubber Top								


Optional

Best choice

STEEL TABLETOP CHAINS



**STRAIGHT RUN
SINGLE HINGE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch				
10-SERIES							
10 S 31	762.10.31	82.5	3.25	2.55	0.18	no	4950
10 S 31 S	762.12.31	82.5	3.25	2.55	0.18	yes	
FERRITIC STAINLESS STEEL							
SS 812-K325	10.001.11.11	82.5	3.25	2.55	0.18	no	4950

Standard length: 3.048 m - 10 feet (80 links)



**STRAIGHT RUN
SINGLE HINGE
MAX-LINE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch				
10-SERIES							
10 S 31 M	762.13.31	82.5	3.25	2.61	0.18	no	4950
10 S 42 M	762.13.42	114.3	4.50	3.28	0.25	no	
10 S 72 M	762.13.72	190.5	7.50	4.99	0.60	no	
60-SERIES							
60 S 22 SM	762.69.22	63.5	2.50	2.14	0.18	yes	6000
60 S 25 M	762.53.25	66.7	2.63	2.27	0.18	no	
60 S 23 M	762.53.23	69.9	2.75	2.34	0.18	no	
60 S 30 M	762.53.30	76.2	3.00	2.43	0.18	no	
60 S 31 M	762.53.31	82.5	3.25	2.61	0.18	no	
60 S 31 XM	762.69.31	82.5	3.25	2.61	0.08	yes	
60 S 84 XM	762.69.84	84.0	3.30	2.63	0.08	yes	
60 S 32 M	762.53.32	88.9	3.50	2.71	0.18	no	
60 S 32 SM	762.69.32	88.9	3.50	2.71	0.18	yes	
60 S 40 M	762.53.40	101.6	4.00	3.17	0.25	no	
60 S 42 M	762.53.42	114.3	4.50	3.28	0.25	no	
60 S 60 M	762.53.60	152.4	6.00	4.14	0.40	no	
60 S 72 M	762.53.72	190.5	7.50	4.99	0.60	no	

STEEL TABLETOP CHAINS



**STRAIGHT RUN
SINGLE HINGE
MAX-LINE (CONTINUED)**





Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
60-SERIES HB							
60 S 31 XM HB	762.69.15	82.5	3.25	2.50	0.08	yes	6000
60 S 84 XM HB	762.69.14	83.8	3.30	2.52	0.08	yes	
66-SERIES XHB							
66 S 31 XM XHB	762.09.31	82.5	3.25	2.61	0.08	yes	6000
66 S 84 XM XHB	762.09.84	84.0	3.30	2.63	0.08	yes	
66 S 72 M	762.03.72	190.5	7.50	4.99	0.60	no	
OPTI-PLUS							
SSC 812-K250	10.006.21.05	63.5	2.50	2.14	0.18	no	6000
SSC 812-K263	10.006.21.08	66.7	2.63	2.27	0.18	no	
SSC 812-K300	10.006.21.10	76.2	3.00	2.43	0.18	no	
SSC 812-K325	10.006.21.11	82.5	3.25	2.61	0.18	no	
SSC 812-K330	10.006.21.20	84.0	3.30	2.63	0.18	no	
SSC 812-K350	10.006.21.12	88.9	3.50	2.71	0.18	no	
SSC 812-K400	10.006.21.13	101.6	4.00	3.17	0.25	no	
SSC 812-K450	10.006.21.14	114.3	4.50	3.28	0.25	no	
SSC 812-K600	10.006.21.15	152.4	6.00	4.14	0.40	no	
SSC 812-K750	10.006.21.16	190.5	7.50	4.99	0.60	no	
CARBON STEEL							
S 815-K225	762.93.21	57.2	2.25	2.12	0.40	no	8350
S 815-K250	762.93.22	63.5	2.50	2.14	0.40	no	
S 815-K263	762.93.25	66.7	2.63	2.27	0.40	no	
S 815-K325	762.93.31	82.5	3.25	2.61	0.40	no	
S 815-K400	762.93.40	101.6	4.00	3.17	0.50	no	
S 815-K450	762.93.42	114.3	4.50	3.28	0.60	no	
S 815-K600	762.93.60	152.4	6.00	4.14	0.80	no	
S 815-K750	762.93.72	190.5	7.50	4.99	0.90	no	
AUSTENITIC CHROME NICKEL							
SS 815-K225	762.33.21	57.2	2.25	2.12	0.18	no	3500
SS 815-K250	762.33.22	63.5	2.50	2.14	0.18	no	
SS 815-K263	762.33.25	66.7	2.63	2.27	0.18	no	
SS 815-K325	762.33.31	82.5	3.25	2.61	0.18	no	
SS 815-K350	762.33.32	88.9	3.50	2.71	0.18	no	
SS 815-K400	762.33.40	101.6	4.00	3.17	0.25	no	
SS 815-K450	762.33.42	114.3	4.50	3.28	0.25	no	
SS 815-K600	762.33.60	152.4	6.00	4.14	0.40	no	
SS 815-K750	762.33.72	190.5	7.50	4.99	0.60	no	
AUSTENITIC STAINLESS STEEL							
SSB 815-K325	10.006.84.11	82.5	3.25	2.61	0.18	no	2900
SSB 815-K450	10.006.84.14	114.3	4.50	3.28	0.25	no	
SSB 815-K600	10.006.84.15	152.4	6.00	4.14	0.40	no	
SSB 815-K750	10.006.84.16	190.5	7.50	4.99	0.60	no	

Standard length: 3.048 m - 10 feet (80 links)


Note: SSB 815 chains have a plate thickness of 3.0 mm instead of 3.1 mm.

STEEL TABLETOP CHAINS



Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
10-SERIES							
10 S 77 M	762.13.77	190.5	7.50	5.64	0.60	no	7000
60-SERIES							
60 S 77 M	762.53.77	190.5	7.50	5.64	0.60	no	8900
66-SERIES							
66 S 77 M	762.03.77	190.5	7.50	5.64	0.60	no	8900
FERRITIC STAINLESS STEEL							
SS 802-K750	10.008.11.16	190.5	7.50	5.64	0.60	no	7000
OPTI-PLUS							
SSC 802-K450	10.008.21.14	114.3	4.50	4.00	0.25	no	8900
SSC 802-K750	10.008.21.16	190.5	7.50	5.64	0.60	no	
CARBON STEEL							
SC 800-K750	10.008.73.16	190.5	7.50	5.64	0.90	no	15000
AUSTENITIC CHROME NICKEL							
SS 805-K750	10.008.94.160	190.5	7.50	5.64	0.60	no	5000

Standard length: 3.048 m - 10 feet (80 links)



Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
60-SERIES							
60 S 75 M	762.53.75	190.5	7.50	5.10	0.60	no	7000
66-SERIES							
66 S 75 M	762.03.75	190.5	7.50	5.10	0.60	no	7000


Standard length: 3.048 m - 10 feet (80 links)

12 NOTE: 60 S 75 M is recommended for medium duty applications, 66 S 75 M is recommended for heavy duty applications

STEEL TABLETOP CHAINS



**STRAIGHT RUN
SINGLE HINGE TAB
MAX-LINE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
OPTI-PLUS							
SSC 812 TAB-K325	10.124.21.11	82.5	3.25	3.14	0.18	no	6000
SSC 812 TAB-K450	10.124.21.14*	114.3	4.50	3.88	0.25	no	
SSC 812 TAB-K750	10.124.21.16*	190.5	7.50	5.67	0.60	no	
CARBON STEEL							
S 815 TAB-K325	763.93.31	82.5	3.25	3.14	0.40	no	8350
S 815 TAB-K450	763.93.42*	114.3	4.50	3.88	0.60	no	
S 815 TAB-K750	763.93.72*	190.5	7.50	5.67	0.90	no	
AUSTENITIC CHROME NICKEL							
SS 815 TAB-K325	763.33.31	82.5	3.25	3.14	0.18	no	3500
SS 815 TAB-K450	763.33.42*	114.3	4.50	3.88	0.25	no	
SS 815 TAB-K750	763.33.72*	190.5	7.50	5.67	0.60	no	

Standard length: 3.048 m - 10 feet (80 links)



**STRAIGHT RUN
SINGLE HINGE TAB
MAX-LINE TRANSFER**



Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
AUSTENITIC CHROME NICKEL							
SS 815 TAB-K750 TRANSFER LEFT	763.33.73*	190.5	7.50	5.56	0.60	no	3500
SS 815 TAB-K750 TRANSFER RIGHT	763.33.74*	190.5	7.50	5.56	0.60	no	


Standard length: 3.048 m - 10 feet (80 links)

* Ask customer service for minimum order quantity

STEEL TABLETOP CHAINS



**STRAIGHT RUN
MINI HINGE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch				
60-SERIES							
60 S 11*	762.50.11	31.8	1.25	1.07	0.18	no	2500
60 S 13**	762.50.13	44.5	1.75	1.35	0.18	no	
66-SERIES							
66 S 11*	762.00.11	31.8	1.25	1.07	0.18	no	2500
66 S 13**	762.00.13	44.5	1.75	1.35	0.18	no	
OPTI-PLUS							
SSR 812-K125	10.010.21.01	31.8	1.25	1.07	0.18	no	2500
SSR 812-K175	10.010.21.02	44.5	1.75	1.35	0.18	no	
CARBON STEEL							
SR 810-K125	10.010.73.01	31.8	1.25	1.07	0.40	no	3250
SR 810-K175	10.010.73.02	44.5	1.75	1.35	0.40	no	

* Packaging: three strands of 3.048 m - 10 feet (3 x 80 links) per box

** Packaging: two strands of 3.048 m - 10 feet (2 x 80 links) per box



**STRAIGHT RUN
SINGLE HINGE
MAX-LINE 1"**





Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
OPTI-PLUS							
SSC 512-K217	10.011.61.04	55.1	2.17	2.29	0.18	no	5000
SSC 512-K236	10.011.61.07	59.9	2.36	2.41	0.18	no	
SSC 512-K250	10.011.61.05	63.5	2.50	2.49	0.18	no	
SSC 512-K283	10.011.61.09	71.9	2.83	2.65	0.18	no	
SSC 512-K325	10.011.61.11	82.5	3.25	2.86	0.18	no	
SSC 512-K350	10.011.61.12	88.9	3.50	3.01	0.18	no	
SSC 512-K400	10.011.61.13	101.6	4.00	3.26	0.25	no	

Standard length: 3.048 m - 10 feet (120 links)

STEEL TABLETOP CHAINS



**STRAIGHT RUN
DOUBLE HINGE
MAX-LINE 1"**



Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
661-SERIES							
661 S 31 SM	762.09.90	82.5	3.25	1.96	0.10	yes	5100
661 S 84 SM	762.09.91	83.8	3.30	1.97			


Standard length: 3.048 m – 10 feet (120 links)



STEEL TABLETOP CHAINS



**MAGNETFLEX®
SINGLE HINGE
MAX-LINE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		
10-SERIES							
10 M 31 M	767.13.31	82.5	3.25	2.50	0.18	yes	4950
10 M 42 M	767.13.42	114.3	4.50	3.12	0.25	yes	
10 M 72 M	767.13.72	190.5	7.50	4.59	0.60	yes	
60-SERIES							
60 M 31 M	767.53.31	82.5	3.25	2.50	0.18	yes	6000
60 M 31 XM	767.69.31	82.5	3.25	2.50	0.08	yes	
60 M 84 XM	767.69.84	84.0	3.30	2.52	0.08	yes	
60 M 42 M	767.53.42	114.3	4.50	3.12	0.25	yes	
60 M 72 M	767.53.72	190.5	7.50	4.59	0.60	yes	
60-SERIES HB							
60 M 31 XM HB	767.69.15	82.5	3.25	2.61	0.08	yes	6000
60 M 84 XM HB	767.69.14	84.0	3.30	2.63	0.08	yes	
66-SERIES XHB							
66 M 31 XM XHB	767.09.31	82.5	3.25	2.50	0.08	yes	6000
66 M 84 XM XHB	767.09.84	84.0	3.30	2.52	0.08	yes	
66 M 72 M	767.03.72	190.5	7.50	4.59	0.60	yes	

Standard length: 3.048 m - 10 feet (80 links). Sideflex radius min. 500 mm.



**SIDEFLEX
SINGLE HINGE BEVEL
MAX-LINE**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
OPTI-PLUS							
SSC 8811-K325	10.115.21.11	82.5	3.25	2.90	0.18	no	6000
SSC 8811-K350	10.115.21.12	88.9	3.50	3.10	0.18	no	
SSC 8811-K450	10.115.21.14	114.3	4.50	3.60	0.25	no	
SSC 8811-K750	10.115.21.16	190.5	7.50	5.30	0.60	no	

16 Standard length: 3.048 m - 10 feet (80 links). Sideflex radius min. 500 mm.

STEEL TABLETOP CHAINS



**SIDEFLEX
SINGLE HINGE BEVEL**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch		kg/m		mm
AUSTENITIC CHROME NICKEL							
SS 881-K325	765.32.31	82.5	3.25	2.97	0.18	no	3500
SS 881-K450	765.32.42	114.3	4.50	3.71	0.25	no	
SS 881-K750	765.32.72	190.5	7.50	5.49	0.60	no	
CARBON STEEL							
S 881-K325	765.92.31	82.5	3.25	2.97	0.40	no	8350
S 881-K450	765.92.42	114.3	4.50	3.71	0.60	no	
S 881-K750	765.92.72	190.5	7.50	5.49	0.90	no	

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm (for K325) and min. 610 mm (for K450 and K750).



**SIDEFLEX
SINGLE HINGE TAB**




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
AUSTENITIC CHROME NICKEL							
SS 881 TAB-K325	765.31.31	82.5	3.25	2.97	0.18	no	3500
SS 881 TAB-K450	765.31.42	114.3	4.50	3.71	0.25	no	
SS 881 TAB-K750	765.31.72	190.5	7.50	5.49	0.60	no	
CARBON STEEL							
S 881 TAB-K325	765.91.31	82.5	3.25	2.97	0.40	no	8350
S 881 TAB-K450	765.91.42	114.3	4.50	3.71	0.60	no	
S 881 TAB-K750	765.91.72	190.5	7.50	5.49	0.90	no	

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm (for K325) and min. 610 mm (for K450 and K750).


STEEL TABLETOP CHAINS



Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	N			
OPTI-PLUS							
SSC 8811 TAB-K325	10.114.21.11	82.5	3.25	3.10	0.18	no	6000
SSC 8811 TAB-K350	10.114.21.12	88.9	3.50	3.30	0.18	no	
SSC 8811 TAB-K450	10.114.21.14	114.3	4.50	3.80	0.25	no	
SSC 8811 TAB-K750	10.114.21.16	190.5	7.50	5.50	0.60	no	

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm.




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
OPTI-PLUS							
SSR 8811 TAB BO-K325	62969	82.5	3.25	3.10	0.18	no	4500

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 200 mm.

STEEL TABLETOP CHAINS




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
60-SERIES							
60 M 75 M	767.53.75	190.5	7.50	5.03	0.60	yes	7000
66-SERIES							
66 M 75 M	767.03.75	190.5	7.50	5.03	0.60	yes	7000

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 860 mm.

NOTE: 60 M 75 M is recommended for medium duty applications, 66 M 75 M is recommended for heavy duty applications




Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
OPTI-PLUS							
SSC 581 M-K325	10.027.21.11*	82.5	3.25	2.80	0.18	no	5000

Standard length: 3.048 m - 10 feet (120 links)

Sideflex radius min. 500 mm.

* Ask customer service for minimum order quantity.

STEEL TABLETOP CHAINS





page 110



page 66

MATERIAL

page 207

Chain type	Code nr.	Plate width		Weight	Surface flatness (max.)	Polished hinge eyes	Working load (max.)
		A					
		mm	inch	kg/m	mm		N
661-SERIES							
661 M 31 SM	767.09.90	82.5	3.25	1.84	0.10	yes	5100
661 M 84 SM	767.09.91	83.8	3.30	1.87			


Standard length: 3.048 m – 10 feet (120 links)



STEEL TABLETOP CHAINS WITH RUBBER TOP



**STRAIGHT RUN
SINGLE HINGE**




Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 S 31 R	762.04.31	82.5	3.25	2.80	no	6000

Standard length: 3.048 m - 10 feet (80 links)





**STRAIGHT RUN
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
OPTI-PLUS						
SSR 812 TAB-K325 RT	10.105.21.11	82.5	3.25	3.40	no	6000

Standard length: 3.048 m - 10 feet (80 links)

STEEL TABLETOP CHAINS WITH RUBBER TOP





Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A		kg/m		N
		mm	inch			
66-SERIES						
66 S 77 RM	762.06.72	190.5	7.50	6.20	no	8900

Standard length: 3.048 m - 10 feet (80 links)





STEEL TABLETOP CHAINS WITH RUBBER TOP



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 S 75 RM	752.64.75	190.5	7.50	5.21	no	7000


Standard length: 3.048 m - 10 feet (80 links)



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 ST 75 RM	763.04.75	190.5	7.50	6.30	no	7000

Standard length: 3.048 m - 10 feet (80 links)


STEEL TABLETOP CHAINS WITH RUBBER TOP



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 M 31 RM	767.06.31	82.5	3.25	2.54	yes	6000
66 M 72 RM	767.06.72	190.5	7.50	4.70	yes	

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm.




Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 B 72 RM	765.17.72	190.5	7.50	5.10	no	6000

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm.


STEEL TABLETOP CHAINS WITH RUBBER TOP



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 T 72 RM	765.16.72	190.5	7.50	5.30	no	6000
OPTI-PLUS						
SSC 8811 TAB-K325 RT	10.117.21.11	82.5	3.25	3.30	no	6000

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 500 mm.



Chain type	Code nr.	Plate width		Weight	Polished hinge eyes	Working load (max.)
		A				
		mm	inch	kg/m		N
66-SERIES						
66 M 75 RM	767.04.75	190.5	7.50	5.14	yes	7000

Standard length: 3.048 m - 10 feet (80 links)

Sideflex radius min. 860 mm.

PLASTIC TABLETOP CHAINS

From standard low friction to specialized high-tech materials for very specific applications, the Rexnord plastic TableTop range is capable of delivering a wide range of solutions for conveyor applications for virtually any industry.

FEATURES

- High strength materials

For dry running and lubricated beverage applications and also for abrasive applications in glass works, special materials are available, offering high PV resistance or very low friction.

- Sliding properties

To ensure superior sliding properties, Rexnord uses a number of patented chain materials. In many cases these materials are especially defined for conveyor applications. All different materials have friction coefficients tailored to the intended application.

- Flatness

The design of the mould and the control of the production process take care of flatness values meeting the highest standards. Together with the optimum sliding properties, this will prevent tipping of the products conveyed.

- Standardization

In case handling a number of different chains are used. Standard chains (XL, LF, HP) are used for general conveying of cases, trays or crates. High friction versions (Rubber Top, SuperGrip) are used for inclines and declines or on stopper belts. Version with rollers (LBP) are used in lines feeding palletizers in order to reduce the backline pressure and noise. The wide product range allows standardization of case handling conveyors, as a result of the same sprockets, track width, return rollers, return design, wearstrips and hinge width, also in co-operation with stainless steel (60 M 75 and 60 S 75). If plastic modular belts are used for straight running, sideflexing chainbelts are ideal for conveyors with 85 mm pitch; FGM 1050, FT 1050 and FTM 1060 match with 1000- and 8500-series, FTM 1055 and FT 1055 with 1005- and 7700-series. These chains feature a maximum support area and excellent transfers, even in small radii. For demanding applications FGM/FTM Magnetflex versions are recommended, whilst the FT tab versions are intended for less critical circumstances.

- 84 mm wide chains

Rexnord offers a complete range of both plastic and steel chains with 84 mm width, intended for the global beverage standard 85 mm pitch between the lanes of multi-lane conveyors. In plastic chains the straight running SHP84 and the sideflexing RHMP84 are companions, running on the same sprockets. The gap between the different tracks/lanes is minimized compared to the traditional 3.25" chains as well as the gap between the links of the chains, to offer superior product handling and minimize the risks of products falling.

- D-pins

SHP, RHMP, 1060, 1055, 879, 880 and 882 chains have D-style pins. Once assembled, the pin retention is done by means of geometrical fit instead of mechanical tension on the hinge eyes. This makes the chain less sensitive for attack by chemicals; it also allows (dis)assembly from both sides of the chains, reducing the chance of error.



PLASTIC TABLETOP CHAINS

PROGRAMME

Plastic slatband chains are available in the following materials:

REXNORD/MCC	
XL	Acetal with low friction, to reduce wear up to 15% over plain acetal; intended for high output applications at moderate to high speeds for general conveying.
LF	Low Friction acetal (POM) and special blend of lubricants. This can reduce wear up to 15% over plain acetal; it is intended for high output applications at moderate to high speeds for general conveying.
HP	High Performance internally lubricated acetal (POM), capable of reducing wear up to 40% over plain acetal; intended for dry running or reduced lubrication and high-speed applications.
PS	Platinum Series internally lubricated acetal (POM). It can decrease wear by 5 times. PV-limits are increased, which means that a sideflexing chain moulded in PS can run 2 times faster than the same chain in acetal and 1.5 times faster than in HP. PET bottles running on PS chains exhibit the lowest friction available, to reduce product backline pressure and minimize pulsations.
WX	Polyamide composite to extend chain wear life in abrasive circumstances up to five times compared to acetal materials; to be used in glass handling applications where abrasive shards of glass can wear other plastic chain materials rapidly; it is also applicable when the chain is subjected to sand and dirt.
DKA	Aramide reinforced acetal (POM) for wet or dry abrasive conditions, offering enhanced wear properties over plain acetals in combination with the low friction of a lubricated material. This material is available on request for a selected range of TableTop products.

Anti-static and chemical resistant materials can be supplied for a limited number of chains. Please ask Customer Service for more details.

CHAIN MATERIAL	APPLICATION				
	Mass handling	Inliner standard	Inliner / PET / high-speed	Abrasive wet	Abrasive dry
XL					
LF					
HP					
PS					
WX					
DKA					


Best choice

Optional

PLASTIC TABLETOP CHAINS



**STRAIGHT RUN
SINGLE HINGE**



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
SH 250 XL	750.42.22	63.5	2.50	0.69	1230	50	4.0
SH 325 XL	750.42.31	82.5	3.25	0.82			
SH 84 XL	750.42.35	83.8	3.30	0.82			
SH 350 XL	750.42.32	88.9	3.50	0.87			
SH 400 XL	750.42.40	101.6	4.00	0.95			
SH 450 XL	750.42.42	114.3	4.50	1.00			
SH 600 XL	750.42.60	152.4	6.00	1.20			
SH 750 XL	750.42.72	190.5	7.50	1.44			
LF-ACETAL							
LF 820-K250	L0820667731	63.5	2.50	0.73	1230	50	4.0
LF 820-K325	L0820603761	82.5	3.25	0.83			
LF 820-K325 plastic pin*	L0820613711	82.5	3.25	0.63	1200		
LF 820-K343	L0820666361	87.0	3.43	0.85	1230		
LF 820-K350	L0820603771	88.9	3.50	0.87			
LF 820-K400	L0820603781	101.6	4.00	0.95			
LF 820-K450	L0820603791	114.3	4.50	1.03			
LF 820-K450 plastic pin*	L0820645211	114.3	4.50	0.83	1200		
LF 820-K600	L0820603801	152.4	6.00	1.25	1230		
LF 820-K750	L0820603811	190.5	7.50	1.47			
HP-ACETAL							
HP 820-K325	L0820613041	82.5	3.25	0.83	1230	50	4.0
HP 820-K343	L0820670561	87.0	3.43	0.85			
HP 820-K350	L0820669071	88.9	3.50	0.87			
HP 820-K400	L0820649231	101.6	4.00	0.95			
HP 820-K450	L0820613051	114.3	4.50	1.03			
HP 820-K600	L0820613061	152.4	6.00	1.25			
HP 820-K750	L0820613071	190.5	7.50	1.47			
PS-ACETAL							
SH 325 PS	750.10.03	82.5	3.25	0.82	1230	50	4.0
PS 820-K325	L0820605513	82.5	3.25	0.82			
SH 84 PS	750.10.04	83.8	3.30	0.82			
SH 450 PS	750.10.11	114.3	4.50	1.00			
PS 820-K450	L0820605523	114.3	4.50	1.00			
SH 750 PS	750.10.09	190.5	7.50	1.44			
WX-POLYAMIDE COMPOSITE							
SH 325 WX	750.10.05	82.5	3.25	0.83	1230	50	4.0
WX 820-K325	L0820646071	82.5	3.25	0.83			
WX 820-K450	L0820616412	114.3	4.50	1.03			
WX 820-K600	L0820606583	152.4	6.00	1.25			
WX 820-K750	L0820670542	190.5	7.50	1.47			


* Pins made of black reinforced polyamide for non-magnetic or chemical applications. Ask customer service for minimum order quantity.

Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS




**STRAIGHT RUN
SINGLE HINGE
SIDEFLEX JOINT HINGE**



Chain type	Code nr.	Plate width		Weight	Working load load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
SHP 325 XL	750.10.22	82.5	3.25	0.94	2100	50	4.0
SHP 84 XL	750.12.35	83.8	3.30	0.94			
PS-ACETAL							
SHP 325 PS	750.10.23	82.5	3.25	0.94	2100	50	4.0
SHP 84 PS	750.10.01	83.8	3.30	0.94			



**STRAIGHT RUN
SINGLE HINGE
WITH THICK TOP PLATE**




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
SHD 325 XL	750.92.31	82.5	3.25	0.87	1230	50	4.8
SHD 450 XL	750.92.42	114.3	4.50	1.06			
SHD 750 XL	750.92.72	190.5	7.50	1.53			
LF-ACETAL							
LF 831-K325	L0831603821	82.5	3.25	0.83	1230	50	4.8
LF 831-K450	L0831603831	114.3	4.50	1.03			
LF 831-K750	L0831603841	190.5	7.50	1.47			
HP-ACETAL							
HP 831-K325	L0831613261	82.5	3.25	0.83	1230	50	4.8
HP 831-K450	L0831613271	114.3	4.50	1.03			
HP 831-K750	L0831613281	190.5	7.50	1.47			
PS-ACETAL							
SHD 325 PS	750.10.02	82.5	3.25	0.87	1230	50	4.8
WX-POLYAMIDE COMPOSITE							
WX 831-K325	L0831603533	82.5	3.25	0.87	1230	50	4.8
WX 831-K450	L0831676362	114.3	4.50	1.06			

Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS



**STRAIGHT RUN
DOUBLE HINGE**




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
SWH 750 XL	750.72.77	190.5	7.50	2.48	2680	50	4.8
SWH 1000 XL	750.72.91	254.0	10.00	2.82			
SWH 1200 XL	750.72.92	304.8	12.00	3.12			
LF-ACETAL							
LF 821-K750	L0821603931	190.5	7.50	2.50	2680	50	4.8
LF 821-K1000	L0821603941	254.0	10.00	2.95			
LF 821-K1200	L0821603951	304.8	12.00	3.25			
HP-ACETAL							
HP 821-K750	L0821613161	190.5	7.50	2.50	2680	50	4.8
HP 821-K1000	L0821613171	254.0	10.00	2.95			
HP 821-K1200	L0821613181	304.8	12.00	3.25			
PS-ACETAL							
SWH 750 PS	750.10.08	190.5	7.50	2.48	2680	50	4.8
WX-POLYAMIDE COMPOSITE							
WX 821-K750	L0821602503*	190.5	7.50	2.50	2680	50	4.8

Standard length: 3.048 m - 10 feet (80 links). * Ask customer service for minimum order quantity.



**STRAIGHT RUN
HEAVY DUTY**




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
HDS 750 XL	752.62.72	190.5	7.50	2.16	3830	50	4.8
HDS 1000 XL	752.62.90	254.0	10.00	2.42			
HDS 1200 XL	752.62.92	304.8	12.00	2.69			

Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS



MAGNETFLEX®




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XL-ACETAL								
RHMP 325 XL	781.10.07	82.5	3.25	0.82	500	2100	50	4.0
RHMP 84 XL	781.10.13	83.8	3.30	0.82				
RHM 350 XL	781.12.32	88.9	3.50	1.10	457			
RHM 450 XL	781.12.42	114.3	4.50	1.16				
PS-ACETAL								
RHMP 325 PS	781.10.08	82.5	3.25	0.82	500	2100	50	4.0
RHMP 84 PS	781.10.14	83.8	3.30	0.82				
WX-POLYAMIDE COMPOSITE								
RHMP 84 WX	781.10.15	83.8	3.30	0.82	500	2100	50	4.0
HP-ACETAL								
RHMP 325 HP	781.10.20	82.5	3.25	0.82	500	2100	50	4.0

Standard length: 3.048 m - 10 feet (80 links)




**MAGNETFLEX®
WITH THICK TOP PLATE**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch					
XL-ACETAL								
RHMDP 325 XL	781.10.10	82.5	3.25	1.08	500	2100	50	4.8
RHMD 450 XL	781.22.42	114.3	4.50	1.26	457			
PS-ACETAL								
RHMDP 325 PS	781.10.11	82.5	3.25	0.87	500	2100	50	4.8


Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	N (21°C)	mm	mm	mm
XL-ACETAL								
HDFM 750 XL	751.32.72	190.5	7.50	2.16	3830	50	610	4.8
HDFM 1000 XL	751.32.90	254.0	10.00	2.42				
HDFM 1200 XL	751.32.92	304.8	12.00	2.69				

Standard length: 3.048 m - 10 feet (80 links)




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 880-K325	L0880603981	82.5	3.25	0.89	457	2100	40	4.0
LF 880-K450	L0880603991	114.3	4.50	1.04				
WX-POLYAMIDE COMPOSITE								
WX 880-K325	L0880639072	82.5	3.25	0.89	457	2100	40	4.0
WX 880-K450	L0880616002	114.3	4.50	1.04				

Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS



**STANDARD RADIUS
SINGLE HINGE BEVEL
WITH THICK TOP PLATE**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 879-K325	LF879K3-1/4	82.5	3.25	0.89	457	2100	40	4.8
LF 879-K450	LF879K4-1/2	114.3	4.50	1.04				
WX-POLYAMIDE COMPOSITE								
WX 879-K450	81428412	114.3	4.50	1.04	457	2100	40	4.8

Standard length: 3.048 m - 10 feet (80 links)



**SIDEFLEX
BEVEL
HEAVY DUTY**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 882-K450	LF882K4-1/2*	114.3	4.50	1.94	610	3830	40	4.8
LF 882-K750	LF882K7-1/2*	190.5	7.50	2.38				
LF 882-K1000	LF882K10	254.0	10.00	2.83				


Standard length: 3.048 m - 10 feet (80 links)

* Ask customer service for minimum order quantity.

PLASTIC TABLETOP CHAINS



**STANDARD RADIUS
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	N (21°C)	mm	mm	mm
XL-ACETAL								
RH 325 XL	751.42.31	82.5	3.25	0.94	457	2100	50	4.0
RH 450 XL	751.42.42	114.3	4.50	1.08				
LF-ACETAL								
LF 880 TAB-K325	L0880604031	82.5	3.25	0.94	457	2100	40	4.0
LF 880 TAB-K325 plastic pin*	L0880632221	82.5	3.25	0.74		1050		
LF 880 TAB-K325 non-magnetic pin**	L0880683712	82.5	3.25	0.94		2100		
LF 880 TAB-K343	L0880667941	87.0	3.43	1.01				
LF 880 TAB-K350	L0880641151	88.9	3.50	1.01				
LF 880 TAB-K450	L0880604041	114.3	4.50	1.08	500			
LF 880 TAB-K450 plastic pin*	L0880648371	114.3	4.50	0.91				
LF 880 TAB-K450 non-magnetic pin**	L0880605273	114.3	4.50	1.08	2100			
PS-ACETAL								
RH 325 PS	751.10.03	82.5	3.25	0.94	457	2100	40	4.0
PS 880 TAB-K325	L0880606723	82.5	3.25	0.94				
PS 880 TAB-K325 non-magnetic pin**	L0880612863	82.5	3.25	0.94				
PS 880 TAB-K343	L0880616043	87.0	3.43	1.01	500			
PS 880 TAB-K450	L0880608503	114.3	4.50	1.08				
PS 880 TAB-K450 non-magnetic pin**	L0880620573	114.3	4.50	1.08				
WX-POLYAMIDE COMPOSITE								
WX 880 TAB-K325	L0880613512	82.5	3.25	0.94	457	2100	40	4.0
WX 880 TAB-K450	L0880639662	114.3	4.50	1.08	500			
HP-ACETAL								
HP 880 TAB-K325	L0880613141	82.5	3.25	0.94	457	2100	40	4.0
HP 880 TAB-K325 non-magnetic pin**	L0880613093	82.5	3.25	0.94				
HP 880 TAB-K450	L0880613151	114.3	4.50	1.08	500			
HP 880 TAB-K450 non-magnetic pin**	L0880620563	114.3	4.50	1.08				

* Pins made of black reinforced polyamide for non-magnetic or chemical applications. Ask customer service for minimum order quantity.


** Pins made of stainless steel for non-magnetic applications.

Standard length: 3.048 m - 10 feet (80 links)

PLASTIC TABLETOP CHAINS



**STANDARD RADIUS
SINGLE HINGE TAB
WITH THICK TOP PLATE**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XL-ACETAL								
RHD 325 XL	751.62.31	82.5	3.25	0.98	457	2100	50	4.8
RHD 450 XL	751.62.42	114.3	4.50	1.14	610			
LF-ACETAL								
LF 879 TAB-K325	L0879604071	82.5	3.25	0.98	457	2100	40	4.8
LF 879 TAB-K450	L0879604081	114.3	4.50	1.14	610			
WX-POLYAMIDE COMPOSITE								
WX 879 TAB-K450	L0879676002	114.3	4.50	1.14	610	2100	40	4.8

Standard length: 3.048 m - 10 feet (80 links)



PLASTIC TABLETOP CHAINS





Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 880 TAB BO-K325	L0880604061	82.5	3.25	0.96	190	1680	40	4.0
LF 880 TAB BO-K450	L0880688981	114.3	4.50	1.11				
HP-ACETAL								
HP 880 TAB BO-K325	L0880649241	82.5	3.25	0.96	190	1680	40	4.0
HP 880 TAB BO-K450	81410922	114.3	4.50	1.11				
WX-POLYAMIDE COMPOSITE								
WX 880 TAB BO-K325	L0880699072*	82.5	3.25	0.96	190	1680	40	4.0

Standard length: 3.048 m - 10 feet (80 links)

* Ask customer service for minimum order quantity.

PLASTIC TABLETOP CHAINS




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 879 TAB BO-K325	L0879605412	82.5	3.25	1.08	190	2100	40	4.8
LF 879 TAB BO-K450	L0879605422	114.3	4.50	1.20				
HP-ACETAL								
HP 879 TAB BO-K325	L0879621823	82.5	3.25	1.08	190	2100	40	4.8
HP 879 TAB BO-K450	L0879615683	114.3	4.50	1.20				
WX-POLYAMIDE COMPOSITE								
WX 879 TAB BO-K325	L0879690932*	82.5	3.25	1.08	190	2100	40	4.8
WX 879 TAB BO-K450	L0879621043*	114.3	4.50	1.20				

Standard length: 3.048 m - 10 feet (80 links).

* Ask customer service for minimum order quantity.




PLASTIC TABLETOP CHAINS



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XL-ACETAL								
HDF 450 XL	751.82.42	114.3	4.50	1.96	610	3830	50	4.8
HDF 750 XL	751.82.72	190.5	7.50	2.38				
HDF 1000 XL	751.82.90	254.0	10.00	2.69				
HDF 1200 XL	751.82.92	304.8	12.00	2.94				

Standard length: 3.048 m - 10 feet (80 links)



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 882 TAB-K325	81402575*	82.5	3.25	1.86	610	3830	40	4.8
LF 882 TAB-K450	L0882604141	114.3	4.50	1.98				
LF 882 TAB-K750	L0882604151	190.5	7.50	2.43				
LF 882 TAB-K1000	L0882604161	254.0	10.00	2.87				
LF 882 TAB-K1200	L0882604171	304.8	12.00	3.41				


Standard length: 3.048 m – 10 feet (80 links)

* Ask customer service for minimum order quantity.

PLASTIC VACUUM CHAINS



**STRAIGHT RUN
VACUUM**



Chain type	Code nr.	Plate width		Weight	Distance between holes B	Hole diameter d1	Working load (max.)	Backflex radius (min.)	Plate thickness
		A							
		mm	inch	kg/m	mm	mm	N (21°C)	mm	mm
LF-ACETAL									
LF 820-K325 V2**	L0820638301	82.5	3.25	0.83	19	6.5	1230	40	4.0
LF 820-K350 V2**	L0820692431	88.9	3.50	0.87	45	4.0			
LF 820-K450 V2 I30**	L0820613392	114.3	4.50	1.03	30	8.0			
LF 820-K450 V2 I50**	L0820670221	114.3	4.50	1.03	50	8.0			
LF 820-K325 V3***	L0820615961	82.5	3.25	0.83	20	7.9			


** 2 holes

*** 3 holes. Hole diameter 3rd hole (d2) is 4.4 mm

Standard length: 3.048 m - 10 feet (80 links)



**SIDEFLEX
TAB
VACUUM**



Chain type	Code nr.	Plate width		Weight	Distance between holes B	Hole diameter d1	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A								
		mm	inch	kg/m	mm	mm	mm	N (21°C)	mm	mm
LF-ACETAL										
LF 880 TAB-K325 V1 D6,5*	L0880655912	82.5	3.25	0.94	-	6.5	457	2100	40	4.0
LF 880 TAB-K325 V1 D8*	L0880684591	82.5	3.25	0.94	-	8.0				
LF 880 TAB-K325 V1 D10*	L0880638221	82.5	3.25	0.94	-	10.0				
LF 880 TAB-K325 V2 D6**	L0880647851	82.5	3.25	0.94	24	6.0				
LF 880 TAB-K325 V2 D8**	L0880615331	82.5	3.25	0.94	20	8.0	500			
LF 880 TAB-K450 V2 D6**	L0880647861	114.3	4.50	1.08	24	6.0				

* 1 hole

** 2 holes


Standard length: 3.048 m - 10 feet (80 links)

* Ask customer service for minimum order quantity of vacuum chains.

PLASTIC SPECIAL CHAINS



**SIDEFLEX
TAB
WITH FLIGHTS**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 880 TAB BO-K325 F25*	L0880609792	82.5	3.25	0.96	190	1680	40	4.0
LF 880 TAB BO-K325 F39**	L0880698801	82.5	3.25	0.96				

* Height of flight (B) 25 mm


** Height of flight (B) 39 mm

Standard length: 3.048 m - 10 feet (80 links)

As a standard flights on every second link; other patterns are possible.



**SIDEFLEX
TAB
WITH FLANGES**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LF 880 TAB-K454	L0880604051	115.3	4.54	1.12	610	2100	100	4.0


Standard length: 3.048 m - 10 feet (80 links)

* Ask customer service for minimum order quantity of these special chains.

PLASTIC SPECIAL CHAINS



**STRAIGHT RUN
MINIATURE**



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
D-ACETAL							
ZN 1108*	L1108WZN	32.0	1.26	0.51	800	21	12.0
SS 1108**	L1108WSS						


* With zinc plated pins
** With stainless steel pins

Standard length: 5 m - 16.4 feet (395 links).

These chains are recommended for packaging machines of pharmaceutical, cosmetic and food products; if installed to the base chain, it facilitates product head transfers.



**SIDEFLEX
ARTICULATED
WITH TOP PLATES**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
D-ACETAL								
W 1080 SS	L1080WSS	85.0	3.35	1.76	83	3950	–	5.9



Standard length: 8 m - 26.2 feet (128 links).

This chain is recommended for closed ring transport due to the lateral traction drive.

PLASTIC TABLETOP CHAINS WITH RUBBER TOP



**STRAIGHT RUN
SINGLE HINGE**





Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
LF-ACETAL							
HFP 820-K325	L0820688461	82.5	3.25	0.83	1230	40	4.0
HFP 820-K400	L0820610152	101.6	4.00	0.95			
HFP 820-K450	L0820606852	114.3	4.50	1.03			
HFP 820-K600	L0820610172	152.4	6.00	1.25			

Standard length: 3.048 m - 10 feet (80 links)

The width (B) of the rubber varies per chain type:
65.0, 101.6, 114.3 and 135.0 for respectively HFP 820-K325, HFP 820-K400, HFP 820-K450 and HFP 820-K600.



**STRAIGHT RUN
DOUBLE HINGE
RUBBER PUSHERS**





Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
LF-ACETAL							
HFP 821-K750 F	L0821609752	190.5	7.50	2.43	2680	70	4.8
HFP 821-K1000 F	L0821609762	254.0	10.00	2.85			
HFP 821-K1200 F	L0821609772	304.8	12.00	3.17			

Standard length: 3.048 m - 10 feet (80 links)

The width (B) of the pushers varies per chain type:
151, 214 and 265 mm for respectively HFP 821-K750 F, HFP 821-K1000 F and HFP 821-K1200 F.

* Ask customer service for minimum order quantity of HFP chains.



PLASTIC TABLETOP CHAINS WITH RUBBER TOP



Chain type	Code nr.	Plate width		Weight	Working load load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
PBT							
SWH 750 SG	780.11.77	190.5	7.50	2.29	2680	50	4.8
SWH 1000 SG	780.11.90	254.0	10.00	2.67			
SWH 1200 SG	780.11.92	304.8	12.00	3.06			

Standard length: 3.048 m - 10 feet (80 links)

The width (G) of the moulded-in rubber top varies per chain type:
134, 192.1 and 252.5 mm for respectively SWH 750 SG, SWH 1000 SG and SWH 1200 SG.




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
LF-ACETAL							
HFP 821-K750	L0821683171	190.5	7.50	2.50	2680	40	4.8
HFP 821-K1000	L0821688301	254.0	10.00	2.95			
HFP 821-K1200	L0821688511	304.8	12.00	3.25			

Standard length: 3.048 m - 10 feet (80 links)

The width (B) of the rubber varies per chain type:
132, 195 and 245 mm for respectively HFP 821-K750, HFP 821-K1000 and HFP 821-K1200.

* Ask customer service for minimum order quantity of HFP chains.


PLASTIC TABLETOP CHAINS WITH RUBBER TOP



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
PBT							
HDS 450 SG	780.31.42	114.3	4.50	1.70	2700	50	4.8
HDS 750 SG	780.31.72	190.5	7.50	2.10			
HDS 1000 SG	780.31.90	254.0	10.00	2.42			
HDS 1200 SG	780.31.92	304.8	12.00	2.69			

Standard length: 3.048 m - 10 feet (80 links)

The width (G) of the moulded-in rubber top varies per chain type:
92, 134, 192 and 252.5 mm for respectively HDS 450 SG, HDS 750 SG, HDS 1000 SG and HDS 1200 SG.



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
PBT								
HDFM 750 SG	780.21.72	190.5	7.50	2.10	610	2700	50	4.8
HDFM 1000 SG	780.21.90	254.0	10.00	2.42				
HDFM 1200 SG	780.21.92	304.8	12.00	2.69				


Standard length: 3.048 m - 10 feet (80 links)

The width (G) of the moulded-in rubber top varies per chain type:
134, 192 and 251 mm for respectively HDFM 750 SG, HDFM 1000 SG and HDFM 1200 SG.

PLASTIC TABLETOP CHAINS WITH RUBBER TOP



**STANDARD RADIUS
HEAVY DUTY
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
HFP 882 TAB-K750	L0882691681	190.5	7.50	2.43	610	3830	40	4.8
HFP 882 TAB-K1000	L0882692981	254.0	10.00	2.87				
HFP 882 TAB-K1200	L0882691811	304.8	12.00	3.41				

Standard length: 3.048 m - 10 feet (80 links)


The width (B) of the rubber varies per chain type:

132, 195 and 246 mm for respectively HFP 882 TAB-K750, HFP 882 TAB-K1000 and HFP 882 TAB-K1200.

Other rubber patterns and materials are possible.



**STANDARD RADIUS
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
HFP 880 TAB-K325	L0880691121	82.5	3.25	0.94	457	2100	40	4.0
HFP 880 TAB-K450	L0880684291	114.3	4.50	1.08	500			

Standard length: 3.048 m - 10 feet (80 links).

The width (B) of the rubber varies per chain type:

65 and 95 mm for respectively HFP 880 TAB-K325 and HFP 880 TAB-K450.


Other rubber patterns and materials are possible.

* Ask customer service for minimum order quantity of HFP chains.

PLASTIC TABLETOP CHAINS WITH RUBBER TOP



**SMALL RADIUS
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	N (21°C)	mm	mm	mm
LF-ACETAL								
HFP 879 TAB BO-K325	L0879618812	82.5	3.25	1.08	2100	40	190	4.8
HFP 879 TAB BO-K450	L0879605452	114.3	4.50	1.20				


Standard length: 3.048 m - 10 feet (80 links)

The width (B) of the rubber varies per chain type:
71 and 102 mm for respectively HFP 879 TAB BO-K325 and HFP 879 TAB BO-K450.

Other rubber patterns and materials are possible.



**SMALL RADIUS
SINGLE HINGE TAB**



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	N (21°C)	mm	mm	mm
LF-ACETAL								
HFP 880 TAB BOT-K325	L0880605222	82.5	3.25	0.96	1680	40	190	4.0

Standard length: 3.048 m - 10 feet (80 links)

The width (B) of the rubber is 65 mm.


Other rubber patterns and materials are possible.

* Ask customer service for minimum order quantity of HFP chains.

PLASTIC TABLETOP LBP CHAINS



**STRAIGHT RUN
SINGLE HINGE
LBP**




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XLA-ACETAL							
SHD 325 LBP	752.85.09	82.5	3.25	2.20	1230	400	4.8

Standard length: 1.524 m - 5 feet (40 links)




**STRAIGHT RUN
DOUBLE HINGE
LBP**



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XLA-ACETAL							
SWH 750 LBP	752.82.09	190.5	7.50	5.30	2680	300	4.8
SWH 1000 LBP	752.82.11	254.0	10.00	6.60			
SWH 1200 LBP	752.82.10	304.8	12.00	7.85			



Standard length: 1.524 m - 5 feet (40 links)

PLASTIC TABLETOP LBP CHAINS



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XLA-ACETAL							
HDS 750 LBP	752.81.13	190.5	7.50	4.28	3830	200	4.8

Standard length: 1.524 m - 5 feet (40 links)




Chain type	Code nr.	Plate width		Weight	Working load load (max.)	Backflex radius (min.)	Plate thickness
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XLA-ACETAL							
HDS 1000 LBP	752.81.19	254.0	10.00	5.23	3830	200	4.8
HDS 1200 LBP	752.81.20	304.8	12.00	5.83			

Standard length: 1.524 m - 5 feet (40 links)


* Ask customer service for minimum order quantity of sprockets with inch bores

PLASTIC TABLETOP LBP CHAINS



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLA-ACETAL								
RHMD 325 LBP	752.87.09	82.5	3.25	2.29	500	2100	400	4.8


Standard length: 1.524 m - 5 feet (40 links)



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLA-ACETAL								
HDFM 750 LBP	752.88.13	190.5	7.50	4.28	610	3830	200	4.8
HDFM 1000 LBP	752.88.19	254.0	10.00	5.23				
HDFM 1200 LBP	752.88.20	304.8	12.00	5.83				


Standard length: 1.524 m - 5 feet (40 links)

PLASTIC TABLETOP LBP CHAINS



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (min.)	Backflex radius (max.)	Plate thickness (min.)
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
LF-ACETAL								
LBP 883 TAB-K450	LBP883TK4.5	114.3	4.50	2.50	610	3830	51	4.8
LBP 883 TAB-K750	LBP883TK7.5	190.5	7.50	3.40				

Standard length: 3.048 m - 10 feet (80 links)



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch					
LF-ACETAL								
LBP 879 TAB BO-K325	L0879605482	82.5	3.25	1.08	200	2100	100	4.8


Standard length: 3.048 m - 10 feet (80 links)

*Ask customer service for minimum order quantity of LBP 879 and 883 chains.

PLASTIC TABLETOP LBP CHAINS



**SIDEFLEX
HEAVY DUTY TAB
LBP**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch					
XLA-ACETAL								
HDF 375 LBP	752.89.09	95.3	3.75	3.30	667	3830	200	4.8

Standard length: 1.524 m - 5 feet (40 links)



**SIDEFLEX
HEAVY DUTY TAB
LBP**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLA-ACETAL								
HDF 750 LBP	752.89.13	190.5	7.50	4.50	610	3830	200	4.8
HDF 1000 LBP	752.89.19	254.0	10.00	5.71				
HDF 1200 LBP	752.89.20	304.8	12.00	6.38	680			

Standard length: 1.524 m - 5 feet (40 links)

CHAINBELTS



**FLUSH GRID
MAGNETFLEX®
1050**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLG-ACETAL								
FGM 1050 XLG	749.11.31	83.8	3.30	1.54	500	1650	130	8.7
PS-ACETAL								
FGM 1050 PS	749.10.11	83.8	3.30	1.54	500	1650	130	8.7

Standard length: 3.048 m - 10 feet (120 links).




CHAINBELTS



Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLG-ACETAL								
FTM 1060 XLG	749.10.06	83.8	3.30	1.68	500	1900	130	8.7
PS-ACETAL								
FTM 1060 PS	749.10.07	83.8	3.30	1.68	500	1900	130	8.7
WX-POLYAMIDE COMPOSITE								
FTM 1060 WX	749.10.08	83.8	3.30	1.68	500	1900	130	8.7

Standard length: 3.048 m - 10 feet (120 links).




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLG-ACETAL								
FTM 1055 XLG K330	749.41.31	83.8	3.30	1.90	500	2200	130	12.7
FTM 1055 XLG K450	749.41.42	114.3	4.50	2.20				
PS-ACETAL								
FTM 1055 PS K330	749.10.10	83.8	3.30	1.90	500	2200	130	12.7
WX-POLYAMIDE COMPOSITE								
FTM 1055 WX K330	749.49.31	83.8	3.30	1.90	500	2200	130	12.7
FTM 1055 WX K450	749.10.25	114.3	4.50	2.20				

Standard length: 3.048 m - 10 feet (120 links).

CHAINBELTS



**FLAT TOP
1050
TAB**




Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLG-ACETAL								
FT 1050 XLG	749.61.31	83.8	3.30	1.93	500	1650	130	8.7
PS-ACETAL								
FT 1050 PS	749.10.12	83.8	3.30	1.93	500	1650	130	8.7

Standard length: 3.048 m - 10 feet (120 links).



**FLAT TOP
1055
TAB**





Chain type	Code nr.	Plate width		Weight	Sideflex radius (min.)	Working load (max.)	Backflex radius (min.)	Plate thickness
		A						
		mm	inch	kg/m	mm	N (21°C)	mm	mm
XLG-ACETAL								
FT 1055 XLG K330	749.71.31	83.8	3.30	2.13	500	2200	130	12.7

Standard length: 3.048 m - 10 feet (120 links).


SPROCKETS FOR TABLETOP CHAINS

Nominal dimensions of the key according ISO 773; keyway tolerances in plastic sprockets may differ from ISO 773 due to material properties.


Idler sprockets and drums are optimised for shafts with diameter tolerance of h9.

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm			
									MATERIAL page 209		
SPLIT SPROCKETS, INJECTION MOULDED - NS 815											
METRIC BORES											
NS815 21-25	L0815663881	21	25	129.3	129.5	52.0	51.0	60			
NS815 21-30	L0815663891	21	30								
NS815 21-35	L0815663901	21	35								
NS815 21-40	L0815663911	21	40								
NS815 21-45	L0815663921	21	45								
NS815 23-25	L0815662481	23	25	141.2	142.0	52.0	51.0				
NS815 23-30	L0815662491	23	30								
NS815 23-35	L0815662501	23	35								
NS815 23-40	L0815662511	23	40								
NS815 23-45	L0815662521	23	45								
NS815 25-25	L0815665331	25	25	153.2	154.2	54.0	58.5				
NS815 25-30	L0815665311	25	30								
NS815 25-35	L0815665341	25	35								
NS815 25-40	L0815664931	25	40								
NS815 25-45	L0815665351	25	45								
INCH BORES											
NS815 21-1	L0815663931	21	1.00"	129.3	129.5	52.0	51.0	60			
NS815 21-1 1/4	L0815663991	21	1.25"								
NS815 23-1	L0815662661	23	1.00"	141.2	142.0	52.0	51.0				
NS815 23-1 1/4	L0815662701	23	1.25"								
NS815 25-1	L0815665411	25	1.00"	153.2	154.2	54.0	58.5				
NS815 25-1 1/4	L0815665451	25	1.25"								
NS815 25-1 1/2	L0815665491	25	1.50"								
For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex. Note: not for heavy duty tab * Ask customer service for minimum order quantity											
SPLIT SPROCKETS, INJECTION MOULDED - NS 815											
METRIC LARGE BORES											
NS815 29-75	L0815660911	29	75	177.2	179.0	52.0	40.0	105			
NS815 29-87	L0815660921	29	87								
For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex. Note: not for heavy duty tab This 29 tooth sprocket doesn't use a keyway, but a 12 mm round pin mounted through the shaft.											
											



SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm	MATERIAL page 209
SPLIT SPROCKETS AND IDLERS, MACHINED - KUS 815									
SPROCKETS, METRIC BORES									
KUS815 17-25	753.62.11	17	25	105.5	104.5	40.0	40.0	-	 
KUS815 17-30	753.62.21	17	30						
KUS815 17-35	753.62.31	17	35						
KUS815 17-40	753.62.41	17	40	117.3	116.3				
KUS815 19-25	753.62.12	19	25						
KUS815 19-30	753.62.22	19	30						
KUS815 19-35	753.62.32	19	35						
KUS815 19-40	753.62.42	19	40						
KUS815 19-50	753.62.62	19	50	129.3	130.0				
KUS815 21-25	753.62.13	21	25						
KUS815 21-30	753.62.23	21	30						
KUS815 21-35	753.62.33	21	35						
KUS815 21-40	753.62.43	21	40						
KUS815 21-50	753.62.63	21	50	141.2	141.9				
KUS815 23-25	753.62.14	23	25						
KUS815 23-30	753.62.24	23	30						
KUS815 23-35	753.62.34	23	35						
KUS815 23-40	753.62.44	23	40						
KUS815 23-50	753.62.64	23	50	153.2	153.9				
KUS815 25-25	753.62.15	25	25						
KUS815 25-30	753.62.25	25	30						
KUS815 25-35	753.62.35	25	35						
KUS815 25-40	753.62.45	25	40						
KUS815 25-50	753.62.65	25	50	165.2	165.9				
KUS815 27-25	753.62.16	27	25						
KUS815 27-30	753.62.26	27	30						
KUS815 27-35	753.62.36	27	35						
KUS815 27-40	753.62.46	27	40						
KUS815 27-50	753.62.66	27	50						
IDLERS, METRIC BORES									
KUS815 17-25	753.61.11	17	25	105.5	104.5	40.0	40.0	-	
KUS815 17-30	753.61.21	17	30						
KUS815 17-35	753.61.31	17	35						
KUS815 17-40	753.61.41	17	40						
KUS815 19-25	753.61.12	19	25						
KUS815 19-30	753.61.22	19	30						
KUS815 19-35	753.61.32	19	35						
KUS815 19-40	753.61.42	19	40						
KUS815 19-50	753.61.62	19	50	129.3	130.0				
KUS815 21-25	753.61.13	21	25						
KUS815 21-30	753.61.23	21	30						
KUS815 21-35	753.61.33	21	35						
KUS815 21-40	753.61.43	21	40						
KUS815 21-50	753.61.63	21	50	141.2	141.9				
KUS815 23-25	753.61.14	23	25						
KUS815 23-30	753.61.24	23	30						
KUS815 23-35	753.61.34	23	35						
KUS815 23-40	753.61.44	23	40						
KUS815 23-50	753.61.64	23	50	153.2	153.9				
KUS815 25-25	753.61.15	25	25						
KUS815 25-30	753.61.25	25	30						
KUS815 25-35	753.61.35	25	35						
KUS815 25-40	753.61.45	25	40						
KUS815 25-50	753.61.65	25	50	165.2	165.9				
KUS815 27-25	753.61.16	27	25						
KUS815 27-30	753.61.26	27	30						
KUS815 27-35	753.61.36	27	35						
KUS815 27-40	753.61.46	27	40						
KUS815 27-50	753.61.66	27	50						
For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex, 66 ST 75 RM									

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore	Pitch diameter	Outside diameter	Width (Teeth)	Hub width	Hub diameter	MATERIAL page 209
			B	E	F	C	A	H	
			mm	mm	mm	mm	mm	mm	
CLASSIC SPROCKETS, MACHINED - KU 815									
METRIC BORES									
KU815 17-20	753.91.77	17	20*	105.5	104.5	40	-	-	
KU815 19-20	753.91.78	19	20*	117.3	116.3				
KU815 21-20	753.91.79	21	20*	129.3	130.0				
KU815 23-20	753.91.80	23	20*	141.2	141.9				
KU815 25-20	753.91.81	25	20*	153.2	153.9				
KU815 27-20	753.91.82	27	20*	165.2	165.9				
*Pre-bore For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex, 66 ST 75 RM 									

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm	
									MATERIAL page 209
SPLIT SPROCKETS, INJECTION MOULDED - NS 820									
METRIC BORES									 
NS820 21-25	L0820664341	21	25	129.3	129.5	52.0	51.0	60	
NS820 21-30	L0820664351	21	30	129.3	129.5	52.0	51.0		
NS820 21-35	L0820664361	21	35	129.3	129.5	52.0	51.0		
NS820 21-40	L0820664371	21	40	129.3	129.5	52.0	51.0		
NS820 21-45	L0820664381	21	45	129.3	129.5	52.0	51.0		
NS820 23-25	L0820662531	23	25	141.2	142.0	52.0	51.0		
NS820 23-30	L0820662541	23	30	141.2	142.0	52.0	51.0		
NS820 23-35	L0820662551	23	35	141.2	142.0	52.0	51.0		
NS820 23-40	L0820662561	23	40	141.2	142.0	52.0	51.0		
NS820 23-45	L0820662571	23	45	141.2	142.0	52.0	51.0		
NS820 25-25	L0820665361	25	25	153.2	154.2	54.0	58.5		
NS820 25-30	L0820665371	25	30	153.2	154.2	54.0	58.5		
NS820 25-35	L0820665381	25	35	153.2	154.2	54.0	58.5		
NS820 25-40	L0820665391	25	40	153.2	154.2	54.0	58.5		
NS820 25-45	L0820665401	25	45	153.2	154.2	54.0	58.5		
INCH BORES*									60
NS820 21-1	L0820664391	21	1.00"	129.3	129.5	52.0	51.0		
NS820 21-1 1/4	L0820664411	21	1.25"	129.3	129.5	52.0	51.0		
NS820 23-1	L0820662741	23	1.00"	141.2	142.0	52.0	51.0		
NS820 23-1 1/4	L0820662761	23	1.25"	141.2	142.0	52.0	51.0		
NS820 25-1	L0820665611	25	1.00"	153.2	154.2	54.0	58.5		
NS820 25-1 1/4	L0820665631	25	1.25"	153.2	154.2	54.0	58.5		
For steel chain series (optional): Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex For plastic chain series: 820, SH; Note: not suitable for 831 and SHD. *Ask Customer service for minimum order quantity of sprockets with inch bores.									
CLASSIC SPROCKETS, INJECTION MOULDED - N 820									
METRIC BORES									 
N820 15-25	L0820661451	15	25	93.7	92.2	50.0	50.0	43	
N820 15-30	L0820661461	15	30	93.7	92.2	50.0	50.0	43	
N820 17-25	L0820661681	17	25	105.5	104.7	51.0	48.0	43	
N820 17-30	L0820661691	17	30	105.5	104.7	51.0	48.0	43	
N820 19-20	L0820661911	19	20	117.4	117.1	50.0	50.0	60	
N820 19-25	L0820661921	19	25	117.4	117.1	50.0	50.0	60	
N820 19-30	L0820661931	19	30	117.4	117.1	50.0	50.0	60	
N820 19-35	L0820661961	19	35	117.4	117.1	50.0	50.0	60	
N820 19-40	L0820661941	19	40	117.4	117.1	50.0	50.0	60	
For steel chain series (optional): Rexnord: 812 (except TAB and mini hinge), 815 MCC: single hinge straight run, single hinge Magnetflex For plastic chain series: 820, SH; Note: not suitable for 831 and SHD									

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter D	Width (Ring) C	Hub width A	Hub diameter H	
			mm/inch	mm	mm	mm	mm	mm	


MATERIAL

page 209

CLASSIC IDLER DRUMS, INJECTION MOULDED - NXT 820

METRIC BORES

NXT820 15-25	L0820662461	15	25	--	95.5	55.0	92.0	40
NXT820 15-30	L0820662471	15	30	--	95.5	55.0	92.0	40
NXT820 17-25	L0820661701	17	25	--	106.5	53.0	57.0	42
NXT820 17-30	L0820661711	17	30	--	106.5	53.0	57.0	42
NXT820 18-25	L0820661801	18	25	--	113.0	57.0	92.0	40
NXT820 18-30	L0820661811	18	30	--	113.0	57.0	92.0	40
NXT820 19-25	L0820661471	19	25	--	118.0	57.0	57.0	42
NXT820 19-30	L0820661481	19	30	--	118.0	57.0	57.0	42
NXT820 19-40	L0820661491	19	40	--	118.0	57.0	57.0	51
NXT820 21-25	L0820662091	21	25	--	130.0	60.0	61.5	35
NXT820 21-30	L0820662101	21	30	--	130.0	60.0	61.5	40
NXT820 21-35	L0820662121	21	35	--	130.0	60.0	61.5	45
NXT820 21-40	L0820662111	21	40	--	130.0	60.0	61.5	50
NXT820 23-25	L0820661821	23	25	--	142.5	59.5	61.5	35
NXT820 23-30	L0820661831	23	30	--	142.5	59.5	61.5	40
NXT820 23-35	L0820661861	23	35	--	142.5	59.5	61.5	45
NXT820 23-40	L0820661841	23	40	--	142.5	59.5	61.5	50
NXT820 25-25	L0820661721	25	25	--	154.5	59.0	61.5	35
NXT820 25-30	L0820661731	25	30	--	154.5	59.0	61.5	40
NXT820 25-35	L0820661741	25	35	--	154.5	59.0	61.5	45
NXT820 25-40	L0820661751	25	40	--	154.5	59.0	61.5	50



INCH BORES

NXT820 21-1	L0820619132	21	1.00"	--	130.0	60.0	61.5	35
NXT820 21-1¼	L0820688801	21	1.25"	--	130.0	60.0	61.5	40
NXT820 21-1½	L0820688811	21	1.50"	--	130.0	60.0	61.5	45
NXT820 23-1¼	L0820661891	23	1.25"	--	142.5	59.5	61.5	40
NXT820 23-1½	L0820661881	23	1.50"	--	142.5	59.5	61.5	45
NXT820 25-1	L0820619142	25	1.00"	--	154.5	59.0	61.5	35
NXT820 25-1¼	L0820661761	25	1.25"	--	154.5	59.0	61.5	40
NXT820 25-1½	L0820661771	25	1.50"	--	154.5	59.0	61.5	45

For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815, 881 (except TAB), 8811 (except TAB)


MCC: single hinge straight run, single hinge Magnetflex

For plastic chain series: 879-Bevel, 880-Bevel, 820, 831, SH, SHD, RHM, RHMD, RHMP, RHMDP, SHP

SPLIT IDLER DRUMS, INJECTION MOULDED - NSXT 820

METRIC BORES

NSXT 820 21-25	L0820665821	21	25	--	130.0	57.0	61.5	40
NSXT 820 21-30	L0820664861	21	30	--	130.0	57.0	61.5	40
NSXT 820 21-35	L0820664881	21	35	--	130.0	57.0	61.5	50
NSXT 820 21-40	L0820665841	21	40	--	130.0	57.0	61.5	50
NSXT 820 23-25	L0820665861	23	25	--	142.5	57.0	61.5	40
NSXT 820 23-30	L0820665881	23	30	--	142.5	57.0	61.5	40
NSXT 820 23-35	L0820665901	23	35	--	142.5	57.0	61.5	50
NSXT 820 23-40	L0820665921	23	40	--	142.5	57.0	61.5	50
NSXT 820 25-25	L0820665591	25	25	--	154.5	57.0	61.5	40
NSXT 820 25-30	L0820665941	25	30	--	154.5	57.0	61.5	40
NSXT 820 25-35	L0820665961	25	35	--	154.5	57.0	61.5	50
NSXT 820 25-40	L0820664901	25	40	--	154.5	57.0	61.5	50
NSXT 820 25-45	L0820697961	25	45	--	154.5	57.0	61.5	50



INCH BORES*

NSXT 820 21-1	L0820619152	21	1.00"	--	130.0	57.0	61.5	40
NSXT 820 21-1¼	L0820619162	21	1.25"	--	130.0	57.0	61.5	40
NSXT 820 25-1	L0820619172	25	1.00"	--	154.5	57.0	61.5	40
NSXT 820 25-1¼	L0820655612	25	1.25"	--	154.5	57.0	61.5	40
NSXT 820 25-1½	L0820604386	25	1.50"	--	154.5	57.0	61.5	50



For steel chain series: Rexnord: 812 (except TAB and mini hinge), 815, 881 (except TAB), 8811 (except TAB)

MCC: single hinge straight run, single hinge Magnetflex, single hinge bevel rubber top



For plastic chain series: 879-Bevel, 880-Bevel, 820, 831, SH, SHD, RHM, RHMD, RHMP, RHMDP, SHP

*Ask Customer service for minimum order quantity of sprockets with inch bores.



SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F/D mm	Width teeth/ ring mm	Hub width A mm	Hub diameter H mm	MATERIAL page 209
SPLIT SPROCKETS AND IDLERS, MACHINED - SS/SI 75									
SPROCKETS, METRIC BORES									
SS 75 21-25	753.63.61	21	25	129.3	130.0	55.0	55.0	-	
SS 75 21-30	753.63.62	21	30						
SS 75 21-35	753.63.63	21	35						
SS 75 21-40	753.63.64	21	40						
SS 75 21-50	753.63.65	21	50						
SS 75 25-25	753.63.81	25	25	153.2	153.9	55.0	55.0	-	
SS 75 25-30	753.63.82	25	30						
SS 75 25-35	753.63.83	25	35						
SS 75 25-40	753.63.84	25	40						
SS 75 25-50	753.63.85	25	50						
IDLERS, METRIC BORES									
SI 75 21-25	753.63.11	21	25	129.3	130.0	55.0	55.0	-	
SI 75 21-30	753.63.12	21	30						
SI 75 21-35	753.63.13	21	35						
SI 75 21-40	753.63.14	21	40						
SI 75 21-50	753.63.15	21	50						
SI 75 25-25	753.63.31	25	25	153.2	153.9	55.0	55.0	-	
SI 75 25-30	753.63.32	25	30						
SI 75 25-35	753.63.33	25	35						
SI 75 25-40	753.63.34	25	40						
SI 75 25-50	753.63.35	25	50						
For steel chain series: MCC: straight run heavy duty, heavy duty Magnetflex									
SPLIT IDLER DRUMS, MACHINED - SD 75									
METRIC BORES									
SD 75 131-20	754.10.46	21	20	129.3	131.0	84.5	84.5	91	
SD 75 131-25	754.10.47	21	25						
SD 75 131-30	754.10.48	21	30						
SD 75 131-35	754.10.49	21	35						
SD 75 131-40	754.10.50	21	40						
SD 75 131-50	754.10.51	21	50	153.2	155.0	84.5	84.5	115	
SD 75 155-20	754.12.86	25	20						
SD 75 155-25	754.12.87	25	25						
SD 75 155-30	754.12.88	25	30						
SD 75 155-35	754.12.89	25	35						
SD 75 155-40	754.12.90	25	40	153.2	155.0	84.5	84.5	115	
SD 75 155-50	754.12.91	25	50						
For steel chain series: MCC: straight run heavy duty, heavy duty Magnetflex									
For plastic chain series: HDS, HDFM									
									


SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Width (Teeth) C	Hub width A	Hub diameter H			
			mm/inch	mm	mm	mm	mm	mm			
SPLIT SPROCKETS AND IDLERS, INJECTION MOULDED - NS/NSX 881											
SPROCKETS, METRIC BORES									  * Ask Customer service for minimum order quantity of sprockets with inch bores.		
NS881 21-25	L0881664501	21	25	129.3	129.5	31.8	51.0	60			
NS881 21-30	L0881664511	21	30								
NS881 21-35	L0881664521	21	35								
NS881 21-40	L0881664531	21	40								
NS881 21-45	L0881664541	21	45								
NS881 23-25	L0881662821	23	25	141.2	142.0		31.8			51.0	60
NS881 23-30	L0881662831	23	30								
NS881 23-35	L0881662841	23	35								
NS881 23-40	L0881662851	23	40								
NS881 23-45	L0881662861	23	45								
NS881 25-25	L0881663351	25	25	153.2	154.2	58.5	58.5	60			
NS881 25-30	L0881663361	25	30								
NS881 25-35	L0881663371	25	35								
NS881 25-40	L0881663381	25	40								
NS881 25-45	L0881663391	25	45								
SPROCKETS, INCH BORES*											
NS881 21-1	L0881664551	21	1.00"	129.3	129.5	31.8	51.0	60			
NS881 21-1 1/4	L0881664571	21	1.25"								
NS881 21-1 1/2	L0881664591	21	1.50"								
NS881 23-1	L0881662921	23	1.00"	141.2	142.0		31.8		51.0	60	
NS881 23-1 1/4	L0881662941	23	1.25"								
NS881 25-1	L0881663401	25	1.00"								
NS881 25-1 1/4	L0881663441	25	1.25"	153.2	154.2		58.5		58.5		60
NS881 25-1 1/2	L0881663481	25	1.50"								
IDLERS, METRIC BORES											
NSX881 21-25	L0881639842	21	25	129.3	129.5	31.8	51.0	60			
NSX881 21-30	L0881612242	21	30								
NSX881 21-35	L0881612252	21	35								
NSX881 21-40	L0881612262	21	40								
NSX881 23-25	L0881631332	23	25	141.2	142.0		31.8		51.0	60	
NSX881 23-30	L0881612272	23	30								
NSX881 23-35	L0881612282	23	35								
NSX881 23-40	L0881612292	23	40								
NSX881 25-30	L0881609932	25	30	153.2	154.2		58.5		58.5		60
NSX881 25-35	L0881600282	25	35								
NSX881 25-40	L0881609942	25	40								
NSX881 25-45	L0881631222	25	45								
For steel chain series: Rexnord: 812 mini hinge, 812-TAB, 881, 8811 (all) MCC: single hinge TAB rubber top											
CLASSIC IDLERS, INJECTION MOULDED - NX 881											
METRIC BORES									 		
NX881 25-25	L0881620072	25	25	153.2	154.2	31.3	65.0	56			
NX881 25-30	L0881666081	25	30								
NX881 25-35	L0881666091	25	35								
NX881 25-40	L0881602916	25	40								
For steel chain series: Rexnord: 812 mini hinge, 812-TAB, 881, 8811 (all)											

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm			
									MATERIAL page 209		
SPLIT SPROCKETS AND IDLERS, INJECTION MOULDED - NS/NSX 821											
SPROCKETS, METRIC BORES											
NS821 21-35	L0821665261	21	35	129.2	129.5	82.0	103.0	60			
NS821 21-40	L0821665121	21	40								
NS821 21-45	L0821665271	21	45								
NS821 23-30	L0821648082	23	30	141.2	142.0	82.0	103.0				
NS821 23-35	L0821663111	23	35								
NS821 23-40	L0821663121	23	40								
NS821 23-45	L0821663131	23	45								
NS821 25-30	L0821600482	25	30	153.2	154.2	89.5	117.0				
NS821 25-35	L0821665671	25	35								
NS821 25-40	L0821665681	25	40								
NS821 25-45	L0821665691	25	45								
IDLERS, METRIC BORES											
NSX821 21-30	L0821665001	21	30	129.2	129.5	82.0	103.0	60			
NSX821 21-35	L0821665031	21	35								
NSX821 21-40	L0821665061	21	40								
NSX821 23-30	L0821663011	23	30	141.2	142.0	82.0	103.0				
NSX821 23-35	L0821663041	23	35								
NSX821 23-40	L0821663071	23	40								
NSX821 25-30	L0821665721	25	30	153.2	154.2	89.5	117.0				
NSX821 25-35	L0821665751	25	35								
NSX821 25-40	L0821665781	25	40								
For steel chain series: Rexnord: 802 (all), 805 MCC: double hinge For plastic chain series: 821, SWH NS 821 is a set of 2 NS 881 sprockets; NSX 821 is a set of 2 NSX 881 idlers											
CLASSIC SPROCKETS AND IDLERS, INJECTION MOULDED - N/NX 800											
SPROCKETS, METRIC BORES											
N800 25-30	L0800666101	25	30	153.2	154.2	89.0	121.5	60			
N800 25-35	L0800666121	25	35								
N800 25-40	L0800666131	25	40								
IDLERS, METRIC BORES											
NX800 25-30	L0800666141	25	30	153.2	154.2	89.0	121.5	60			
NX800 25-35	L0800666161	25	35								
NX800 25-40	L0800666181	25	40								
For steel chain series: Rexnord: 802 (all), 805 MCC: double hinge											

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm	MATERIAL page 209	
CLASSIC SPROCKETS AND IDLERS, MACHINED - KU 821										
SPROCKETS, METRIC BORES										
KU821 19-25	753.94.07	19	25	117.3	116.3	80.0	-	-		
KU821 19-30	753.94.08	19	30							
KU821 19-35	753.94.09	19	35							
KU821 19-40	753.94.10	19	40							
KU821 19-50	753.94.11	19	50							
KU821 21-25	753.94.13	21	25	129.3	130.0					
KU821 21-30	753.94.14	21	30							
KU821 21-35	753.94.15	21	35							
KU821 21-40	753.94.16	21	40							
KU821 21-50	753.94.17	21	50							
KU821 23-25	753.94.19	23	25	141.2	141.9					
KU821 23-30	753.94.20	23	30							
KU821 23-35	753.94.21	23	35							
KU821 23-40	753.94.22	23	40							
KU821 23-50	753.94.23	23	50							
KU821 25-25	753.94.25	25	25	153.2	153.9					
KU821 25-30	753.94.26	25	30							
KU821 25-35	753.94.27	25	35							
KU821 25-40	753.94.28	25	40							
KU821 25-50	753.94.29	25	50							
KU821 27-25	753.94.31	27	25	165.2	165.9					
KU821 27-30	753.94.32	27	30							
KU821 27-35	753.94.33	27	35							
KU821 27-40	753.94.34	27	40							
KU821 27-50	753.94.35	27	50							
KU821 29-25	753.94.37	29	25	177.2	178.0					
KU821 29-30	753.94.38	29	30							
KU821 29-35	753.94.39	29	35							
KU821 29-40	753.94.40	29	40							
KU821 29-50	753.94.41	29	50							
IDLERS, METRIC BORES										
KU821 19-25	753.94.47	19	25	117.3	116.3	80.0	-	-		
KU821 19-30	753.94.48	19	30							
KU821 19-35	753.94.49	19	35							
KU821 19-40	753.94.50	19	40							
KU821 19-50	753.94.51	19	50							
KU821 21-25	753.94.52	21	25	129.3	130.0					
KU821 21-30	753.94.53	21	30							
KU821 21-35	753.94.54	21	35							
KU821 21-40	753.94.55	21	40							
KU821 21-50	753.94.56	21	50							
KU821 23-25	753.94.57	23	25	141.2	141.9					
KU821 23-30	753.94.58	23	30							
KU821 23-35	753.94.59	23	35							
KU821 23-40	753.94.60	23	40							
KU821 23-50	753.94.61	23	50							
KU821 25-25	753.94.62	25	25	153.2	153.9					
KU821 25-30	753.94.63	25	30							
KU821 25-35	753.94.64	25	35							
KU821 25-40	753.94.65	25	40							
KU821 25-50	753.94.66	25	50							
KU821 27-25	753.94.67	27	25	165.2	165.9					
KU821 27-30	753.94.68	27	30							
KU821 27-35	753.94.69	27	35							
KU821 27-40	753.94.70	27	40							
KU821 27-50	753.94.71	27	50							
KU821 29-25	753.94.72	29	25	177.2	178.0					
KU821 29-30	753.94.73	29	30							
KU821 29-35	753.94.74	29	35							
KU821 29-40	753.94.75	29	40							
KU821 29-50	753.94.76	29	50							
For steel chain series: Rexnord: 802 (all), 805 MCC: double hinge For plastic chain series: 821, SWH										

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F/D	Width teeth/ ring	Hub width A	Hub diameter H	
			mm	mm	mm	mm	mm	mm	


MATERIAL

page 209


SPLIT SPROCKETS AND IDLERS, MACHINED - KUS 821

SPROCKETS, METRIC BORES

KUS821 23-25	753.64.71	23	25	141.2	141.9	80.0	-	-	
KUS821 23-30	753.64.72	23	30						
KUS821 23-35	753.64.73	23	35						
KUS821 23-40	753.64.74	23	40						
KUS821 23-50	753.64.75	23	50						
KUS821 27-25	753.64.91	27	25	165.2	165.9				
KUS821 27-30	753.64.92	27	30						
KUS821 27-35	753.64.93	27	35						
KUS821 27-40	753.64.94	27	40						
KUS821 27-50	753.64.95	27	50						



IDLERS, METRIC BORES

KUS821 23-25	753.64.21	23	25	141.2	141.9	80.0	-	-	
KUS821 23-30	753.64.22	23	30						
KUS821 23-35	753.64.23	23	35						
KUS821 23-40	753.64.24	23	40						
KUS821 23-50	753.64.25	23	50						
KUS821 27-25	753.64.41	27	25	165.2	165.9				
KUS821 27-30	753.64.42	27	30						
KUS821 27-35	753.64.43	27	35						
KUS821 27-40	753.64.44	27	40						
KUS821 27-50	753.64.45	27	50						


For steel chain series: Rexnord: 802 (all), 805 MCC: double hinge
For plastic chain series: 821, SWH

CLASSIC IDLER DRUMS, MACHINED - KXT 800



METRIC BORES

KXT 800 21-25	L0800605761	21	25*	106.8	129.8	100.0	-	106.8	
KXT 800 23-25	L0800605771	23	25*	119.3	142.3			119.3	
KXT 800 25-25	L0800605781	25	25*	131.7	154.7			131.7	


* Pre-bore
For steel chain series: Rexnord: 802 (all), 805 MCC: double hinge




SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter H mm	MATERIAL page 209				
CLASSIC SPROCKETS, MACHINED - ST 512													
METRIC BORES													
ST512 13-20	753.93.77	13	20*	106.1	107.4	42.9	42.9	-					
ST512 15-20	753.93.78	15	20*	122.2	123.9								
ST512 17-20	753.93.79	17	20*	138.2	140.3								
ST512 19-20	753.93.80	19	20*	154.3	156.6								
ST512 21-20	753.93.81	21	20*	170.4	172.9								
ST512 23-20	753.93.82	23	20*	186.5	189.2								
ST512 25-20	753.93.83	25	20*	202.7	205.4								
* Pre-bore For steel chain series: Rexnord: 512, 581 M													
SPLIT SPROCKETS, MACHINED - SS MINI													
METRIC BORES													
SS MINI 21-25	753.67.61	21	25	129.3	130.0	21.0	21.0	-					
SS MINI 21-30	753.67.62	21	30										
SS MINI 21-35	753.67.63	21	35										
SS MINI 21-40	753.67.64	21	40										
SS MINI 21-50	753.67.65	21	50	153.2	153.9								
SS MINI 25-25	753.67.81	25	25										
SS MINI 25-30	753.67.82	25	30										
SS MINI 25-35	753.67.83	25	35										
SS MINI 25-40	753.67.84	25	40										
SS MINI 25-50	753.67.85	25	50										
For steel chain series: Rexnord: 812-narrow, mini hinge													


SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F/D mm	Hub width A mm						
MATERIAL page 209												
SPLIT SPROCKETS AND IDLERS, MACHINED - SS/SI 661												
SPROCKETS, METRIC BORES												
SS 661 11-30	753.95.01	11	30	90.2	89.9	40						
SS 661 11-35	753.95.02	11	35									
SS 661 11-40	753.95.03	11	40									
SS 661 13-30	753.95.14	13	30	106.1	106.7			40				
SS 661 13-35	753.95.15	13	35									
SS 661 13-40	753.95.16	13	40									
SS 661 14-30	753.95.27	14	30	114.1	114.6				40			
SS 661 14-35	753.95.28	14	35									
SS 661 14-40	753.95.29	14	40									
SS 661 15-30	753.95.40	15	30	122.2	122.8					40		
SS 661 15-35	753.95.41	15	35									
SS 661 15-40	753.95.42	15	40									
SS 661 16-30	753.95.53	16	30	130.2	131.0						40	
SS 661 16-35	753.95.54	16	35									
SS 661 16-40	753.95.55	16	40									
SS 661 19-30	753.95.66	19	30	154.3	155.4							40
SS 661 19-35	753.95.67	19	35									
SS 661 19-40	753.95.68	19	40									
SPROCKETS, INCH BORES												
SS 661 11-1 1/4 "	753.95.04	11	1.250 "	90.2	89.9	40						
SS 661 11-1 7/16 "	753.95.05	11	1.438 "									
SS 661 11-1 1/2 "	753.95.06	11	1.500 "									
SS 661 13-1 1/4 "	753.95.17	13	1.250 "	106.1	106.7			40				
SS 661 13-1 7/16 "	753.95.18	13	1.438 "									
SS 661 13-1 1/2 "	753.95.19	13	1.500 "									
SS 661 14-1 1/4 "	753.95.30	14	1.250 "	114.1	114.6				40			
SS 661 14-1 7/16 "	753.95.31	14	1.438 "									
SS 661 14-1 1/2 "	753.95.32	14	1.500 "									
SS 661 15-1 1/4 "	753.95.43	15	1.250 "	122.2	122.8					40		
SS 661 15-1 7/16 "	753.95.44	15	1.438 "									
SS 661 15-1 1/2 "	753.95.45	15	1.500 "									
SS 661 16-1 1/4 "	753.95.56	16	1.250 "	130.2	131.0						40	
SS 661 16-1 7/16 "	753.95.57	16	1.438 "									
SS 661 16-1 1/2 "	753.95.58	16	1.500 "									
SS 661 19-1 1/4 "	753.95.69	19	1.250 "	154.3	155.4							40
SS 661 19-1 7/16 "	753.95.70	19	1.438 "									
SS 661 19-1 1/2 "	753.95.71	19	1.500 "									
IDLERS, METRIC BORES							For steel chain series: 661					
SI 661 11-30	753.95.07	11	30	90.2	89.9	40						
SI 661 11-35	753.95.08	11	35									
SI 661 11-40	753.95.09	11	40									
SI 661 13-30	753.95.20	13	30	106.1	106.7			40				
SI 661 13-35	753.95.21	13	35									
SI 661 13-40	753.95.22	13	40									
SI 661 14-30	753.95.33	14	30	114.1	114.6				40			
SI 661 14-35	753.95.34	14	35									
SI 661 14-40	753.95.35	14	40									
SI 661 15-30	753.95.46	15	30	122.2	122.8					40		
SI 661 15-35	753.95.47	15	35									
SI 661 15-40	753.95.48	15	40									
SI 661 16-30	753.95.59	16	30	130.2	131.0						40	
SI 661 16-35	753.95.60	16	35									
SI 661 16-40	753.95.61	16	40									
SI 661 19-30	753.95.72	19	30	154.3	155.4							40
SI 661 19-35	753.95.73	19	35									
SI 661 19-40	753.95.74	19	40									
IDLERS, INCH BORES												
SI 661 11-1 1/4 "	753.95.10	11	1.250 "	90.2	89.9	40						
SI 661 11-1 7/16 "	753.95.11	11	1.438 "									
SI 661 11-1 1/2 "	753.95.12	11	1.500 "									
SI 661 13-1 1/4 "	753.95.23	13	1.250 "	106.1	106.7			40				
SI 661 13-1 7/16 "	753.95.24	13	1.438 "									
SI 661 13-1 1/2 "	753.95.25	13	1.500 "									
SI 661 14-1 1/4 "	753.95.36	14	1.250 "	114.1	114.6				40			
SI 661 14-1 7/16 "	753.95.37	14	1.438 "									
SI 661 14-1 1/2 "	753.95.38	14	1.500 "									
SI 661 15-1 1/4 "	753.95.49	15	1.250 "	122.2	122.8					40		
SI 661 15-1 7/16 "	753.95.50	15	1.438 "									
SI 661 15-1 1/2 "	753.95.51	15	1.500 "									
SI 661 16-1 1/4 "	753.95.62	16	1.250 "	130.2	131.0						40	
SI 661 16-1 7/16 "	753.95.63	16	1.438 "									
SI 661 16-1 1/2 "	753.95.64	16	1.500 "									
SI 661 19-1 1/4 "	753.95.75	19	1.250 "	154.3	155.4							40
SI 661 19-1 7/16 "	753.95.76	19	1.438 "									
SI 661 19-1 1/2 "	753.95.77	19	1.500 "									

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) C mm	Hub width A mm	Hub diameter	MATERIAL page 209	
METRIC BORES										
NS831 21-25	L0831604102	21	25	129.3	129.5	42.9	51.0	60		
NS831 21-30	L0831604112	21	30							
NS831 21-35	L0831604122	21	35							
NS831 21-40	L0831604132	21	40							
NS831 21-45	L0831604142	21	45							
NS831 23-25	L0831604152	23	25	141.2	142.0		58.5			
NS831 23-30	L0831604162	23	30							
NS831 23-35	L0831604172	23	35							
NS831 23-40	L0831604182	23	40							
NS831 23-45	L0831604192	23	45							
NS831 25-25	L0831604202	25	25	153.2	154.2					
NS831 25-30	L0831604212	25	30							
NS831 25-35	L0831604222	25	35							
NS831 25-40	L0831604232	25	40							
NS831 25-45	L0831604242	25	45							
INCH BORES										
NS831 21-1	L0831604252	21	1.000"	129.26	129.5	42.9	51.0	60		
NS831 25-1	L0831604312	25	1.000"	153.21	154.2	42.9	58.5			
For plastic chain series: 820, 831, SH, SHD * Ask Customer service for minimum order quantity of sprockets with inch bores.										

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) mm	Hub width mm	Hub diameter H mm	MATERIAL page 205
SPLIT SPROCKETS, MACHINED - SS SH									
METRIC BORES									
SS SH 17-25	754.62.11	17	25	105.5	104.5	40	40	--	
SS SH 17-30	754.62.21	17	30						
SS SH 17-35	754.62.31	17	35						
SS SH 17-40	754.62.41	17	40						
SS SH 19-25	754.62.12	19	25	117.3	116.3				
SS SH 19-30	754.62.22	19	30						
SS SH 19-35	754.62.32	19	35						
SS SH 19-40	754.62.42	19	40						
SS SH 19-50	754.62.62	19	50						
SS SH 21-25	754.62.13	21	25	129.3	130.0				
SS SH 21-30	754.62.23	21	30						
SS SH 21-35	754.62.33	21	35						
SS SH 21-40	754.62.43	21	40						
SS SH 21-50	754.62.63	21	50						
SS SH 23-25	754.62.14	23	25	141.2	141.9				
SS SH 23-30	754.62.24	23	30						
SS SH 23-35	754.62.34	23	35						
SS SH 23-40	754.62.44	23	40						
SS SH 23-50	754.62.64	23	50						
SS SH 25-25	754.62.15	25	25	153.2	153.9				
SS SH 25-30	754.62.25	25	30						
SS SH 25-35	754.62.35	25	35						
SS SH 25-40	754.62.45	25	40						
SS SH 25-50	754.62.65	25	50						
SS SH 27-25	754.62.16	27	25	165.2	165.9				
SS SH 27-30	754.62.26	27	30						
SS SH 27-35	754.62.36	27	35						
SS SH 27-40	754.62.46	27	40						
SS SH 27-50	754.62.66	27	50						
INCH BORES									
SS SH 21-1	754.66.12	21	1.000"	129.3	130.0	40	40	--	
SS SH 21-1 ³ / ₁₆	754.66.22	21	1.188"						
SS SH 21-1 ¹ / ₄	754.66.32	21	1.250"						
SS SH 21-1 ⁷ / ₁₆	754.66.42	21	1.438"						
SS SH 21-1 ¹ / ₂	754.66.52	21	1.500"						
SS SH 25-1	754.66.15	25	1.000"	153.2	153.9				
SS SH 25-1 ³ / ₁₆	754.66.25	25	1.188"						
SS SH 25-1 ¹ / ₄	754.66.35	25	1.250"						
SS SH 25-1 ⁷ / ₁₆	754.66.45	25	1.438"						
SS SH 25-1 ¹ / ₂	754.66.55	25	1.500"						
For plastic chain series: 820, 831, SH, SHD									

Split idlers are also available; all parameters are the same as for SS SH; just change in the code nr. 62 into 61 and 66 into 65.

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter D	Width (Ring)	Hub width A	Hub diameter H	
			mm	mm	mm	mm	mm	mm	

MATERIAL

page 209


CLASSIC IDLER DRUMS, INJECTION MOULDED - NXT 821

METRIC BORES

NXT821 25-30	L0821661601	25	30	153.2	154.7	153.0	176.0	42.5
NXT821 25-35	L0821661611	25	35					

For plastic chain series: 821, SWH





SPLIT SPROCKETS INJECTION MOULDED - NSH 880

SPROCKETS, METRIC BORES


NSH880 12-40	751.90.02	12	40	147.2	147.4	15.9	58.5	60
--------------	-----------	----	----	-------	-------	------	------	----

SPROCKETS, INCH BORES

NSH880 12-1 1/2"	751.90.05	12	1.5"	147.2	147.4	15.9	58.5	60
------------------	-----------	----	------	-------	-------	------	------	----

For plastic chain series: 879, 880, RH, RHD, RHM, RHMD, RHMP, RHMDP, SHP






SPLIT IDLER DRUMS, MACHINED - SD RH

METRIC BORES



SD RH 131-25	754.10.62	10	25	123.3	131.0	87.5	87.5	--		
SD RH 131-30	754.10.63	10	30							
SD RH 131-35	754.10.64	10	35							
SD RH 131-40	754.10.65	10	40							
SD RH 131-50	754.10.66	10	50	135.2	143.0					
SD RH 143-25	754.11.82	11	25							
SD RH 143-30	754.11.83	11	30							
SD RH 143-35	754.11.84	11	35							
SD RH 143-40	754.11.85	11	40	147.2	155.0					
SD RH 143-50	754.11.86	11	50							
SD RH 155-25	754.13.02	12	25							
SD RH 155-30	754.13.03	12	30							
SD RH 155-35	754.13.04	12	35							
SD RH 155-40	754.13.05	12	40							
SD RH 155-50	754.13.06	12	50							

For plastic chain series: 879-TAB, 880-TAB, RH, RHD





SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Width (Teeth)	Hub width	Hub diameter H						
			mm/inch	mm	mm	mm	mm	mm						
SPLIT SPROCKETS AND IDLERS, MACHINED - SS/SI HD														
SPROCKETS, METRIC BORES														
SS HD 11-25	754.63.71	11	25	135.2	135.4	22.0	40	90						
SS HD 11-30	754.63.72	11	30											
SS HD 11-35	754.63.73	11	35											
SS HD 11-40	754.63.74	11	40											
SS HD 11-50	754.63.75	11	50	147.2	147.6	22.0	40	90						
SS HD 12-25	754.63.81	12	25											
SS HD 12-30	754.63.82	12	30											
SS HD 12-35	754.63.83	12	35											
SS HD 12-40	754.63.84	12	40											
SS HD 12-50	754.63.85	12	50											
SPROCKETS, INCH BORES														
SS HD 11-1	754.63.76	11	1.000"	135.2	135.4	22.0	40	90						
SS HD 11-1 ³ / ₁₆	754.63.77	11	1.188"											
SS HD 11-1 ¹ / ₄	754.63.78	11	1.250"											
SS HD 11-1 ⁷ / ₁₆	754.63.79	11	1.438"											
SS HD 11-1 ¹ / ₂	754.63.80	11	1.500"	147.2	147.6	22.0	40	90						
SS HD 12-1	754.63.86	12	1.000"											
SS HD 12-1 ³ / ₁₆	754.63.87	12	1.188"											
SS HD 12-1 ¹ / ₄	754.63.88	12	1.250"											
SS HD 12-1 ⁷ / ₁₆	754.63.89	12	1.438"											
SS HD 12-1 ¹ / ₂	754.63.90	12	1.500"											
IDLERS, METRIC BORES														
SI HD 11-25	754.63.21	11	25	135.2	135.4	22.0	40	90						
SI HD 11-30	754.63.22	11	30											
SI HD 11-35	754.63.23	11	35											
SI HD 11-40	754.63.24	11	40											
SI HD 11-50	754.63.25	11	50	147.2	147.6	22.0	40	90						
SI HD 12-25	754.63.31	12	25											
SI HD 12-30	754.63.32	12	30											
SI HD 12-35	754.63.33	12	35											
SI HD 12-40	754.63.34	12	40											
SI HD 12-50	754.63.35	12	50											
For plastic chain series: 882, 883, HDF, HDFM, HDS														
SPLIT SPROCKETS AND IDLERS, INJECTION MOULDED - NS(X) 882														
SPROCKETS, METRIC BORES														
NS882 12-25	L0882663551	12	25	147.2	149.9	22.2	58.5	60						
NS882 12-30	L0882663561	12	30											
NS882 12-35	L0882663571	12	35											
NS882 12-40	L0882663581	12	40											
NS882 12-45	L0882663591	12	45											
SPROCKETS, INCH BORES*														
NS882 12-1	L0882663601	12	1.000"	147.2	149.9	22.2	58.5	60						
NS882 12-1 ¹ / ₄	L0882619072	12	1.250"											
NS882 12-1 ¹ / ₂	L0882619082	12	1.500"											
IDLERS, METRIC BORES														
NSX882 12-25	L0882663641	12	25	147.2	149.9	22.2	58.5	60						
NSX882 12-30	L0882663651	12	30											
NSX882 12-35	L0882663661	12	35											
NSX882 12-40	L0882663671	12	40											
For plastic chain series: 882, 883, HDF, HDFM, HDS														
*Ask Customer service for minimum order quantity of NS882 sprockets with inch bores.														

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Width (Teeth)	Hub width	Hub diameter H	
			mm/inch	mm	mm	mm	mm	mm	

SPLIT SPROCKETS AND IDLERS, MACHINED - SS/SI RH

SPROCKETS, METRIC BORES

SS RH 9-25	754.60.51	9	25	111.4	109.0	16.0	40.0	75
SS RH 9-30	754.60.52	9	30					
SS RH 9-35	754.60.53	9	35					
SS RH 9-40	754.60.54	9	40					
SS RH 10-25	754.60.61	10	25	123.3	121.4			
SS RH 10-30	754.60.62	10	30					
SS RH 10-35	754.60.63	10	35					
SS RH 10-40	754.60.64	10	40					
SS RH 11-25	754.60.71	11	25	135.2	133.9			90
SS RH 11-30	754.60.72	11	30					
SS RH 11-35	754.60.73	11	35					
SS RH 11-40	754.60.74	11	40					
SS RH 12-25	754.60.81	12	25	147.2	145.8			
SS RH 12-30	754.60.82	12	30					
SS RH 12-35	754.60.83	12	35					
SS RH 12-40	754.60.84	12	40					

IDLERS, METRIC BORES

SI RH 9-25	754.60.01	9	25	111.4	109.0	16.0	40.0	75
SI RH 9-30	754.60.02	9	30					
SI RH 9-35	754.60.03	9	35					
SI RH 9-40	754.60.04	9	40					
SI RH 10-25	754.60.11	10	25	123.3	121.4			
SI RH 10-30	754.60.12	10	30					
SI RH 10-35	754.60.13	10	35					
SI RH 10-40	754.60.14	10	40					
SI RH 11-25	754.60.21	11	25	135.2	133.9			90
SI RH 11-30	754.60.22	11	30					
SI RH 11-35	754.60.23	11	35					
SI RH 11-40	754.60.24	11	40					
SI RH 12-25	754.60.31	12	25	147.2	145.8			
SI RH 12-30	754.60.32	12	30					
SI RH 12-35	754.60.33	12	35					
SI RH 12-40	754.60.34	12	40					

For plastic chain series: 879, 880, RH, RHD, RHM, RHMD, RHMP, RHMDP, SHP

SPLIT SPROCKETS AND IDLERS, INJECTION MOULDED - NS(X) 880

SPROCKETS, METRIC BORES

NS880 10-25	L0880662171	10	25	123.3	122.5	15.9	58.5	60
NS880 10-30	L0880662211	10	30					
NS880 10-35	L0880662251	10	35					
NS880 10-40	L0880662291	10	40					
NS880 10-45	L0880662331	10	45	147.2	147.4			
NS880 12-25	L0880663151	12	25					
NS880 12-30	L0880663161	12	30					
NS880 12-35	L0880663171	12	35					
NS880 12-40	L0880663181	12	40	147.2	147.4			
NS880 12-45	L0880663191	12	45					

SPROCKETS, INCH BORES

NS880 12-1	L0880663201	12	1.000"	147.2	147.4	15.9	58.5	60
NS880 12-1¼	L0880663241	12	1.250"					

IDLERS, METRIC BORES






NSX880 10-25	L0880662401	10	25	123.3	122.5	15.9	58.5	60
NSX880 10-30	L0880662421	10	30					
NSX880 10-35	L0880662441	10	35					
NSX880 10-40	L0880619422	10	40					
NSX880 12-25	L0880604082	12	25	147.2	147.4			
NSX880 12-30	L0880604092	12	30					
NSX880 12-35	L0880699811	12	35					
NSX880 12-40	L0880604602	12	40					

For plastic chain series: 879, 880, RH, RHD, RHM, RHMD, RHMP, RHMDP, SHP



<

* Ask Customer service for minimum order quantity of NS880 sprockets with inch bores.

SPROCKETS FOR TABLETOP CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Width (Teeth) mm	Hub width mm	Hub diameter H mm	MATERIAL page 209	
CLASSIC SPROCKET AND IDLER, INJECTION MOULDED - N(X) 1108										
SPROCKET, METRIC BORE										
N1108 12-12	L1108666211	12	12	49.1	54.0	21.4	25.0	28.0		
IDLER, METRIC BORE										
NX1108 12-12	L1108666231	12	12	49.1	54.0	21.4	25.0	28.0		
For plastic chain series: 1108 The drive sprocket is fixed by mounting a pin radially through sprocket and shaft. 1108 plastic chains also run on standard 1/2 pitch roller chain sprockets that meet ANSI 40.										
										
CLASSIC SPROCKETS - ST 1080										
METRIC PREBORES										
ST1080 08-30	L1080668371	8	30	165.9	177.7	8.5	14.0	119.0		
ST1080 09-30	L1080668381	9	30	185.7	198.5	8.5	14.0	136.0		
ST1080 10-30	L1080668391	10	30	205.5	219.3	8.5	14.0	158.0		
ST1080 12-30	L1080668401	12	30	245.4	260.5	8.5	14.0	200.0		
ST1080 14-30	L1080668411	14	30	285.4	301.5	8.5	14.0	240.0		
For plastic chain series: 1080										
SPLIT SPROCKETS AND IDLERS, INJECTION MOULDED - SSW/SIW 1050										
SPROCKETS, METRIC BORES										
SSW 1050 16-30	749.82.23	16	30	131.2	130.9	11.0	40.0	40.0		
SSW 1050 16-40	749.82.43	16	40	131.2	130.9	11.0	40.0	50.0		
SSW 1050 18-30	749.82.25	18	30	147.2	146.8	11.0	40.0	40.0		
SSW 1050 18-40	749.82.45	18	40	147.4	146.8	11.0	40.0	50.0		
SPROCKETS, INCH BORES										
SSW 1050 16-1 1/2	749.86.53	16	1.500"	131.2	130.9	11.0	40.0	48.1		
SSW 1050 18-1 1/2	749.86.55	18	1.500"	147.4	146.8	11.0	40.0	48.1		
IDLERS, METRIC BORES										
SIW 1050-16-30	749.81.23	16	30	131.2	130.9	11.0	40.0	40.0		
SIW 1050-16-40	749.81.43	16	40	131.2	130.9	11.0	40.0	50.0		
SIW 1050-18-30	749.81.25	18	30	147.4	146.8	11.0	40.0	40.0		
SIW 1050-18-40	749.81.45	18	40	147.4	146.8	11.0	40.0	50.0		
IDLERS, INCH BORES										
SIW 1050-16-1 1/2	749.85.53	16	1.500"	131.2	130.9	11.0	40.0	48.1		
SIW 1050-18-1 1/2	749.85.55	18	1.500"	147.4	146.8	11.0	40.0	48.1		
For plastic chain series: 1050, 1055, 1060										

CORNER DISCS FOR TABLETOP CHAINS

Corner disc type	Code nr.	Execution	Open/ closed	Pitch diameter chain	Outside diameter F	Weight	MATERIAL page 207
				mm	mm	kg	
FOR PLASTIC SLATBAND TAB CHAINS 879BO, 880BO, 880BO F, HFP880BOT AND LBP879BO							
WITH 32 TEETH							
N880BOT32	L0880684051	drive	open	380	352	0.98	
- clamping device not included (bore 50H7 mm)							
WITH 32 TEETH							
NX880BOT32	L0880698581	carry/return	closed	380	352	0.98	
- inclusive 2x single race ball bearing 25x47x8 - contour symmetrical: no difference between carry and return corner disc - opened by breaking out diaphragm							
WITHOUT TEETH							
NXT880 BO	L0880632762	carry/return	closed	380	335	0.98	
- inclusive 2x single race ball bearing 25x47x8 - contour symmetrical: no difference between carry and return corner disc - opened by breaking out diaphragm							

See page 74 for explanation.

MULTIFLEX AND CASE CONVEYOR CHAINS

The product program offers a wide range of Rexnord multiflex chains and MCC case conveyor chains. These chains are intended for single lane product handling in a variety of applications.

FEATURES

- Multiflex chains

These chains use a unique pivot to connect the hinge pin with the chain link. In standard sideflexing chains the pin and hinge have to deal with horizontal rotation, due to the sideflexing of the chain in the curve, and with vertical rotation of the hinge, when moving over the sprocket. The pivot uncouples these movements, as the hinge pin is only involved in the rotations because of the chain links moving over the sprocket. The pivot can rotate inside the chain link, allowing sideflexing in a curve. Due to the pivot, multiflex chains are ideally suitable for running through multiple curves.

- Armor Clad

The 1700 multiflex chains are also available with a hardened steel cover, the Armor Clad AC 1700 K. Because of this cover the chain is very suitable to convey parts with a high temperature that could damage a plastic chain surface. The steel cover gives the chain an excellent wear life, to make it suitable for part handling in automotive and similar applications.

- Safety

The ZeroGap 1765 and 2565 multiflex chain have a patented top plate design. The chain surface always stays closed when the chain is running through a curve or over a sprocket. Both chains are commonly used in packaging and automotive industry. The 1710 K and 1713 K multiflex chains also offer surfaces preventing people's fingers to be trapped if larger products have to be conveyed.

- Case conveyor chains

These chains have a very robust design, making them ideally suited for tough applications, such as case and crate handling. They are very open to deal with the often abrasive debris in these kinds of applications. The conveyor design for these chains can be very simple, resulting in a very economic solution for the sometimes very long distances empty or full crates and cases have to be conveyed in a production line.

- Pin design

Both Multiflex and Case Conveyor chains have chain links characterized by two legs. The pins have a special design to prevent opening up of these link legs. This results in a high allowable working load.

- Corner discs

For multiflex and some sideflexing slatband chains, corner discs can be used to reduce the friction in the curves, allowing a multitude of curves within one conveyor. The use of corner discs is mainly found in conveyors with low-speed part handling in dairy applications, automotive part handling, tobacco industry, etc.

The N880 drive corner disc with a toothed contour is used to drive the chain, integrating sprocket and curve function in the corner disc. This means that no return section for the chain is needed, making the conveyor design more simple and economic. In this kind of conveyor design however the amount of pitch elongation due to wear that can be absorbed is limited. The disc is mounted on the drive shafts by means of a clamping device, for which standard machine components can be used.

The carry disc is used in the upper part of the conveyor, contacting the chain in the normal position when it is conveying products. The return disc is used in the return part of the conveyor, contacting the chain when it is in the upside-down position.

The ball bearing types of corner discs are recommended for high-speed and high-load applications; ball bearings are not included. In all other applications corner discs with thermoplastic bushings can be used.

An open corner disc is mounted on the shaft which needs to run through the disc. A closed corner disc is mounted on top of the shaft. Some closed versions, such as 880BO, offer the ability to break out a diaphragm in the closing cap.



MULTIFLEX AND CASE CONVEYOR CHAINS

PROGRAMME

Multiflex and case conveyor chains are available in the following executions:


REXNORD MULTIFLEX CHAINS	
1765	ZeroGap 50 mm pitch chain without gaps if sideflexing or running over a sprocket; low noise and long wear life
2565	ZeroGap 76 mm pitch chain without gaps if sideflexing; heavy duty execution in wear resistant polyamide
1757	1.5" pitch chain with unique top plate design, ideal for extruded aluminum modular conveyor designs, commonly used for part handling applications; also available with rubber top
1700	Basic 50 mm pitch chain when using corner disks; available in 3 versions: standard, with tabs and with hardened steel top surface (AC1700K)
1702	Basic 50 mm pitch chain; bidirectional and FDA-approved for direct food contact
1720	50 mm pitch chain for irregular cardboard containers; bidirectional and smooth edges
1710	1700 Base chain with round top plates for a uniform and continuous surface, also in curves
1713	1700 Base chain with wide top plates riveted to the chain; the links overlap even in tight corners, so there are no gaps causing safety issues
1775	1775 ZeroGap 1.5" pitch chain with unique zeroGap plate design, ideal for critical product handling like delicate consumer packaging
MCC CASE CONVEYOR CHAINS	
CC 600	Standard chain; available in straight running and sideflexing executions
CC 631	Standard chain with higher links; available in sideflexing execution; can be supplied with pusher
CC 1400	Reinforced chain; available in straight running and sideflexing executions
CC 1431	Reinforced chain with higher links; available in sideflexing execution

CHAIN TYPE	APPLICATION								
	Standard stable products	Small parts & unstable products	Large & heavy products (industrial)	Wide products	Bi-directional conveyors	Abrasive parts conveying	Incline conveyors	Crate conveying	Finger safety
1700									
AC 1700									
1702									
1710									
1713									
1720									
1757									
1765 ZeroGap									
1775 ZeroGap									
2565									
CC 600/631/1400/1431									

Best choice


Optional

MULTIFLEX CHAINS



Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
HP-ACETAL							
HP 1765 ZeroGap	L1765604062	55.0	2.17	1.46	2670	64	125
WX-POLYAMIDE COMPOSITE							
WX 1765 ZeroGap	L1765654842	55.0	2.17	1.46	2670	64	125

Standard length: 3.05 m - 10 feet (61 links)




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
BWX-POLYAMIDE							
BWX 2565	81432921	88.9	3.50	2.67	10675	89	241

Standard length: 3.048 m - 10 feet (40 links)


MATERIAL

page 207



Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
LF-ACETAL							
LF 1757 TAB	81400161	82.6	3.25	1.48	1735	102	152

Standard length: 3.048 m - 10 feet (80 links)




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
HP-ACETAL							
HPM 1757 TAB	81421361	82.6	3.25	1.48	1735	102	152

Standard length: 3.048 m - 10 feet (80 links)

*Ask Customer service for minimum order quantity of 1757 Chains.

MULTIFLEX CHAINS




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
LF-ACETAL							
A 1700 K	L1700AK	55.0	2.17	1.26	2670	38	140
WLF-ACETAL							
WLF 1700 K	L1700WLFK	55.0	2.17	1.26	2670	38	140
HP-ACETAL							
HP 1700 K	L1700HPK	55.0	2.17	1.26	2670	38	140
ACETAL WITH HARDENED STEEL TOP PLATES							
AC 1700 K	L1700ACK	55.0	2.17	60	2670	38	140


Standard length: 10 m - 32.8 feet (200 links)



AC (ARMOR CLAD) EXECUTION



AC (ARMOR CLAD) EXECUTION




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
WLF-ACETAL							
WLF 1700 TAB K	L1700WLF TABK	55.0	2.17	1.30	2670	38	140

Standard length: 10 m - 32.8 feet (200 links)

MULTIFLEX CHAINS




1702




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
WLF-ACETAL							
WLF 1702	L1702698592	53.1	2.09	1.43	2670	38	140

Standard length: 3.05 m - 10 feet (61 links)



1720 K




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
HP-ACETAL							
HP 1720 K	L1720HPK	55.0	2.17	1.26	2600	50	140

Standard length: 10 m - 32.8 feet (200 links)



1775 ZERO GAP




Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
HP-ACETAL							
HP®1775	L1775634993	70.0	2.76	1.05	1000	80	150

Standard length: 5 m – 16.4 ft (200 pitches)

MULTIFLEX CHAINS



1710 K



page 84



page 82, 83




page 207

Chain type	Code nr.	Link width A		Weight kg/m	Working load (max.) N (21°C)	Backflex radius (min.) mm	Sideflex radius (min.) mm
		mm	inch				
WLF-ACETAL							
WLF 1710 K	L1710WLFK	98.0	3.86	1.88	2600	0	140

Standard length: 10 m - 32.8 feet (200 links). Top plate grey polyamide.



1710 TAB K



page 84



page 124



page 82, 83



page 207


Chain type	Code nr.	Link width A		Weight kg/m	Working load (max.) N (21°C)	Backflex radius (min.) mm	Sideflex radius (min.) mm
		mm	inch				
WLF-ACETAL							
WLF 1710 TAB K	L1710WLFTABK	98.0	3.86	1.93	2600	0	140

Standard length: 10 m - 32.8 feet (200 links). Top plate grey polyamide.

MULTIFLEX CHAINS



1713 K





page 82, 83



MATERIAL


page 207

Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
WLF-ACETAL							
WLF 1713 K	L1713WLFK	253.0	9.96	2.70	2600	1000	500

Standard length: 10 m - 32.8 feet (200 links). Top plate white acetal.



1713 TAB K





page 124



page 82, 83





MATERIAL

page 207

Chain type	Code nr.	Link width A		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		mm	inch	kg/m	N (21°C)	mm	mm
WLF-ACETAL							
WLF 1713 TAB K	L1713WLFTABK	253.0	9.96	2.75	2600	1000	500

Standard length: 10 m - 32.8 feet (200 links). Top plate white acetal.

SPROCKETS FOR MULTIFLEX CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Width (Teeth/ Ring) mm	Hub width mm	Hub diameter H mm	
MATERIAL page 209									
CLASSIC PLASTIC SPROCKETS, INJECTION MOULDED, BRASS HUB - N 1700									
METRIC BORES									
N1700 10-24	L1700661391	10	24	161.8	165.1	11.1	44.0	57	
N1700 10-25	L1700661381	10	25						
N1700 10-30	L1700661401	10	30						
For Multiflex chain series: 1700, 1702, 1710, 1713, 1720, 1765									
CLASSIC PLASTIC IDLER, INJECTION MOULDED - NX 1700									
METRIC BORE									
NX1700 10-25	L1700661411	10	25	161.8	165.1	11.1	43.0	50	
For Multiflex chain series: 1700, 1702, 1710, 1713, 1720, 1765									
CLASSIC PLASTIC SPROCKETS, MACHINED - KU 1700									
METRIC BORES									
KU1700 08-19	L1700668341	8	19	130.7	132.8	11.1	42.0	79	
KU1700 08-25	L1700613242	8	25						
KU1700 08-30	L1700630842	8	30						
KU1700 10-19	L1700668351	10	19	161.8	165.1	11.1	42.0	110	
KU1700 10-25	L1700602806	10	25						
KU1700 10-30	L1700618392	10	30						
KU1700 13-19	L1700668361	13	19	209.0	215.2	11.1	42.0	158	
For Multiflex chain series: 1700, 1702, 1710, 1713, 1720, 1765									

SPROCKETS FOR MULTIFLEX CHAINS

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Width (Teeth/ Ring)	Hub width	Hub diameter H	
			mm/inch	mm	mm	mm	mm	mm	

MATERIAL


page 209

CLASSIC ZINC PLATED STEEL IDLERS - ZN 1700

METRIC BORES

ZN1700 10-20	L1700661421	10	20	161.8	165.1	11.1	44.0	69.0
ZN1700 12-20	L1700661431	12	20	193.2	196.1			

For Multiflex chain series: 1700, 1702, 1710, 1713, 1720, 1765






CLASSIC SEMI-STEEL SPROCKET, EXCENTERED HUB - GG 1757

INCH BORE

GG1757 12-3 4 prebore	414-36-2	12	0.750"	147.2	152.4	9.7	38.1	66.5
-----------------------	----------	----	--------	-------	-------	-----	------	------

For Multiflex chain series: 1757






CLASSIC PLASTIC IDLER DRUM, INJECTION MOULDED - NXT 1757

METRIC BORE

NXT1757 10-25	614-35-1	10	25	-	149.9	81	84.1	38.1
---------------	----------	----	----	---	-------	----	------	------

For Multiflex chain series: 1757







SPLIT PLASTIC SPROCKETS, INJECTION MOULDED - KUS 2500

METRIC BORE



KUS 2500 T09 R50	614-681-8	9	50	222.8	221.2	18.0	73.0	165.0
------------------	-----------	---	----	-------	-------	------	------	-------

For Multiflex chain series: 2565






CORNER DISCS FOR MULTIFLEX CHAINS

Corner disc type	Code nr.	Execution	Open/ closed	Pitch diameter chain	Outside diameter	Weight	MATERIAL page 207
				mm	mm	kg	
FOR PLASTIC MULTIFLEX CHAINS 1700 K, 1710 K, 1720 K AND 1765 ZEROGAP							
STANDARD							
ND1700BC-TR	L1700669701	carry	closed	300	247	0.70	
ND1700BO-TR	L1700669721	carry	open				
ND1700BC-RET	L1700669611	return	closed				
ND1700BO-RET	L1700669641	return	open				
- prepared for 2x single race ball bearing (25x47x12 mm)							
WITH 4 HOLES ON BOTTOM FOR PUSHERS							
ND1700-TR	L1700669561	carry	open	300	247	0.47	
ND1700-RET	L1700669591	return	open				
- plastic bushing diameter ø25 mm							
WITH FLANGES (ø355)							
ND1700FL-TR	L1700689461	carry	open	300	247	0.92	
ND1700FL-RET	L1700609602	return	open				
- plastic bushing diameter ø25 mm							
FOR PLASTIC MULTIFLEX CHAINS 1700 TAB K AND 1710 TAB K							
STANDARD							
ND1700TBC-TR	L1700669741	carry	closed	300	247	0.70	
ND1700TBO-TR	L1700669761	carry	open				
ND1700TBC-RET	L1700669661	return	closed				
ND1700TBO-RET	L1700669681	return	open				
- prepared for 2x single race ball bearing (25x47x12 mm)							
WITH 4 HOLES ON BOTTOM FOR PUSHERS							
ND1700T-TR	L1700669571	carry	open	300	247	0.47	
ND1700T-RET	L1700669601	return	open				
- plastic bushing diameter ø25 mm - holes ø 8.5 mm							

PLASTIC CASE CONVEYOR CHAINS




**STRAIGHT RUN
WITHOUT TABS**




Chain type	Code nr.	Link width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 600 XL	752.72.05	42.0	1.66	1.20	3950	50	457
NC-ACETAL							
CC 600 NC	752.75.05	42.0	1.66	1.20	3950	50	457
WPP-POLYPROPYLENE							
CC 600 WPP	752.77.05	42.0	1.66	1.00	1975	50	457

Standard length: 3.048 m - 10 feet (48 links)



**SIDEFLEX
WITH TABS**




Chain type	Code nr.	Link width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 600 TXL	752.72.04	42.0	1.66	1.25	3950	50	457
NC-ACETAL							
CC 600 TNC	752.75.04	42.0	1.66	1.25	3950	50	457
WPP-POLYPROPYLENE							
CC 600 TWPP	752.77.04	42.0	1.66	1.03	1975	50	457

Standard length: 3.048 m - 10 feet (48 links)

PLASTIC CASE CONVEYOR CHAINS




**SIDEFLEX
WITH TABS
WITH HIGHER LINK**



Chain type	Code nr.	Link width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 631 TXL	752.42.04	42.0	1.66	1.35	3950	50	457
NC-ACETAL							
CC 631 TNC	752.45.04	42.0	1.66	1.35	3950	50	457


Standard length: 3.048 m - 10 feet (48 links)

PLASTIC CASE CONVEYOR CHAINS



Chain type	Code nr.	Link width		Weight	Working load load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 1400 XL	752.32.05	50.0	1.97	1.70	6500	50	660
NC-ACETAL							
CC 1400 NC	752.35.05	50.0	1.97	1.70	6500	50	660

Standard length: 3.053 m - 10 feet (37 links)




Chain type	Code nr.	Link width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 1400 TXL	752.32.04	50.0	1.97	1.75	6500	50	660
NC-ACETAL							
CC 1400 TNC	752.35.04	50.0	1.97	1.75	6500	50	660

Standard length: 3.053 m - 10 feet (37 links)

PLASTIC CASE CONVEYOR CHAINS



**SIDEFLEX
REINFORCED
WITH TABS WITH HIGHER LINK**



Chain type	Code nr.	Link width		Weight	Working load (max.)	Backflex radius (min.)	Sideflex radius (min.)
		A					
		mm	inch	kg/m	N (21°C)	mm	mm
XL-ACETAL							
CC 1431 TXL	752.92.04	50.0	1.97	2.02	6500	50	660
NC-ACETAL							
CC 1431 TNC	752.95.04	50.0	1.97	2.02	6500	50	660

Standard length: 3.053 m - 10 feet (37 links)

* Ask customer service for minimum order quantity of CC1431 TBL chains.



SPROCKETS FOR CASE CONVEYOR CHAINS




Type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	
							MATERIAL page 209
SEMI-SPLIT SPROCKETS FOR CC600/631							
SPROCKET RING SET							
SR CC600 10	753.83.62	10	-	205.5	209.4	-	
SR CC600 14	753.83.65	14	-	285.4	289.8	-	
CARBON STEEL HUB							
CH CC-C 24	753.78.62	-	24	-	-	50	
STAINLESS STEEL HUB							
CH CC-S 24	753.78.61	-	24	-	-	50	
The split sprocket rings and unsplit hubs are supplied separately, so that the hub doesn't need to be replaced in case of wear of the sprocket rings.							
CLASSIC SPROCKETS FOR CC600/631							
METRIC BORES							
KU 600 06-20	L0600699111	6	20	127.0	128.0	50	
KU 600 08-20	L0600604046	8	20	165.9	177.7		
KU 600 10-20	L0600605916	10	20	205.5	219.3		
SEMI-SPLIT SPROCKETS FOR CC1400/1431							
SPROCKET RING SET							
SR CC1400 10	753.83.42	10	-	267.0	278.4	-	
CARBON STEEL HUB							
CH CC-C 24	753.78.62	-	24	-	-	50	
STAINLESS STEEL HUB							
CH CC-S 24	753.78.61	-	24	-	-	50	
The split sprocket rings and unsplit hubs are supplied separately, so that the hub doesn't need to be replaced in case of wear of the sprocket rings.							

PLATE TOP AND GRIPPER CHAINS

Rexnord has a wide variety of Plate Top and Gripper chains. The roller chain based Plate Top is developed for greater loading capacity and permits even higher speeds and longer runs than slatband chains. The roller based Gripper is perfect for product elevating, lowering, rinsing, sterilizing and inverting, by means of soft rubber gripper elements. The base chain is made of steel or stainless steel.

FEATURES

- Plate Top chains


These chains permit a huge loading capacity, higher speeds and longer runs with a single drive. The straight running 843- and the 1843-series have a roller base chain ANSI 40. The 12.7 mm small pitch reduces the sagging effect and permits the use of smaller sprockets. They are recommended for step by step positioning.

The straight running 1864- and 963-series have a roller base chain ANSI 60. The sideflexing 1874-, 1873-, and 3873-series have a roller base chain Side Bow ANSI 63 SB. They are also very suitable for step by step positioning.

Plate Top chains fitted with steel top plates are designed for abrasive and heavy duty or high-temperature conditions. 963-, 1873-, and 3873-series, with "snap-on" plastic top plates combine the benefits of a plastic conveying surface with those of a precision roller base chain: less slip-stick, high working load and accurate positioning; the replaceable top plates are clipped on to the protruding pins.

- Gripper chains

Main applications of Plate Top Gripper chains can be found in glass works. However, they can be used in various other situations, such as crate handling and can manufacturing. Typical Gripper solutions are omegas for easy crossing of production lines, all lifting and lowering with Gripper chain elevators. The grippers are provided in 2- or 3-finger grippers for smaller products and in D-type Grippers for other applications.



- Connection links

All roller based chains are supplied in 10 ft sections and provided with a connection link, so that the chains can be coupled very easily.

- Sprockets

Plate Top chains don't require special sprockets. Standard ANSI 40 and 60 sprockets will fit; therefore they are not part of Rexnord's standard offering.

PLATE TOP AND GRIPPER CHAINS

PROGRAMME

PLATE TOP	
1864	Straight running chains with steel top plates, suitable for heavy loads, long distances and high speeds. The chain consists of a base roller chain with welded on top plates in various steel alloys. The gap between the plates is 1.6 mm wide
963	Straight running chains with plastic overlapping top plates, therefore a uni-directional travel. The continuous surface facilitates stability and eases operations with unstable products
843	Straight running chains with plastic overlapping top plates, clipped on the protruding pins. Uni-directional travel
1843 TAB	Sideflexing tab chains with plastic top plates. Same construction as 843
1874 TAB	Sideflexing chains with steel "snap-on" top plates to form a continuous flat conveying surface. Hold-down tabs provide positive retention in curves and inclines. They will be used in abrasive and heavy duty or high-temperature conditions
1873 TAB	Sideflexing chains with plastic top plates; bi-directional travel. Also available with a rubber, anti-slip insert for inclined conveying up to 25°. The TAB guides permit to continue either from an inclined run to a plain one or vice versa
3873 TAB	Sideflexing chains with plastic top plates for a continuous surface, even in tight radius. Perfect for transport of trays.
	The Polycarbonate top plates are extreme resistant against impact
GRIPPER	
1874 TAB	Fitted with steel top plates for abrasive or high-temperature conditions. The base is a standard roller chain Side Bow ANSI 63 SB. The gripper elements are available as GD (smooth pad) and GJ (grooved pad); as clipped on they are easily replaceable. The clip for the TAB guide is riveted on the top plate. The heavy duty execution can handle higher loads, resulting in an increased tensile strength by 15%, and permits reduced stretching during operation. The heavy duty design of the top plates implies that guide and top plate are a single unit
1843 TAB	Fitted with thermoplastic top plates for a quieter and smoother operation; these mini-gripper chains enable reduction of plant weight, increase of conveying speed and dry service. The base is a standard roller chain Side Bow ANSI 43 SB. The clipped on gripper elements are available as GD (smooth pad) and GJ (grooved pad). These chains are specially suited for conveying ampoules, test tubes and other minute products, such as small industrial components
1873 TAB	Fitted with thermoplastic top plates for a quieter and smoother operation, enabling reduction of plant weight, increase of conveying speed and dry service. The base chain is a standard roller chain Side Bow ANSI 63 SB. GSD/GS2J/GS3J grippers are clipped on for easy replacement, GDB/GJB grippers are resistant to bending and GJM grippers are integrated in the top plate, ideal for packaging applications
The chain description consists of respectively the material, type, a K number for the plate width in inches, a G for grippers and a code indicating the gripper execution: D for D-style grippers, providing a smooth pad or flat surface; J for grooved path, in some cases combined with the number of gripper fingers per link. Finally S means a special rubber gripper assembly system, resistant to bending. M stands for an integrated gripper, moulded into the top plate, ideal for packaging applications.	



PLATE TOP CHAIN TYPE	APPLICATION								
	Clean, dry, light duty	Clean, wet, light duty	Abrasive, dry, light duty	Abrasive, wet, light duty	Clean, dry, heavy duty	Clean, wet, heavy duty	Abrasive, dry, heavy duty	Abrasive, wet, heavy duty	Incline conveyor
1864									
1864 SS									
963									
843									
1843 TAB									
1874 TAB									
1873 TAB, LF top plate									
1873 TAB, WX top plate									
3873 TAB									
HFP 1873 TAB									

GRIPPER CHAIN TYPE	APPLICATION						
	Small empty product elevator	Small full product elevator	Large empty product elevator	Large full product elevator	High load, abrasive application	Rinser application, ambient	Rinser application, high temperature
1874 TAB, stainless steel top plate							
1874 TAB HD, stainless steel top plate							
1843 TAB, LF top plate							
1873 TAB, HP top plate							
1873 TAB, LF top plate							

Steel base chains are recommended for dry applications, stainless steel base chains are recommended for wet applications.

Best choice
Optional

PLATE TOP CHAINS




MATERIAL

page 208

Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Connection link	
		A					type	code nr.
		mm	inch					
STEEL TOP PLATE/STEEL BASE CHAIN								
1864-K325	814036213	82.5	3.25	3.33	514-113-13	4500	CL-1864 CA	514-331-1
1864-K450	814036219	114.3	4.50	4.00	514-113-19			
1864-K600	814036223	152.4	6.00	4.40	514-113-23			
1864-K750	814036225	190.5	7.50	4.80	514-113-25			
STAINLESS STEEL TOP PLATE/STAINLESS STEEL BASE CHAIN								
1864 SS-K325	814036313	82.5	3.25	3.33	514-114-13	3400	CL-1864 SS	514-115-1
1864 SS-K450	814036319	114.3	4.50	4.00	514-114-19			
1864 SS-K600	814036323	152.4	6.00	4.40	514-114-23			
1864 SS-K750	814036325	190.5	7.50	4.80	514-114-25			

Standard length: 3.048 m – 10 feet (160 links). Min. backflex radius 305 mm.




MATERIAL

page 208

Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Connection link	
		A					type	code nr.
		mm	inch					
LF-ACETAL TOP PLATE/STEEL BASE CHAIN								
LF 963-K325	L0963604431	82.5	3.25	2.10	114-139-5	2700	CL-63	36742
LF 963-K450	L0963604441	114.3	4.50	2.23	114-139-6			
LF 963-K600	L0963604451	152.4	6.00	2.53	114-139-7			
LF 963-K750	L0963604461	190.5	7.50	2.68	114-139-8			
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN								
LF 963 SS-K325	L0963604471	82.5	3.25	2.10	114-139-5	1900	CL-63 SS	36747
LF 963 SS-K450	L0963604481	114.3	4.50	2.23	114-139-6			
LF 963 SS-K600	L0963604491	152.4	6.00	2.53	114-139-7			
LF 963 SS-K750	L0963604501	190.5	7.50	2.68	114-139-8			

Standard length: 3.048 m – 10 feet (160 links). Min. backflex radius 153 mm.

PLATE TOP CHAINS




MATERIAL
page 208

Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Connection link	
		A						
		mm	inch	kg/m	code nr.	N (21°C)	type	code nr.
LF-ACETAL TOP PLATE/STEEL BASE CHAIN								
LF 843-K138	L0843604271	34.9	1.38	0.83	L0843621601	2700	CL-843	36418
LF 843-K144	L0843604281	36.5	1.44	0.84	L0000601742			
LF 843-K200	L0843604291	50.8	2.00	0.89	L0000669391			
LF 843-K325	L0843604301	82.5	3.25	1.03	L0843623581			
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN								
LF 843 SS-K138	L0843604311	34.9	1.38	0.83	L0843621601	1900	CL-843 SS	69479
LF 843 SS-K144	L0843604321	36.5	1.44	0.84	L0000601742			
LF 843 SS-K200	L0843604331	50.8	2.00	0.89	L0000669391			
LF 843 SS-K325	L0843604341	82.5	3.25	1.03	L0843623581			

Standard length: 3.048 m – 10 feet (240 links).

Min. backflex radius 153 mm.



upon request


MATERIAL
page 208

Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						type	code nr.
		mm	inch						
LF-ACETAL TOP PLATE/STEEL BASE CHAIN									
LF 1843 TAB-K125	L1843604601	31.8	1.25	0.74	114-495-1	2700	254	CL-1843	1843-MO-CL
LF 1843 TAB-K200	L1843688961	50.8	2.00	0.90	114-1448-1				

Standard length: 3.048 m – 10 feet (240 links).

Min. backflex radius 102 mm.

PLATE TOP CHAINS




Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						type	code nr.
		mm	inch	kg/m	code nr.	N (21°C)	mm		
STEEL TOP PLATE/STEEL BASE CHAIN									
1874 TAB-K325	1874K3-1/4	82.5	3.25	4.20	114-130-1	4500	381	CL-63	36742
1874 TAB-K450	1874K4-1/2	114.3	4.50	4.80	114-130-2		381		
1874 TAB-K600	1874K6	152.4	6.00	5.70	114-130-6		457		
1874 TAB-K750	1874K7-1/2	190.5	7.50	6.40	114-130-3		610		
STAINLESS STEEL TOP PLATE/STAINLESS STEEL BASE CHAIN									
1874 TAB SS-K325	1874SSK3-1/4	82.5	3.25	4.20	114-130-4	3400	381	CL-63 SS	36747
1874 TAB SS-K450	1874SSK4-1/2	114.3	4.50	4.80	114-130-5		381		
1874 TAB SS-K600	1874SSK6	152.4	6.00	5.70	114-130-8		457		
1874 TAB SS-K750	1874SSK7-1/2	190.5	7.50	6.40	114-130-7		610		

Standard length: 3.048 m – 10 feet (160 links).

Min. backflex radius 254 mm.

PLATE TOP CHAINS



Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Sideflex radius (min.)	Connection link	
		A							
		mm	inch	kg/m	code nr.	N (21°C)	mm	type	code nr.
LF-ACETAL TOP PLATE/STEEL BASE CHAIN									
LF 1873 TAB-K325	L1873604731	82.5	3.25	2.10	L1873615621	4500	356	CL-63	36742
LF 1873 TAB-K450	L1873604741	114.3	4.50	2.30	L1873LF623621				
LF 1873 TAB-K600	L1873604751	152.4	6.00	2.40	L1873LF631801				
LF 1873 TAB-K750	L1873604761	190.5	7.50	2.60	L1873LF622011				
LF 1873 TAB-K1000	L1873604771	254.0	10.00	2.80	L1873LF610701				
LF 1873 TAB-K1200	L1873604781	304.8	12.00	3.00	L1873LF645071				
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN									
LF 1873 TAB SS-K325	L1873604791	82.5	3.25	2.10	L1873615621	3400	356	CL-63 SS	36747
LF 1873 TAB SS-K450	L1873604801	114.3	4.50	2.30	L1873LF623621				
LF 1873 TAB SS-K600	L1873604811	152.4	6.00	2.40	L1873LF631801				
LF 1873 TAB SS-K750	L1873604821	190.5	7.50	2.60	L1873LF622011				
LF 1873 TAB SS-K1000	L1873604831	254.0	10.00	2.80	L1873LF610701				
LF 1873 TAB SS-K1200	L1873604841	304.8	12.00	3.00	L1873LF645071				
WX-POLYAMIDE COMPOSITE TOP PLATE/STEEL BASE CHAIN									
WX 1873 TAB-K450	L1873683652*	114.3	4.50	2.30	L1873610683	4500	356	CL-63 SS	36742

Standard length: 3.048 m – 10 feet (160 links).


Min. backflex radius 305 mm.

* Ask customer service for minimum order quantity of WX 1873 chains.

PLATE TOP CHAINS



**SIDEFLEX 3/4" PITCH TAB
PLASTIC TOP PLATE
CLOSED SURFACE**




Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Sideflex radius (min.)	Connection link	
		A							
		mm	inch	kg/m	code nr.	N (21°C)	mm	type	code nr.
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN									
LF 3873 TAB SS-K1000	L3873604921	254.0	10.00	3.10	114-129-2	3400	457	CL-63 SS	36747
PC POLYCARBONATE TOP PLATE/STAINLESS STEEL BASE CHAIN									
WPC 3873 TAB SS-K1200	L3873604941	304.8	12.00	3.20	114-1046-5	3400	610	CL-63 SS	36747

Standard length: 3.048 m – 10 feet (160 links).

Min. backflex radius 178 mm.



**SIDEFLEX 3/4" PITCH TAB
PLASTIC TOP PLATE
WITH RUBBER**



Chain type	Code nr.	Plate width		Weight	Loose top plate	Working load (max.)	Sideflex radius (min.)	Connection link	
		A							
		mm	inch	kg/m	code nr.	N (21°C)	mm	type	code nr.
LF-ACETAL TOP PLATE/STEEL BASE CHAIN									
HFP 1873 TAB-K750	L1873648142	190.5	7.50	3.10	L1873635192	4500	457	CL-63	36742
HFP 1873 TAB-K1000	L1873648152	254.0	10.00	3.40	L1873635222				
HFP 1873 TAB-K1200	L1873645302	304.8	12.00	3.60	L1873635252		610		
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN									
HFP 1873 TAB SS-K750	L1873653102	190.5	7.50	3.10	L1873635192	3400	457	CL-63 SS	36747
HFP 1873 TAB SS-K1000	L1873645522	254.0	10.00	3.40	L1873635222				
HFP 1873 TAB SS-K1200	L1873644202	304.8	12.00	3.60	L1873635252		610		


Standard length: 3.048 m – 10 feet (160 links).

Rubber: SEBS grey; 60 shore A hardness. Other rubber patterns and materials are possible.

Min. backflex radius 305 mm.

* Ask customer service for minimum order quantity of HFP 1873 TAB chains


PLATE TOP GRIPPER CHAINS



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						
		mm	inch	kg/m	N (21°C)	mm	type	code nr.
STEEL TOP PLATE/STEEL BASE CHAIN								
1874 TAB-K363 GDB	L1874606541	92.1	3.63	5.60	4500	381	CL-63	36742
1874 TAB-K363 GJB	L1874606322							
STAINLESS STEEL TOP PLATE/STAINLESS STEEL BASE CHAIN								
1874 TABSS-K363 GDB	L1874606581	92.1	3.63	5.60	3400	381	CL-63 SS	36747
1874 TABSS-K363 GJB	L1874606591							

Standard length: 3.048 m – 10 feet (160 links).

Gripper: EPDM black; 50 shore A hardness.





Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A					type	code nr.
		mm	inch					
STEEL TOP PLATE/STEEL BASE CHAIN								
1874 TAB HD-K363 GDB	L1874695701	92.1	3.63	6.30	4900	400	CL-1874 HD	102910
1874 TAB HD-K363 GJB	L1874606332							
STAINLESS STEEL TOP PLATE/STAINLESS STEEL BASE CHAIN								
1874 TAB HDSS-K363 GJB	L1874606342	92.1	3.63	6.30	3700	400	CL-1874 HD SS	102406
1874 TAB HDSS-K363 GDB	L1874695711							

Standard length: 3.048 m – 10 feet (160 links).

Gripper: EPDM black; 50 shore A hardness.

PLATE TOP GRIPPER CHAINS




MATERIAL
page 208

Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A					type	code nr.
		mm	inch	kg/m	N (21°C)	mm		
LF-ACETAL TOP PLATE/STEEL BASE CHAIN								
LF 1843 TAB-K150 GDB	L1843606461	38.1	1.50	1.20	2700	254	CL-1843	1843-MO-CL
LF 1843 TAB-K150 GJB	L1843606471							
LF-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN								
LF 1843 TABSS-K150 GDB	L1843606481	38.1	1.50	1.20	1900	254	CL-1843 SS	1843 SS-MO-CL
LF 1843 TABSS-K150 GJB	L1843606491							

Standard length: 3.048 m – 10 feet (240 links).

Gripper: EPDM black; 40 shore A hardness.



MATERIAL
page 123

MATERIAL
page 208

Chain type	Code nr.	Plate width A		Gripper width C	Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		mm	pollici	mm	kg/m	N (21°C)	mm	type	code nr.
HP-ACETAL TOP PLATE/STEEL BASE CHAIN									
HP 1873 TAB-K325 GSD	L1873628703	82,5	3.25	70	2.90	4500	381	CL-63	36742
HP 1873 TAB-K450 GSD	L1873631143	114,3	4.50	102	3.00				
HP-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN									
HP 1873 TABSS-K325 GSD	L1873628753	82,5	3.25	70	2.90	3400	381	CL-63 SS	36747
HP 1873 TABSS-K450 GSD	L1873631383	114,3	4.50	102	3.00				


Standard length: 3.048 m – 10 feet (160 links).

Gripper: EPDM grey; 55 shore A hardness.

PLATE TOP GRIPPER CHAINS



SNAP-ON 2-FINGER GRIPPER
¾" PITCH
PLASTIC TAB



page 123



MATERIAL


page 207

Chain type	Code nr.	Plate width		Gripper width C	Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A							
		mm	pollici	mm	kg/m	N (21°C)	mm	type	code nr.
HP-ACETAL TOP PLATE /STEEL BASE CHAIN									
HP 1873 TAB-K325 GS2J	L1873628693	82.5	3.25	77	2.90	4500	381	CL-63	36742
HP 1873 TAB-K450 GS2J	L1873628713	114.3	4.50	108	3.00				
HP-ACETAL TOP PLATE /STAINLESS STEEL BASE CHAIN									
HP 1873 TABSS-K325 GS2J	L1873628743	82.5	3.25	77	2.90	3400	381	CL-63 SS	36747
HP 1873 TABSS-K450 GS2J	L1873628763	114.3	4.50	108	3.00				

Standard length: 3.048 m – 10 feet (160 links). Gripper: EPDM black; 45 shore



SNAP-ON 3-FINGER GRIPPER
¾" PITCH
PLASTIC TAB



page 123



MATERIAL

page 207


Chain type	Code nr.	Plate width		Gripper width C	Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A							
		mm	pollici	mm	kg/m	N (21°C)	mm	type	code nr.
HP-ACETAL TOP PLATE /STEEL BASE CHAIN									
HP 1873 TAB-K325 GS3J	L1873628673	82.5	3.25	82.5	2.90	4500	381	CL-63	36742
HP 1873 TAB-K450 GS3J	L1873631773	114.3	4.50	107	3.00				
HP-ACETAL TOP PLATE /STAINLESS STEEL BASE CHAIN									
HP 1873 TABSS-K325 GS3J	L1873628723	82.5	3.25	82.5	2.90	3400	381	CL-63 SS	36747
HP 1873 TABSS-K450 GS3J	L1873632733	114.3	4.50	107	3.00				
HP-ACETAL TOP PLATE /STEEL BASE CHAIN									
HP 1873 TAB-K325 GS3JA	L1873628683	82.5	3.25	82.5	2.90	4500	381	CL-63	36742
HP 1873 TAB-K450 GS3JA	L1873631863	114.3	4.50	109	3.00				
HP-ACETAL TOP PLATE /STAINLESS STEEL BASE CHAIN									
HP 1873 TABSS-K325 GS3JA	L1873628733	82.5	3.25	82.5	2.90	3400	381	CL-63 SS	36747
HP 1873 TABSS-K450 GS3JA	L1873631873	114.3	4.50	109	3.00				

Standard length: 3.048 m – 10 feet (160 links). Gripper EPDM grey 55 shore A hardness for GS3J K325-K450, gripper black for GS3JA K450 45 shore A hardness.

PLATE TOP GRIPPER CHAINS



CLOSED GRIPPER
3/4" PITCH
PLASTIC TAB



* 34.1 FOR STRAIGHT RUNNING CHAINS




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						
		mm	pollici	kg/m	N (21°C)	mm	type	code nr.
HP-ACETAL TOP PLATE/STEEL BASE CHAIN								
HP 1873 TAB-K375 GSD	L1873677162	95.3	3.75	2.80	4500	381	CL-63	36742
HP-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN								
HP 1873 TABSS-K375 GSD	L1873677172	95.3	3.75	2.80	3400	381	CL-63 SS	36747

Standard length: 3.048 m – 10 feet (160 links)

Gripper: EPDM Grey; 55 shore A hardness



3-FINGER GRIPPER
3/4" PITCH
PLASTIC TAB




Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						
		mm	pollici	kg/m	N (21°C)	mm	type	code nr.
HP-ACETAL TOP PLATE/STEEL BASE CHAIN								
HP 1873 TAB-K375 GS3J	L1873677082	95.3	3.75	2.80	4500	381	CL-63	36742
HP-ACETAL TOP PLATE/STAINLESS STEEL BASE CHAIN								
HP 1873 TABSS-K375 GS3J	L1873677092	95.3	3.75	2.80	3400	381	CL-63 SS	36747

Standard length: 3.048 m – 10 feet (160 links)

Gripper: EPDM Grey; 55 shore A hardness

PLATE TOP GRIPPER CHAINS



Chain type	Code nr.	Plate width		Weight	Working load (max.)	Sideflex radius (min.)	Connection link	
		A						
		mm	pollici	kg/m	N (21°C)	mm	type	code nr.
LF-ACETAL TOP PLATE /STEEL BASE CHAIN								
LF 1873 TAB-K325 GJM	L1873649841	82.5	3.25	3.00	4500	356	CL-63	36742
LF-ACETAL TOP PLATE /STAINLESS STEEL BASE CHAIN								
LF 1873 TABSS-K325 GJM	L1873613912	82.5	3.25	3.00	3400	356	CL-63 SS	36747

Standard length: 3.048 m – 10 feet (160 links).

Gripper: TPE black; 75 shore A hardness.

* Ask customer service for minimum order quantity of 1873 TAB GJM chains.


CURVES AND STRAIGHT TRACKS

For steel and plastic sideflexing chains Rexnord offers the corresponding curve profiles. Without a doubt Magnetflex® is worldwide seen as the superior curve system. The programme also includes curves and straight tracks for Bevel and TAB chains.


Magnetflex® system

The MCC Magnetflex system has become the worldwide standard in the beverage industry. The great advantages of this patented system have made it the choice of the worlds leading OEMs. It is a Combi system for both plastic and steel chains. Magnets underneath the track hold the chain down in a reliable way.

Magnetflex is the only system where two magnets cover almost the complete base of the curve instead of just the track. Because the magnets are connected by a steel plate, a very broad magnetic field is being formed. Unlike other magnetic curves this results in a force that keeps down plastic chains with steel pins just as well as steel chains. Another advantage is that this magnet position only has a slight reduction in hold-down force when the chain is being lifted, in case of pollution or broken glass, without jumping from the track. Where in other systems the chains can block and jam in the curve profile due to pollution, in the Magnetflex system the chain simply lifts slightly and keeps on running. The magnets are placed in the curve at fixed angles instead of at fixed distances to make sure that no pulsation effect is being created by the magnets, when a chain is being pulled through the curve.



MAGNETFLEX CURVE WITH 2 MAGNETS FOR BETTER HOLD-DOWN OF THE CHAIN




USUAL MAGNETIC CURVE WITH ONLY 1 MAGNET


The magnets make sure that all chains lie perfectly flat in the curve without tilting. In other systems the chain tension is causing the chain to use up the play in the chain guidance, causing chain edges to lift. Especially in multiple-strand curves and with high-speed conveying this means product toppling.

Another big advantage of the Magnetflex system is the easy installation of the chains and the perfect cleanability of the system. This is due to the open and rectangular track in the curve. The chains can easily be installed from above as if the curve was a straight part of the conveyor. Also the chains can easily be lifted from the track for maintenance and cleaning, without breaking the chain or even removing it from the conveyor construction.

Magnetflex curves can be installed in the conveyor frame in different ways. The upper and return part can be supplied bolted together and with inserts to mount the assembled curve into the conveyor frame. The option most often used in multiple track curves is to deliver the upper and return part separately. They are then mounted against a conveyor crossbar. In this case both upper part and return part are equipped with inserts and/or holes. In both build-in options the hole and inserts can be standard or customer specific.




UPPER AND RETURN PART BOLTED TOGETHER




UPPER AND RETURN PART MOUNTED AGAINST A CROSS BAR


Most Magnetflex curves are equipped with a return guide shoe. This machined shoe is meant to bring the chain at the right level to enter the return part of the curve. The position of the return guide shoe is determined by the design of the return part (level or staggered) and by the chain type. A staggered design is used when the pitch between the tracks is too small to allow the chains to run at the same level in the return. In that case two levels of tracks are made in the return part: one level in which the uneven tracks (1, 3, 5 etc.) run and one in which the even tracks run. The height of a staggered return part (usually 63 mm) is always higher than that of a non-staggered return (usually 55 mm).



RETURN PART AT SAME LEVEL



STAGGERED RETURN PART




CHAINBELTS

A special execution of a Magnetflex curve is a CIP (Cleaning in Place) curve, equipped with spraying nozzles and tubes. It is opened up as much as possible to allow good cleaning of the steel or plastic chain and curve profile from the inside of the curve. The CIP curve can be integrated in an existing CIP system.

CURVES AND STRAIGHT TRACKS

Magnetflex curves are available in four different materials. The standard material, Combi-A, is a high grade of polyethylene. It is suitable for most lubricated applications with steel and plastic chains. In clean environment and with low chain speeds Combi-A can also be used in dry running applications. For dry running applications with plastic TableTop chains Combi-L and Combi-S are recommended. These materials are able to work with higher chain speeds. Combi-S has the largest application field, where Combi-L offers better noise reduction. Rexnord's calculation program determines the PV (pressure-velocity) load on the curve in a specific application and will advise in which application load and speed require Combi-L or Combi-S curves. For lubricated, abrasive applications (filler discharge) or abrasive, dry running applications (glassworks) with (stainless) steel chains, Combi-G is most suitable. This ceramic reinforced polyethylene offers an extremely good wear resistance.



FROM LEFT TO RIGHT: COMBI-A, -G, -S AND -L

CURVE MATERIAL	APPLICATION						
	Lubricated, clean, stainless steel chains plastic chains	Lubricated, abrasive, stainless steel chains	Lubricated, abrasive, plastic chains	Dry running, low speed, abrasive, steel chains	Dry running, low speed, clean, plastic chains	Dry running high speed, clean plastic chains	Dry running, high speed, abrasive, plastic chains
Combi-A							
Combi-L							
Combi-S							
Combi-G							

Best choice
Optional

Combi-C Non Marking Tubular Returnpart

With today's high speed conveyor applications and sometimes also abrasive conditions, it is required that the chain surface remains in optimum condition to avoid any unwanted product handling issues. Therefore Rexnord has developed a special Non Marking returnpart section to be combined with the standard Magnetflex upper part. This new returnpart features a Stainless Steel tubular return which reduces abrasive wear of the chain topsurface. The result is that the chain surface will remain in perfect condition over a long period of time, and optimum product handling at high speeds can be achieved.



RETURNPART EQUIPPED WITH TUBES

Tab and Bevel



In many industry segments Tab and Bevel curves and straight tracks are an economic solution if stability of the product conveyed, cleanliness and ease of installation are not the key areas of interest. They are available for TableTop, Multiflex and Plate Top chains. Tab and Bevel machined profiles retain the chains in a mechanical way. For these tracks a high grade, wear resistant polyethylene is used.

Customized curves

If these standard versions do not meet specific conveyor needs, it is possible to order customized versions. Both standard and customer specific curves can be supplied in just several working days.



MAGNETFLEX CURVES



SELECTION TABLES

Select your curve by reading the tables from left to right. You'll find more information on the specified pages.


For chain type(s)	Radius	Pitch	Basic width B	Infeed length L	Total height H	Version number	See page	
	R	P						
	mm	mm	mm	mm	mm			
FOR CHAINS WITH 3.25"/3.30" PLATE WIDTH								
Steel/plastic	500	85	100	0	82 / 90	C7	109	
				100	90	C6	109	
			111	100	90	C4	106	
				100	90	C14	110	
		89	100	125	82	C1	105	
		90	100	100	82	C2	105	
			110	0	82	C3	106	
		590	180	100	100	82	C5B	107
		680	–	100	100	82	C5A	107
		750	85	111	100	90	C42	112
	860	–	100	125	82	C5C	108	
	1000	–	100	0	82	C5D	108	
		85	111	100	90	C43	112	
	CIP-CURVE FOR CHAINS WITH 3.25" PLATE WIDTH FOR CHAINS WITH 4.50" PLATE WIDTH							
661 steel	500	85	100	100	82	CF6	110	
Steel	500	85	111	100	100	CIP4	119	
Steel/plastic	500	120	129	125	90	C21A	111	
	610	120	129	125	90	C22A	111	
FOR CHAINS WITH 7.50" PLATE WIDTH								
Steel	610	196	214	125	90	C61	113	
	860	–	214	0	82	C66	114	
	1000	–	214	0	82	C65	114	
Steel / HDFM 750 (SG)	610	195	200	100	95	C81	115	
	860	–	214	0	87	C86	115	
FOR CHAINS WITH 10.00" PLATE WIDTH								
HDFM 1000 (SG)	860	–	290	0	87	C91	116	
FOR CHAINS WITH 12.00" PLATE WIDTH								
HDFM 1200 (SG)	860	–	340	0	87	C96	116	
FOR LBP CHAINS								
RHMD 325 LBP	500	90	100	100	90	LBP2	117	
HDFM 750 LBP	860	–	214	0	95	LBP861	117	
HDFM 1000 LBP	860	–	290	0	95	LBP91	118	
HDFM 1200 LBP	860	–	340	0	95	LBP96	118	
FOR CHAINBELTS								
FGM 1050/FTM 1060	500	85	100	100	90	CB6	119	
FTM 1055 K330	500	85	100	100	90	CC6	120	
FTM 1055 K450	500	120	129	125	90	CC21	120	

All these Magnetflex curves include a return guide shoe, except C7. Inserts are optional; M8 or M10 inserts in the return part and M6 or M8 inserts in the guide shoe can be supplied according your detailed drawing. If you need a special Magnetflex curve, following parameters are necessary:



1. Basic width
2. Radius
3. Infeed length
4. Pitch
5. Angle
6. Number of tracks

For tab and bevel curves see page 121-126.

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	189 mm	278 mm	367 mm	456 mm	545 mm
VERSION C1						
15°	704.05.16	704.05.17	704.05.18	704.05.19	704.05.20	704.05.21
30°	704.05.31	704.05.32	704.05.33	704.05.34	704.05.35	704.05.36
45°	704.05.46	704.05.47	704.05.48	704.05.49	704.05.50	704.05.51
60°	704.05.61	704.05.62	704.05.63	704.05.64	704.05.65	704.05.66
75°	704.05.76	704.05.77	704.05.78	704.05.79	704.05.80	704.05.81
90°	704.05.01	704.05.02	704.05.03	704.05.04	704.05.05	704.05.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	190 mm	280 mm	370 mm	460 mm	550 mm
VERSION C2						
15°	704.06.16	704.06.17	704.06.18	704.06.19	704.06.20	704.06.21
30°	704.06.31	704.06.32	704.06.33	704.06.34	704.06.35	704.06.36
45°	704.06.46	704.06.47	704.06.48	704.06.49	704.06.50	704.06.51
60°	704.06.61	704.06.62	704.06.63	704.06.64	704.06.65	704.06.66
75°	704.06.76	704.06.77	704.06.78	704.06.79	704.06.80	704.06.81
90°	704.06.01	704.06.02	704.06.03	704.06.04	704.06.05	704.06.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	110 mm	200 mm	290 mm	380 mm	470 mm	560 mm
VERSION C3						
15°	704.07.16	704.07.17	704.07.18	704.07.19	704.07.20	704.07.21
30°	704.07.31	704.07.32	704.07.33	704.07.34	704.07.35	704.07.36
45°	704.07.46	704.07.47	704.07.48	704.07.49	704.07.50	704.07.51
60°	704.07.61	704.07.62	704.07.63	704.07.64	704.07.65	704.07.66
75°	704.07.76	704.07.77	704.07.78	704.07.79	704.07.80	704.07.81
90°	704.07.01	704.07.02	704.07.03	704.07.04	704.07.05	704.07.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84




Nr. of tracks	1	2	3	4	5	6
Width W	111 mm	196 mm	281 mm	366 mm	451 mm	536 mm
VERSION C4						
15°	704.08.16	704.08.17	704.08.18	704.08.19	704.08.20	704.08.21
30°	704.08.31	704.08.32	704.08.33	704.08.34	704.08.35	704.08.36
45°	704.08.46	704.08.47	704.08.48	704.08.49	704.08.50	704.08.51
60°	704.08.61	704.08.62	704.08.63	704.08.64	704.08.65	704.08.66
75°	704.08.76	704.08.77	704.08.78	704.08.79	704.08.80	704.08.81
90°	704.08.01	704.08.02	704.08.03	704.08.04	704.08.05	704.08.06




More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84


MAGNETFLEX CURVES





Nr. of tracks	1		
Width W	100 mm		
VERSION C5A			
15°	704.09.16		
30°	704.09.31		
45°	704.09.46		
60°	704.09.61		
75°	704.09.76		
90°	704.09.01		



RADIUS




RETURN GUIDE SHOE



More than 1 track on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84





Nr. of tracks	2		
Width W	280 mm		
VERSION C5B			
15°	704.10.17		
30°	704.10.32		
45°	704.10.47		
60°	704.10.62		
75°	704.10.77		
90°	704.10.02		

A technical drawing of a curved track section. It shows two parallel tracks curving at a 90-degree angle. The radius of the curve is indicated as R=590. The width of the track is 100. The diagram includes dimension lines and a curved arrow indicating the direction of travel.

RADIUS

A technical drawing of a return guide shoe assembly. It shows a shoe with four rollers. The dimensions are 15, 20, 10, and MB. The diagram includes dimension lines and a curved arrow indicating the direction of travel.



RETURN GUIDE SHOE





Special twin-track design for crate conveyors.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84

MAGNETFLEX CURVES




Nr. of tracks	1	
Width W	100 mm	
VERSION C5C		
15°	704.11.16	
30°	704.11.31	
45°	704.11.46	
60°	704.11.61	
75°	704.11.76	
90°	704.11.01	





More than 1 track on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM, SSC 581 M-K325
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84




Nr. of tracks	1	
Width W	100 mm	
VERSION C5D		
15°	704.12.16	
30°	704.12.31	
45°	704.12.46	
60°	704.12.61	
75°	704.12.76	
90°	704.12.01	





More than 1 track on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM, SSC 581 M-K325
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	440 mm	525 mm
VERSION C6						
15°	704.14.16	704.14.17	704.14.18	704.14.19	704.14.20	704.14.21
30°	704.14.31	704.14.32	704.14.33	704.14.34	704.14.35	704.14.36
45°	704.14.46	704.14.47	704.14.48	704.14.49	704.14.50	704.14.51
60°	704.14.61	704.14.62	704.14.63	704.14.64	704.14.65	704.14.66
75°	704.14.76	704.14.77	704.14.78	704.14.79	704.14.80	704.14.81
90°	704.14.01	704.14.02	704.14.03	704.14.04	704.14.05	704.14.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	440 mm	525 mm
VERSION C7						
15°	704.15.16	704.15.17	704.15.18	704.15.19	704.15.20	704.15.21
30°	704.15.31	704.15.32	704.15.33	704.15.34	704.15.35	704.15.36
45°	704.15.46	704.15.47	704.15.48	704.15.49	704.15.50	704.15.51
60°	704.15.61	704.15.62	704.15.63	704.15.64	704.15.65	704.15.66
75°	704.15.76	704.15.77	704.15.78	704.15.79	704.15.80	704.15.81
90°	704.15.01	704.15.02	704.15.03	704.15.04	704.15.05	704.15.06





More than 6 tracks on request. The height of the return part is 55 mm in case of a single track C7.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	111 mm	196 mm	281 mm	366 mm	451 mm	536 mm
VERSION C14						
15°	704.19.16	704.19.17	704.19.18	704.19.19	704.19.20	704.19.21
30°	704.19.31	704.19.32	704.19.33	704.19.34	704.19.35	704.19.36
45°	704.19.46	704.19.47	704.19.48	704.19.49	704.19.50	704.19.51
60°	704.19.61	704.19.62	704.19.63	704.19.64	704.19.65	704.19.66
75°	704.19.76	704.19.77	704.19.78	704.19.79	704.19.80	704.19.81
90°	704.19.01	704.19.02	704.19.03	704.19.04	704.19.05	704.19.06





More than 6 tracks on request. C14 curves include inserts, of which the pattern varies per angle.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84





Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	440 mm	525 mm
VERSION CF6						
15°	624.38.16	624.38.17	624.38.18	624.38.19	624.38.20	624.38.21
30°	624.38.31	624.38.32	624.38.33	624.38.34	624.38.35	624.38.36
45°	624.38.46	624.38.47	624.38.48	624.38.49	624.38.50	624.38.51
60°	624.38.61	624.38.62	624.38.63	624.38.64	624.38.65	624.38.66
75°	624.38.76	624.38.77	624.38.78	624.38.79	624.38.80	624.38.81
90°	624.38.01	624.38.02	624.38.03	624.38.04	624.38.05	624.38.06





More than 6 tracks on request.

- Other curves, such as CF4, CF7, CF42 and CF5C can be supplied as well. Please ask Technical Support for all details.
- For steel chains: 661 M 31 SM, 661 M 84 SM

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	
Width W	129 mm	249 mm	369 mm	489 mm	
VERSION C21A					
15°	714.08.16	714.08.17	714.08.18	714.08.19	
30°	714.08.31	714.08.32	714.08.33	714.08.34	
45°	714.08.46	714.08.47	714.08.48	714.08.49	
60°	714.08.61	714.08.62	714.08.63	714.08.64	
75°	714.08.76	714.08.77	714.08.78	714.08.79	
90°	714.08.01	714.08.02	714.08.03	714.08.04	





More than 4 tracks on request.

- For steel chains: 10/60 M 42 M
- For plastic chains: RHM 450, RHMD 450




Nr. of tracks	1	2	3	4	
Width W	129 mm	249 mm	369 mm	489 mm	
VERSION C22A					
15°	714.09.16	714.09.17	714.09.18	714.09.19	
30°	714.09.31	714.09.32	714.09.33	714.09.34	
45°	714.09.46	714.09.47	714.09.48	714.09.49	
60°	714.09.61	714.09.62	714.09.63	714.09.64	
75°	714.09.76	714.09.77	714.09.78	714.09.79	
90°	714.09.01	714.09.02	714.09.03	714.09.04	





More than 4 tracks on request.

- For steel chains: 10/60 M 42 M
- For plastic chains: RHM 450, RHMD 450

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	111 mm	196 mm	281 mm	366 mm	451 mm	536 mm
VERSION C42						
15°	704.28.16	704.28.17	704.28.18	704.28.19	704.28.20	704.28.21
30°	704.28.31	704.28.32	704.28.33	704.28.34	704.28.35	704.28.36
45°	704.28.46	704.28.47	704.28.48	704.28.49	704.28.50	704.28.51
60°	704.28.61	704.28.62	704.28.63	704.28.64	704.28.65	704.28.66
75°	704.28.76	704.28.77	704.28.78	704.28.79	704.28.80	704.28.81
90°	704.28.01	704.28.02	704.28.03	704.28.04	704.28.05	704.28.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84




Nr. of tracks	1	2	3	4	5	6
Width W	111 mm	196 mm	281 mm	366 mm	451 mm	536 mm
VERSION C43						
15°	704.29.16	704.29.17	704.29.18	704.29.19	704.29.20	704.29.21
30°	704.29.31	704.29.32	704.29.33	704.29.34	704.29.35	704.29.36
45°	704.29.46	704.29.47	704.29.48	704.29.49	704.29.50	704.29.51
60°	704.29.61	704.29.62	704.29.63	704.29.64	704.29.65	704.29.66
75°	704.29.76	704.29.77	704.29.78	704.29.79	704.29.80	704.29.81
90°	704.29.01	704.29.02	704.29.03	704.29.04	704.29.05	704.29.06




More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM, SSC 581 M-K325
- For plastic chains: RHMP 325, RHMDP 325, RHMP 84


MAGNETFLEX CURVES



Nr. of tracks	1	2	3	4	
Width W	214 mm	410 mm	606 mm	802 mm	
VERSION C61					
15°	724.05.16	724.05.17	724.05.18	724.05.19	
30°	724.05.31	724.05.32	724.05.33	724.05.34	
45°	724.05.46	724.05.47	724.05.48	724.05.49	
60°	724.05.61	724.05.62	724.05.63	724.05.64	
75°	724.05.76	724.05.77	724.05.78	724.05.79	
90°	724.05.01	724.05.02	724.05.03	724.05.04	




RADIUS




RETURN GUIDE SHOE

More than 4 tracks on request.


- For steel chains: 10/60/66 M 72 M, 66 M 72 RM



Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	340 mm	525 mm
VERSION C6T						
15°	704.32.16	704.32.17	704.32.18	704.32.19	704.32.20	704.32.21
30°	704.32.31	704.32.32	704.32.33	704.32.34	704.32.35	704.32.36
45°	704.32.46	704.32.47	704.32.48	704.32.49	704.32.50	704.32.51
60°	704.32.61	704.32.62	704.32.63	704.32.64	704.32.65	704.32.66
75°	704.32.76	704.32.77	704.32.78	704.32.79	704.32.80	704.32.81
90°	704.32.01	704.32.02	704.32.03	704.32.04	704.32.05	704.32.06



RADIUS




OPTIONAL INFED ROLLER



More than 6 tracks on request.

- For plastic chains: RHMP 325, RHMDP 325, RHMP 84
- Not suitable for steel chains
- Also available in the following executions:
 - COMBI A VERSION CB6T suitable for: FGM 1050 and FTM 1060 chainbelts
 - COMBI A VERSION CC6T suitable for: FTM 1055 chainbelts

MAGNETFLEX CURVES




Nr. of tracks	1	
Width W	214 mm	
VERSION C65		
15°	724.07.16	
30°	724.07.31	
45°	724.07.46	
60°	724.07.61	
75°	724.07.76	
90°	724.07.01	





More than 1 track on request.

- For steel chains: 10/60/66 M 72 M, 66 M 72 RM




Nr. of tracks	1	
Width W	214 mm	
VERSION C66		
15°	724.11.16	
30°	724.11.31	
45°	724.11.46	
60°	724.11.61	
75°	724.11.76	
90°	724.11.01	




More than 1 track on request.

- For steel chains: 10/60/66 M 72 M, 66 M 72 RM


MAGNETFLEX CURVES



Nr. of tracks	1	2	3	4			
Width W	200 mm	395 mm	590 mm	785 mm			
VERSION C81							
15°	724.31.16	724.31.17	724.31.18	724.31.19			
30°	724.31.31	724.31.32	724.31.33	724.31.34			
45°	724.31.46	724.31.47	724.31.48	724.31.49			
60°	724.31.61	724.31.62	724.31.63	724.31.64			
75°	724.31.76	724.31.77	724.31.78	724.31.79			
90°	724.31.01	724.31.02	724.31.03	724.31.04			




RADIUS




RETURN GUIDE SHOE

More than 4 tracks on request.


- For steel chains: 60/66 M 75 M, 66 M 75 RM
- For plastic chains: HDFM 750 XL/SG



Nr. of tracks	1			
Width W	214 mm			
VERSION C86				
15°	724.36.16			
30°	724.36.31			
45°	724.36.46			
60°	724.36.61			
75°	724.36.76			
90°	724.36.01			



RADIUS






RETURN GUIDE SHOE

More than 1 track on request.

- For steel chains: 60/66 M 75 M, 66 M 75 RM
- For plastic chains: HDFM 750 XL/SG


MAGNETFLEX CURVES





Nr. of tracks	1				
Width W	290 mm				
VERSION C91					
15°	724.42.16				
30°	724.42.31				
45°	724.42.46				
60°	724.42.61				
75°	724.42.76				
90°	724.42.01				

More than 1 track on request.

- For plastic chains: HDFM 1000 XL/SG




Nr. of tracks	1				
Width W	340 mm				
VERSION C96					
15°	724.44.16				
30°	724.44.31				
45°	724.44.46				
60°	724.44.61				
75°	724.44.76				
90°	724.44.01				



More than 1 track on request.

- For plastic chains: HDFM 1200 XL/SG

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	190 mm	280 mm	370 mm	460 mm	550 mm
VERSION LBP2						
15°	704.34.16	704.34.17	704.34.18	704.34.19	704.34.20	704.34.21
30°	704.34.31	704.34.32	704.34.33	704.34.34	704.34.35	704.34.36
45°	704.34.46	704.34.47	704.34.48	704.34.49	704.34.50	704.34.51
60°	704.34.61	704.34.62	704.34.63	704.34.64	704.34.65	704.34.66
75°	704.34.76	704.34.77	704.34.78	704.34.79	704.34.80	704.34.81
90°	704.34.01	704.34.02	704.34.03	704.34.04	704.34.05	704.34.06





More than 6 tracks on request.

- For plastic chains: RHMD 325 LBP




Nr. of tracks	1	
Width W	214 mm	
VERSION LBP861		
15°	724.47.16	
30°	724.47.31	
45°	724.47.46	
60°	724.47.61	
75°	724.47.76	
90°	724.47.01	



More than 1 track on request.

- For plastic chains: HDFM 750 LBP

MAGNETFLEX CURVES





Nr. of tracks	1		
Width W	290 mm		
VERSION LBP91			
15°	724.45.16		
30°	724.45.31		
45°	724.45.46		
60°	724.45.61		
75°	724.45.76		
90°	724.45.01		

A technical drawing of a quarter-circle arc representing the return guide shoe. A dashed line indicates the radius, labeled 'R900'.

RADIUS


A technical drawing showing the return guide shoe assembly. It includes a cross-section of the shoe with dimensions: 15, 20, and 10. The shoe is labeled 'M8'.

RETURN GUIDE SHOE



More than 1 track on request.

- For plastic chains: HDFM 1000 LBP





Nr. of tracks	1		
Width W	340 mm		
VERSION LBP96			
15°	724.46.16		
30°	724.46.31		
45°	724.46.46		
60°	724.46.61		
75°	724.46.76		
90°	724.46.01		

A technical diagram showing a quarter-circle arc of a return guide shoe. A dashed line indicates the radius, labeled 'R960'. Arrows indicate the direction of movement along the arc.

RADIUS

A technical diagram showing a side view of the return guide shoe assembly. It includes dimensions: 15 for the height of the shoe, 20 for the height of the track, and 10 for the width of the track. The label 'MB' is also present.


RETURN GUIDE SHOE





More than 1 track on request.

- For plastic chains: HDFM 1200 LBP

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	111 mm	196 mm	281 mm	366 mm	451 mm	536 mm
VERSION CIP4						
15°	785.45.16	785.45.17	785.45.18	785.45.19	785.45.20	785.45.21
30°	785.45.31	785.45.32	785.45.33	785.45.34	785.45.35	785.45.36
45°	785.45.46	785.45.47	785.45.48	785.45.49	785.45.50	785.45.51
60°	785.45.61	785.45.62	785.45.63	785.45.64	785.45.65	785.45.66
75°	785.45.76	785.45.77	785.45.78	785.45.79	785.45.80	785.45.81
90°	785.45.01	785.45.02	785.45.03	785.45.04	785.45.05	785.45.06





More than 6 tracks on request.

- For steel chains: 10/60/66 M 31 M, 60/66 M 31 XM, 66 M 31 RM, 60/66 M 84 XM




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	440 mm	525 mm
VERSION CB6						
15°	604.14.16	604.14.17	604.14.18	604.14.19	604.14.20	604.14.21
30°	604.14.31	604.14.32	604.14.33	604.14.34	604.14.35	604.14.36
45°	604.14.46	604.14.47	604.14.48	604.14.49	604.14.50	604.14.51
60°	604.14.61	604.14.62	604.14.63	604.14.64	604.14.65	604.14.66
75°	604.14.76	604.14.77	604.14.78	604.14.79	604.14.80	604.14.81
90°	604.14.01	604.14.02	604.14.03	604.14.04	604.14.05	604.14.06





More than 6 tracks on request.

- For plastic chains: FGM 1050, FTM 1060

MAGNETFLEX CURVES




Nr. of tracks	1	2	3	4	5	6
Width W	100 mm	185 mm	270 mm	355 mm	440 mm	525 mm
VERSION CC6						
15°	614.02.16	614.02.17	614.02.18	614.02.19	614.02.20	614.02.21
30°	614.02.31	614.02.32	614.02.33	614.02.34	614.02.35	614.02.36
45°	614.02.46	614.02.47	614.02.48	614.02.49	614.02.50	614.02.51
60°	614.02.61	614.02.62	614.02.63	614.02.64	614.02.65	614.02.66
75°	614.02.76	614.02.77	614.02.78	614.02.79	614.02.80	614.02.81
90°	614.02.01	614.02.02	614.02.03	614.02.04	614.02.05	614.02.06





More than 6 tracks on request.

- For plastic chains: FTM 1055 K330




Nr. of tracks	1	2	3	4
Width W	129 mm	249 mm	369 mm	489 mm
VERSION CC21				
15°	614.08.16	614.08.17	614.08.18	614.08.19
30°	614.08.31	614.08.32	614.08.33	614.08.34
45°	614.08.46	614.08.47	614.08.48	614.08.49
60°	614.08.61	614.08.62	614.08.63	614.08.64
75°	614.08.76	614.08.77	614.08.78	614.08.79
90°	614.08.01	614.08.02	614.08.03	614.08.04




More than 4 tracks on request.

- For plastic chains: FTM 1055 K450

TAB CURVES



Nr. of tracks	1	2	3	Pitch E	Basic width B	Radius R
				mm	mm	mm
VERSION KTU 013						
Width W	100 mm	190 mm	280 mm	For 3.25" wide chains		
15°	787.02.77	787.08.24	787.08.25	90	100	500
30°	787.05.60	787.08.29	787.08.30			
45°	787.03.08	787.04.06	787.08.34			
60°	787.05.71	787.08.38	787.08.39			
75°	787.05.77	787.08.43	787.08.44			
90°	787.00.02	787.00.51	787.00.50			
VERSION KTU 018						
Width W	125 mm	245 mm	365 mm	For 4.50" wide chains		
15°	787.08.49	787.08.50	787.08.51	120	125	610
30°	787.08.55	787.08.56	787.08.57			
45°	787.07.37	787.08.61	787.08.62			
60°	787.08.66	787.08.67	787.08.68			
75°	787.08.72	787.08.73	787.08.74			
90°	787.01.09	787.00.87	787.01.10			
VERSION KTU 030						
Width W	200 mm	395 mm	590 mm	For 7.50" wide chains		
15°	787.08.80	787.08.81	787.08.82	195	200	610
30°	787.08.86	787.08.87	787.08.88			
45°	787.08.92	787.08.93	787.08.94			
60°	787.08.98	787.08.99	787.09.00			
75°	787.09.04	787.09.05	787.09.06			
90°	787.00.07	787.01.11	787.01.12			



For steel chains:


- 8811 TAB
- 881 TAB
- 66 T 72 RM

For plastic chains:

- 880 TAB
- 880 TAB BO
- 879 TAB
- 879 TAB BO
- 880 TAB BOT
- RH
- RHD
- 1050 TAB
- 1055 TAB

The code nr. includes both upper and under part


TAB CURVES



page 38, 45,
50, 51

MATERIAL
page 209

Nr. of tracks	1	2	3	Pitch E	Basic width B	Radius R
				mm	mm	mm
VERSION KTU 215						
Width W	110 mm	210 mm	310 mm	For 3.25" and 3.75" wide chains		
15°	787.12.09	787.12.10	787.12.11	100	110	700
30°	787.12.15	787.12.16	787.12.17			
45°	787.12.21	787.12.22	787.12.23			
60°	787.12.27	787.12.28	787.12.29			
75°	787.12.33	787.12.34	787.12.35			
90°	787.00.05	787.12.39	787.12.40			
VERSION KTU 218						
Width W	130 mm	250 mm	370 mm	For 4.50" wide chains		
15°	787.11.08	787.11.09	787.11.10	120	130	610
30°	787.11.14	787.11.15	787.11.16			
45°	787.04.69	787.11.20	787.11.21			
60°	787.04.07	787.11.25	787.11.26			
75°	787.11.30	787.11.31	787.11.32			
90°	787.02.80	787.07.80	787.11.36			
VERSION KTU 230						
Width W	210 mm	405 mm	600 mm	For 7.50" wide chains		
15°	787.11.40	787.11.41	787.11.42	195	210	610
30°	787.11.46	787.11.47	787.11.48			
45°	787.04.68	787.11.52	787.11.53			
60°	787.11.57	787.11.58	787.11.59			
75°	787.11.63	787.11.64	787.11.65			
90°	787.00.54	787.11.69	787.11.70			
VERSION KTU 240						
Width W	270 mm	530 mm	790 mm	For 10.00" wide chains		
15°	787.11.74	787.11.75	787.11.76	260	270	610
30°	787.11.80	787.11.81	787.11.82			
45°	787.11.86	787.11.87	787.11.88			
60°	787.11.92	787.11.93	787.11.94			
75°	787.11.98	787.11.99	787.12.00			
90°	787.00.06	787.03.26	787.12.04			
VERSION KTU 248						
Width W	320 mm	630 mm	940 mm	For 12.00" wide chains *		
15°	787.12.44	787.12.45	787.12.46	310	320	610
30°	787.12.50	787.12.51	787.12.52			
45°	787.12.56	787.12.57	787.12.58			
60°	787.12.62	787.12.63	787.12.64			
75°	787.12.68	787.12.69	787.12.70			
90°	787.00.21	787.12.74	787.12.75			



For plastic chains:

- 882 TAB
- 883 TAB
- HDF


* not for LBP 1200 chains

The code nr. includes both upper and under part


TAB CURVES



**KTU 300
FOR PLATE TOP CHAINS**



Nr. of tracks	1	2	3	Pitch E	Basic width B	Radius R
				mm	mm	mm
VERSION KTU 313						
Width W	100 mm	190 mm	280 mm	For 3.25" wide chains		
15°	787.09.13	787.09.14	787.09.15	90	100	500
30°	787.09.19	787.09.20	787.09.21			
45°	787.09.25	787.09.26	787.09.27			
60°	787.09.31	787.09.32	787.09.33			
75°	787.09.37	787.09.38	787.09.39			
90°	787.01.13	787.01.14	787.01.15			
VERSION KTU 318						
Width W	125 mm	245 mm	365 mm	For 4.50" wide chains		
15°	787.09.45	787.09.46	787.09.47	120	125	500
30°	787.09.51	787.09.52	787.09.53			
45°	787.07.50	787.09.57	787.09.58			
60°	787.09.62	787.09.63	787.09.64			
75°	787.09.68	787.09.69	787.09.70			
90°	787.01.16	787.01.17	787.01.18			
VERSION KTU 324						
Width W	160 mm	320 mm	480 mm	For 6.00" wide chains		
15°	787.09.77	787.09.78	787.09.79	160	160	610
30°	787.09.83	787.09.84	787.09.85			
45°	787.09.89	787.09.90	787.09.91			
60°	787.09.95	787.09.96	787.09.97			
75°	787.10.01	787.10.02	787.10.03			
90°	787.01.19	787.01.20	787.01.21			
VERSION KTU 330						
Width W	200 mm	395 mm	590 mm	For 7.50" wide chains		
15°	787.10.10	787.10.11	787.10.12	195	200	610
30°	787.10.16	787.10.17	787.10.18			
45°	787.10.22	787.10.23	787.10.24			
60°	787.10.28	787.10.29	787.10.30			
75°	787.10.34	787.10.35	787.10.36			
90°	787.01.22	787.01.23	787.01.24			
VERSION KTU 340						
Width W	260 mm	520 mm	780 mm	For 10.00" wide chains		
15°	787.10.43	787.10.44	787.10.45	260	260	610
30°	787.10.49	787.10.50	787.10.51			
45°	787.04.70	787.10.55	787.10.56			
60°	787.10.60	787.10.61	787.10.62			
75°	787.10.66	787.10.67	787.10.68			
90°	787.01.25	787.01.26	787.01.27			
VERSION KTU 348						
Width W	310 mm	620 mm	930 mm	For 12.00" wide chains		
15°	787.10.75	787.10.76	787.10.77	310	310	610
30°	787.10.81	787.10.82	787.10.83			
45°	787.10.87	787.10.88	787.10.89			
60°	787.10.93	787.10.94	787.10.95			
75°	787.10.99	787.11.00	787.11.01			
90°	787.01.28	787.01.29	787.01.30			




For plate top chains:


- 1873 TAB
- 1874 TAB
- 3873 TAB

The code nr. includes both upper and under part

TAB CURVES



Nr. of tracks	1		Basic width B
			mm
VERSION KTU 508			
Radius	250 mm	500 mm	For 1700 TAB K
15°	787.12.79	787.12.89	100
30°	787.12.80	787.04.35	
45°	787.12.81	787.12.90	
60°	787.12.82	787.12.91	
75°	787.12.83	787.12.92	
90°	787.03.31	787.01.81	
VERSION KTU 515			
Radius	250 mm	500 mm	For 1710 TAB K
15°	787.12.84	787.12.93	110
30°	787.12.85	787.12.94	
45°	787.12.86	787.12.95	
60°	787.12.87	787.12.96	
75°	787.12.88	787.12.97	
90°	787.02.97	787.00.40	
VERSION KTU 540			
Radius	500 mm		For 1713 TAB K
15°	787.12.98		270
30°	787.12.99		
45°	787.13.00		
60°	787.13.01		
75°	787.13.02		
90°	787.03.63		




For plastic Multiflex chains:


- 1700 TAB K
- 1710 TAB K
- 1713 TAB K

The code nr. includes both upper and under part

BEVEL CURVES



Nr. of tracks	1	2	3	Pitch E	Basic width B	Radius R
				mm	mm	mm
VERSION KSU 013						
Width W	100 mm	190 mm	280 mm	For 3.25" wide chains		
15°	787.13.03	787.13.04	787.13.05	90	100	500
30°	787.02.50	787.13.09	787.13.10			
45°	787.02.51	787.13.14	787.13.15			
60°	787.13.19	787.13.20	787.13.21			
75°	787.13.25	787.13.26	787.13.27			
90°	787.00.85	787.00.97	787.00.75			
VERSION KSU 018						
Width W	125 mm	245 mm	365 mm	For 4.50" wide chains		
15°	787.13.33	787.13.34	787.13.35	120	125	610
30°	787.13.39	787.13.40	787.13.41			
45°	787.13.45	787.13.46	787.13.47			
60°	787.13.51	787.13.52	787.13.53			
75°	787.13.57	787.13.58	787.13.59			
90°	787.00.17	787.00.98	787.00.99			
VERSION KSU 030						
Width W	200 mm	395 mm	590 mm	For 7.50" wide chains		
15°	787.13.66	787.13.67	787.13.68	195	200	610
30°	787.13.72	787.13.73	787.13.74			
45°	787.13.78	787.13.79	787.13.80			
60°	787.13.84	787.13.85	787.13.86			
75°	787.13.90	787.13.91	787.13.92			
90°	787.00.94	787.01.00	787.01.01			



For steel chains:


- 8811
- 881
- 66 B 72 RM

For plastic chains:


- 880
- 879

The code nr. includes both upper and under part

BEVEL CURVES



Nr. of tracks	1	2	3	Pitch E	Basic width B	Radius R
				mm	mm	mm
VERSION KSU 218						
Width W	125 mm	245 mm	365 mm	For 4.50" wide chains		
15°	787.13.99	787.14.00	787.14.01	120	125	610
30°	787.14.05	787.14.06	787.14.07			
45°	787.14.11	787.14.12	787.14.13			
60°	787.14.17	787.14.18	787.14.19			
75°	787.14.23	787.14.24	787.14.25			
90°	787.00.95	787.01.02	787.01.03			
VERSION KSU 230						
Width W	200 mm	395 mm	590 mm	For 7.50" wide chains		
15°	787.14.32	787.14.33	787.14.34	195	200	610
30°	787.14.38	787.14.39	787.14.40			
45°	787.14.44	787.14.45	787.14.46			
60°	787.14.50	787.14.51	787.14.52			
75°	787.14.56	787.14.57	787.14.58			
90°	787.00.96	787.01.04	787.01.05			
VERSION KSU 240						
Width W	265 mm	525 mm	785 mm	For 10.00" wide chains		
15°	787.14.65	787.14.66	787.14.67	260	265	610
30°	787.14.71	787.14.72	787.14.73			
45°	787.14.77	787.14.78	787.14.79			
60°	787.14.83	787.14.84	787.14.85			
75°	787.14.89	787.14.90	787.14.91			
90°	787.01.06	787.01.07	787.01.08			







For plastic chains:

- 882



The code nr. includes both upper and under part

STRAIGHT TRACKS



Type	Code number	Basic width B	For chain types	
VERSION STU				
STU 013	787.90.09	100	• 8811 TAB • 881 TAB • 880 TAB/BO/BOT • 879 TAB/BO • RH/RHD • 1050/1055 TAB	
STU 018	787.90.04	130		
VERSION STU 200				
STU 218	787.90.17	130	• 882 TAB • 883 TAB • HDF	
STU 230	787.90.05	210		
STU 240	787.90.06	270		
STU 248	787.90.07	320		
VERSION STU 300				
STU 313	787.45.27	100	• 1873 TAB • 1874 TAB • 3873 TAB	
STU 318	787.47.56	125		
STU 324	787.47.97	160		
STU 330	787.46.85	200		
STU 340	787.48.04	260		
STU 348	787.90.16	310		
VERSION STU 500				
STU 508	787.40.74	100	• 1700 TAB K • 1710 TAB K • 1713 TAB K	
STU 515	787.90.11	110		
STU 540	787.90.20	270		

















Type	Code number	Basic width B	For chain types	
VERSION SSU				
SSU 013	787.90.02	100	• 8811 • 881 • 880 • 879	
SSU 018	787.90.18	130		
RETURN PLATES				
SSU 013 P	787.90.03	100	• 8811 • 881 • 880 • 879	
SSU 018 P	787.90.19	130		














All straight tracks have a standard length of 2 meters; other lengths upon request.

OVERVIEW REXNORD MATTOP M

Pitch inch mm	1/2" 12.8	9/16" 15	3/4" 19.1		1" 25.4		
Series	500/510	1500	8500	5930	1000	1005	1010
CLOSED SURFACE							
	515 SOLID TOP Page 135	1505 SOLID TOP Page 137	8505 SOLID TOP Page 143	5935 SOLID TOP Page 147	1000 FLAT TOP Page 151	1005 FLAT TOP Page 159	1015 SOLID TOP Page 165
OPEN AREA							
	500 FLUSH GRID Page 133	1506 PERFORATED TOP Page 138	8506 PERFORATED TOP Page 144	5936 PERFORATED TOP Page 147	1000 FLUSH GRID Page 152		
OTHER							
		1505 FLAT TOP METRIC Page 139		5935 VACUUM TOP Page 148	1000 SUPERGRIP Page 153	1005 SUPERGRIP Page 160	
							
		1505 SUPERGRIP Page 140			1000 RAISED RIB Page 154, 155	1005 SUPERGRIP SIDE-INDENT Page 161	
							
					1000 LBP Page 156	1005 LBP Page 162	

MODULAR CONVEYOR BELTS

1" 25.4		1 ³¹ / ₃₂ " 50		2" 50.8		2 ¹ / ₄ " 57.2		2 ¹ / ₂ " 63.6		3" 76.2					
7700		6300		2000		2010		6990		9200		2500		3120	
															
7705 SOLID TOP Page 167		6390T SOLID TOP Page 171		2000 FLAT TOP Page 175		2015 SOLID TOP Page 181		6995 SOLID TOP Page 191		9200 FORTREX Page 185		2500 SOLID RIB Page 189		3125 SOLID TOP Page 194	
															
7706 PERFORATED TOP Page 168		6391T PERFORATED TOP Page 172		2000 FLUSH GRID Page 175		2016 PERFORATED TOP Page 181									
															
7708 PERFORATED TOP Page 168		6392T PERFORATED TOP Page 173		2000 RAISED RIB Page 176		2011 TEXTURED TOP Page 182		6999 SAFETY TOP Page 191				3129 SAFETY TOP Page 194			
															
				2000 RAISED RIB HEAVY DUTY Page 176											
															
				2000 SUPER RIB Page 177											
Pitch inch mm	1/2" 12.8		1 1/4" 31.9												
Series	505		1200								7956				
FLEXBELTS															
	505 Page 197		1255 Page 199		1265 Page 200		1275 Page 201		1285 Page 202		7956 Page 204				

PLASTIC MODULAR BELTS

With a large variety of MatTop executions and materials Rexnord has got a conveying solution for virtually any application, especially in combination with the huge TableTop chain programme. The MCC brand has set a standard for modular conveyor belts in beverage industry and now the cleanable designs and specific accessories make several Rexnord MatTop series very suitable for food industry as well. Also in many other industries, such as container making, pharmaceutical and automotive, lines are equipped with Rexnord modular belts.

MatTop modular belts offer a reliable drive concept, using Rexnord's great experience in chain drive technology. The design of both belt and sprocket make a perfect combination meeting high standards for tooth and belt engagement, belt release from the sprocket and allowable elongation. Rexnord and MCC modular belts are also known for their clever pin retention systems, which make them very easy to install and maintain.

- MatTop modular belts

The range of MatTop modular belts varies from 1/2-inch small pitch sideflexing executions to 2 1/2-inch pitch straight running heavy duty solutions. The different series are offered in many variations to suit any application:

• Solid Top/Flat Top

A fully closed surface is used if products require maximum support, due to their vulnerability or instability, and if small particles, such as broken glass, bolts and nuts, bones or the product itself, could get stuck in the surface of the belt, possibly damaging or jamming the product or the belt.

• Perforated Top/Flush Grid

An open area surface is used to allow water- or airflow through the belt and to remove debris, making sure the contact surface between the belt and the conveyed product stays clean. Pollution is washed out in a regular cleaning program. The open area varies per belt type.

• Raised Top/Raised Rib

If (unstable) products need to be conveyed onto or from a belt or chain, Raised Top belts and fingerplates are suitable. The fingers of the transfer plate reach into and below the surface of the ribs of the belt. Fingerplates are available with longer and shorter fingers; short fingers are normally used in case of a risk of broken glass.

• Vacuum Top

Vacuum conveyors are mainly used for can making or empty can handling in beverage plants. Small holes in a Solid Top belt enable to handle the empty cans by means of a vacuum underneath the belt.

• Rubber Top/SuperGrip

On inclined and declined conveyors packs or crates can be handled smoothly using surfaces with rubber, moulded on top of a specially prepared module using either over-moulding or 2-component technology, ensuring 100% secure bonding. Rubber Top modular belts can be used up to an angle of 20 degrees, depending on the pack style and material.

• Low Backline Pressure (LBP)

Handling accumulated products (cardboard cases, shrink-wrapped packs, flat based crates, tires, etc.) LBP belts are the best choice. LBP1005 modular belts are recommended for shrink-wrapped packages without solid (cardboard) base and small packages, while LBP7703 is the best choice for (cardboard) cases, shrink-wrapped packs with a cardboard bottom and larger products. Both executions guarantee optimum product protection and low noise operation.

• Sideflexing


This belt range offers a solution for almost any curved application.



- Metric and imperial widths

Most belt series are available in either metric or imperial widths. Metric width has developed as the standard of the (European) beverage industry, following the standard 85 mm pitch between different strands of slatband chains.

This enables a high level of standardization between TableTop and MatTop conveyor design. Imperial widths, mainly used in the North American market, are the standard in many applications outside (European) beverage industry.





- Positrack guiding system

In several MatTop series Rexnord offers Positrack or Tab guiding. This system consists of two lugs underneath the belt, offering an easy way to guide it in the conveyor. Positrack has advantages if lateral forces apply, as on side transfers of beverage containers and products entering from the side otherwise. The system retains the belt on the conveyor frame without the need for additional wearstrips at the sides. The lugs are usually situated on one side only (double Positrack) allowing for belt expansion without interfering with the accurate guiding of the belt.

- Dynamic Transfer System (DTS/FreeFlow)

The DTS option makes it possible to construct self-clearing 90-degree transfers on which no products are left behind, avoiding the use of dead plates. A narrow DTS or FreeFlow belt is often used next to the main conveyor belt. Due to the constant moving belt underneath the product, pressure between the products, and therefore noise and product damage, is minimized in comparison with dead plate transfers. This system is available on 1500-, 8500-, 1000-, 1005- and 7700-series.



- Flights and sideguards

In several series flights and sideguards can be selected. Due to the great variety in positioning of these accessories these belts don't have fixed codes. On the product page a table is added explaining the possibilities; examples are given how to make a description for the desired product configuration.

PLASTIC MODULAR BELTS

PROGRAMME

STRAIGHT RUNNING BELT SERIES		APPLICATION														
		Small Products (Packs)	Glass handling	PET handling	Can handling	Pack handling	Pack accumulation	Pack incline conveyors	Pasteurizer, warmer, cooler	Accumulation tables	Crates, bread tins	Direct food contact	Blancher, cooker, cooler	Loose food incline conveyors	Cutting	Automotive
type	pitch															
500	1/2"															
510	1/2"															
1500	15 mm															
8500	3/4"															
5930	3/4"															
1000	1"															
1005	1"															
1010	1"															
7700	1"															
6300T	50 mm															
2000	2"															
2010	2"															
6990	2 1/4"															
9200	2 1/4"															
2500	2 1/2"															
3120	3"															

SIDEFLEXING BELT TYPES		APPLICATION							
		Small packages	Standard packages	180-Degree conveyors	High-speed conveyors	Small radius	Crates, bread tins	Incline conveyors	Direct food contact
type	pitch								
505	1/2"								
1255	1 1/4"								
1265	1 1/4"								
1275	1 1/4"								
1285	1 1/4"								
7956	1 1/4"								

Best choice

Optional

MATERIAL	APPLICATION											
	Mass handling	Inliner standard	Inliner / high-speed / PET	Abrasive wet	Abrasive dry	Static electricity sensitive (dry)	Chemicals, strong cleaning agents	Direct food contact (FDA approved)	Cutting	High temperatures	Freezing	General conveying food industry
LF												
XLG												
HP												
PS												
WX												
DKA												
AS												
XP/HT												
WSA/WSM*												
WHA/WHT*												
WLA/WLT*												
BSM/BYSM												

* For different colours of similar materials (e.g. BSA, BHA, etc.) the same recommendations apply. Not all materials are available in each belt series, but for specific applications the best materials are chosen.

*) for individual application advice consult your local technical support representative

500-SERIES MODULAR BELTS

The 500-series 1/2-inch pitch belt offers the smallest pitch available in the market. This pitch makes this belt very suitable for handling small or unstable products requiring small inline transfers, such as infeed conveyors of packaging equipment and can manufacturing. As a standard the belts are supplied in low friction acetal.

FEATURES

- Perfect product handling due to very small pitch ensuring smooth operation and low friction acetal.
- The small 12.7 mm pitch reduces chordal action and permits the use of small or no dead plates at inline transfers.
- Rounded outside edges for better side transfers and improved product handling.
- Pin retention system with clips allows easy pin access for installation and maintenance.

PROGRAMME	
500 Flush Grid	16% Open area; this guarantees optimum water- and airflow and allows pollution to fall through and maintain a clean contact surface between products and the belt; suitable for amongst others can making and can processing
Positrack	Small lugs on one or both sides of the belt, to ensure a superior guiding of the belt even on long conveyors and at side transfers. Positrack is also recommended on 85 mm wide single track belt executions




SMALL BOTTLE CONVEYOR WITH 500 BELT




CAN PROCESSING ON 500 BELT

500-SERIES





**FLUSH GRID
500**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	FG 500 XLG	857.40.xx	4 to 80	4 to 65	13000	6.00	8
POSITRACK LEFT	FGP 500 XLG	874.05.xx					
POSITRACK RIGHT	FGP 500 XLG	874.06.xx					
POSITRACK TWO SIDES	FGP 500 XLG	874.04.xx					

* In code numbers xx corresponds with the belt width (A), starting with 10 for 85 mm, 11 for 170 mm and so on in steps of 85 mm. See page 206 for all code numbers. Cut to width options upon request.




FLUSH GRID 500 BELT WITH POSITRACK

Sprocket Type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A	
			mm/inch	mm	mm	mm	


MATERIAL

page 209

SPLIT SPROCKETS						
ROUND BORES						
SSW 500 28-30	899.14.17	28	30 mm	113.4	113.4	39
SSW 500 28-40	899.14.11	28	40 mm			
SSW 500 28-1½	899.14.31	28	1.5"			
SQUARE BORES						
SSW 500 28-40x40	899.14.21	28	40 mm	113.4	113.4	39
SSW 500 28-1½ x1½	899.14.41	28	1.5"			



CLASSIC SPROCKETS						
ROUND BORES						
CS 500 16-25	895.26.16	16	25 mm	65.2	65.2	20
CS 500 16-30	895.26.17	16	30 mm			
CS 500 28-25	895.24.16	28	25 mm	113.4	113.4	
CS 500 28-30	895.24.17	28	30 mm			
CS 500 28-40	895.24.11	28	40 mm			
CS 500 28-1½	895.24.41	28	1.5"			
CS 500 38-40	895.20.11	38	40 mm	153.8	153.1	
SQUARE BORES						
CS 500 28-40x40	895.24.21	28	40 mm	113.4	113.4	20
CS 500 28-60x60	895.24.28	28	60 mm			





510-SERIES MODULAR BELTS

The 510-series ½-inch pitch belt is meant for light duty applications, where cleanability and hygiene have got the highest importance. The extreme small ½" pitch enables very small transfers, high speeds and low noise. It can handle meat, poultry, seafood, fruits and salads after being cut or processed otherwise. As a standard the belts are supplied in food grade materials with antibacterial protection, especially for direct food contact and high risk areas.

FEATURES

- When turning over a small roller and/or nose bar (suitable for up to 20mm) the hinges open, exposing a large pin surface, offering excellent cleaning possibilities. The hinge design is extremely open and accessible, so a large surface of the pin and the inside of the hinge can be cleaned directly. The bottom of the module is rounded, improving drainage and reducing drying time of the belt after cleaning.
- The belt is supplied mould-to-width up to 12 inch, avoiding adjacent surfaces between the modules. The hinges are ½ inch wide, reducing the number of adjacent surfaces in-between.
- Smooth running at high speeds (up to 2 m/s) and low noise operation. Bi-directional; virtual no chordal action due to the specific hinge design and therefore smooth handling of most vulnerable.
- Double teeth rows fully closed machine sprockets, ideal for cleaning. Sprocket well positioned and retained sideways. Sprockets drive on the pin (roller chain principle).
- Small transfers, total centre to centre distance 43 mm only.
- Moulded pin with T-shaped pin retention. Minimum of pin coverage by eyes (front and bottom) and easy pin retention without loose parts. Open and accessible the pin is completely "free" from the module.
- As a standard antibacterial protection incorporated for direct food contact.

PROGRAMME	
515 Solid Top	Closed Surface; it offers the best support to vulnerable products and prevents loss of small products




515 BELT ON INFEED OF AUTOMATIC PORK TRIMMER



MEAT PROCESSING ON 515 BELT

510-SERIES





Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYESTER PINS							
STANDARD	WLA 515	846.42.02	-40 to +35	-40 to +35	3000	4.40	15
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYESTER PINS							
STANDARD	BLA 515	846.42.52	-40 to +35	-40 to +35	3000	4.40	15
ANTIBACTERIAL WHA-POLYPROPYLENE WITH POLYESTER PINS							
STANDARD	WHA 515	849.42.02	4 to 80	4 to 65	5000	4.20	15
ANTIBACTERIAL BHA-POLYPROPYLENE WITH POLYESTER PINS							
STANDARD	BHA 515	849.42.52	4 to 80	4 to 65	5000	4.20	15
ANTIBACTERIAL WSA-ACETAL WITH POLYESTER PINS							
STANDARD	WSA 515	844.42.02	-40 to +80	-40 to +65	7500	6.10	15
ANTIBACTERIAL BSA-ACETAL WITH POLYESTER PINS							
STANDARD	BSA 515	844.42.52	-40 to +80	-40 to +65	7500	6.10	15

* In code numbers xx corresponds with the belt width (A), for White belts (WLA, WHA, WSA) starting with 02 for 4", 03 for 5", for Blue belts (BLA, BHA, BSA) starting with 52 for 4", 53 for 5", and so on in steps of 1", up to 44"; see also page 206.

Sprocket type	Code nr.	Nr. of teeth	Bore	Pitch diameter	Outside diameter	Hub width	
			B	E	F	A	
			mm	mm	mm	mm	

MATERIAL

page 209

CLASSIC SPROCKETS							
ROUND BORES							
KU 510 T10 R20	897.01.01	10	20	41.1	43.6	16.7	
KU 510 T14 R25	897.00.00	14	25	57.1	61.1		
KU 510 T24 R25	897.00.01	24	25	97.3	101.3		
KU 510 T38 R 40	897.00.10	38	40	153.8	157.8		
SQUARE BORES							
KU 510 T24 S40	774.01.80	24	40	97.3	101.3	16.7	
KU 510 T32 S40	897.01.73	32	40	129.6	133.6		
KU 510 T38 S40	897.00.11	38	40	153.8	157.8		





1500-SERIES MODULAR BELTS

The 1500-series 15 mm pitch belt helps to eliminate container tipping and jam-ups at conveyor transfer points. These belts are designed to enable smooth inline nose-over and 90° transfers. 1500-series is available in open, closed and rubber top executions, of which last two in both imperial and metric widths. As a standard the belts are supplied in high-performance acetal and high-temperature resistant polypropylene for beverage applications and in materials with antibacterial protection, especially for direct food contact and high-risk food processing environments.

FEATURES

- The 15 mm pitch in combination with the curved underside of the belt reduces chordal action and permits the use of very short transfer plates or no transfer plates at all.
- The small pitch ensures perfect product handling, even for the most vulnerable products.
- Practical plug pin retention system allows easy installation and maintenance; metric executions have orange plugs, imperial versions have a yellow pin retention.
- Belt and sprocket design ensure optimum engagement and a reliable, bi-directional drive.

PROGRAMME	
1505 Flat Top	Closed surface; suitable for (instable) glass and PET containers and otherwise vulnerable products
1506 Flush Grid	26% Open area for optimum water- and airflow; suitable for amongst others can handling
1505 SuperGrip	Rubber Top for inclined and declined conveyors with packs and for metering applications;
DTS	Positrack and 44 mm side-indent possible. Standard angles up to 20° Single module Dynamic Transfer System for left- or right-hand self-clearing 90° transfers to avoid
Positrack	dead plates; as a standard equipped with Positrack guiding Lugs for accurate guiding of the belt in the conveyor (metric execution and DTS only)
Belt accessories	Flights and sideguards for special applications in food industry (imperial executions only)



WINE BOTTLE CONVEYOR WITH 1505 BELT




HYGIENIC POULTRY PROCESSING ON 1505 BELT

1500-SERIES



**FLAT TOP
1505
IMPERIAL SIZES**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HP-ACETAL WITH PBT PINS							
STANDARD	HP 1505	I1505HPKxx	-40 to +80	-40 to +65	13200	6.24	16
DTS LEFT	HP 1505 DTS SX	81413971					
DTS RIGHT	HP 1505 DTS DX	81414111					
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	HT 1505	I1505HTKxx	5 to 105	5 to 105	7300	4.52	16
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 1505	I1505WLAKxx	-70 to +35	-70 to +35	2800	4.80	16
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	BLA 1505	I1505BLAKxx	-70 to +35	-70 to +35	2800	4.80	16
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	WHA 1505	I1505WHAKxx	4 to 80	4 to 65	7300	4.50	16
ANTIBACTERIAL BHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	BHA 1505	I1505BHAKxx	4 to 80	4 to 65	7300	4.50	16
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS							
STANDARD	WSA 1505	I1505WSAKxx	-40 to +80	-40 to +65	13200	6.20	16
ANTIBACTERIAL BSA-ACETAL WITH PBT PINS							
STANDARD	BSA 1505	I1505BSAKxx	-40 to +80	-40 to +65	13200	6.20	16

* In code numbers xx corresponds with the belt width (A). Standard nominal widths of these belts begin at 3" with 3" increments, or optionally 3/4" up to 96". NOTE: 3 3/4" is impossible. Example: I1505HPK06.75 is a 6.75" wide belt. See also page 206.

If you need flights or sideguards, describe the belt by choosing from the required options listed in the 2nd column of the table:


Material	WLA or BLA or WHA or BHA or WSA or BSA	
Belt type	1505	
Width (A)	K-.. (in inches)	
Flights	F1 or F2 or H..	Standard height of 1" (25.4 mm), 2" (50.8 mm) or special height in mm
Pitch between flights	T..P	Flights on every .. th row
Flight side-indent	N.. (in inches)	Minimal 1 7/8" (48 mm) with 3/4" (19 mm) increments
Sideguards	SG2	Standard height of 2"

Example: BLA 1505 K-12 H50 T4P N1 7/8 SG2 is a 1505 Flat Top belt, made of blue polyethylene with Microban, width 12", special 50 mm high flights on every 4th row at 1 7/8" from the sides and 2" high sideguards.




DYNAMIC TRANSFER SYSTEM (DTS) 1500-SERIES IMPERIAL

1500-SERIES



**FLUSH GRID
1506
IMPERIAL SIZES**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HP-ACETAL WITH PBT PINS							
STANDARD	HP 1506	I1506HPKxx	-40 to +80	-40 to +65	13200	6.24	16
DTS LEFT	HP 1505 DTS SX	81413971					
DTS RIGHT	HP 1505 DTS DX	81414111					
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	HT 1506	I1506HTKxx	5 to 105	5 to 105	7300	4.52	16
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 1506	I1506WLAKxx	-70 to +35	-70 to +35	2800	4.80	16
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	BLA 1506	I1506BLAKxx	-70 to +35	-70 to +35	2800	4.80	16
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	WHA 1506	I1506WHAKxx	4 to 80	4 to 65	7300	4.50	16
ANTIBACTERIAL BHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	BHA 1506	I1506BHAKxx	4 to 80	4 to 65	7300	4.50	16
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS							
STANDARD	WSA 1506	I1506WSAKxx	-40 to +80	-40 to +65	13200	6.20	16
ANTIBACTERIAL BSA-ACETAL WITH PBT PINS							
STANDARD	BSA 1506	I1506BSAKxx	-40 to +80	-40 to +65	13200	6.20	16

* In code numbers xx corresponds with the belt width (A). Standard nominal widths of these belts begin at 3" (76.2 mm), with 3" increments, or optionally ¾" up to 120". NOTE: 3¾" is impossible. Example: I1506HPK06.75 is a 6.75" wide belt. See also page 206.


If you need flights or sideguards, describe the belt by choosing from the required options listed in the 2nd column of the table:

Material	WLA or BLA or WHA or BHA or WSA or BSA	
Belt type	1506	
Width (A)	K-.. (in inches)	
Flights	F1 or F2 or H..	Standard height of 1" (25.4 mm), 2" (50.8 mm) or special height in mm
Pitch between flights	T..P	Flights on every .. th row
Flight side-indent	N.. (in inches)	Minimal 1⅞" (48 mm) with ¾" (19 mm) increments
Sideguards	SG2	Standard height of 2"


Example: WSA 1506 K-15¾ F1 T8P N1⅞ SG2 is a 1506 Flush Grid belt, made of white acetal with Microban, width 15¾", 1" high flights on every 8th row at 1⅞" from the sides and 2" high sideguards.




FLIGHT FOR 1500-SERIES IMPERIAL




SIDEGUARDS FOR 1500-SERIES IMPERIAL



1500-SERIES



**FLAT TOP
1505
METRIC SIZES**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH PBT PINS							
STANDARD	FT 1505 XLG	873.44.xx	-40 to +80	-40 to +65	13200	6.35	25
DOUBLE POSITRACK	FTDP 1505 XLG	873.54.xx					
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	FT 1505 XP	873.46.xx	4 to 104	4 to 104	7300	4.49	25
DOUBLE POSITRACK	FTDP 1505 XP	873.56.xx					
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS							
STANDARD	WSA 1505 FT	873.48.xx	-40 to +80	-40 to +65	13200	6.35	25
DOUBLE POSITRACK	WSA 1505 FTDP	873.57.xx					
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	WHA 1505 FT	873.49.xx	4 to 104	4 to 104	7300	4.49	25
DOUBLE POSITRACK	WHA 1505 FTDP	873.58.xx					


* In code numbers xx corresponds with the belt width (A), starting with 11 for 170 mm, 12 for 255 mm and so on in steps of 85 mm, up to 6120 mm; wider belts upon request. See page 206 for all code numbers. Cut to width options are possible.




POSITRACK 1505 METRIC



1500-SERIES




**FLAT TOP
1505
SUPERGRIP**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet			
XLG-ACETAL WITH PBT PINS							
STANDARD	SG 1505 XLG	878.00.xx	-40 to +80	-40 to +65	13200	6.35	25
DOUBLE POSITRACK	SGDP 1505 XLG	878.12.xx					
SIDE-INDENT	SGS 1505 XLG	878.01.xx					
SIDE-INDENT DOUBLE POSITRACK	SGSDP 1505 XLG	878.13.xx					
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	SG 1505 XP	878.02.xx	4 to 80	4 to 65	7300	4.49	25
DOUBLE POSITRACK	SGDP 1505 XP	878.14.xx					
SIDE-INDENT	SGS 1505 XP	878.03.xx					
SIDE-INDENT DOUBLE POSITRACK	SGSDP 1505 XP	878.15.xx					
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS							
STANDARD	SG 1505 WSA	878.06.xx	-40 to +80	-40 to +65	13200	6.35	25
DOUBLE POSITRACK	SGDP 1505 WSA	878.16.xx					
SIDE-INDENT	SGS 1505 WSA	878.07.xx					
SIDE-INDENT DOUBLE POSITRACK	SGSDP 1505 WSA	878.17.xx					
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS							
STANDARD	SG 1505 WHA	878.04.xx	4 to 80	4 to 65	7300	4.49	25
DOUBLE POSITRACK	SGDP 1505 WHA	878.18.xx					
SIDE-INDENT	SGS 1505 WHA	878.05.xx					
SIDE-INDENT DOUBLE POSITRACK	SGSDP 1505 WHA	878.19.xx					

* In code numbers xx corresponds with the belt width (A), starting with 11 for 170 mm, 12 for 255 mm and so on in steps of 85 mm, up to 6120 mm. SuperGrip Side-indent versions start with 255 mm width. See page 206 for all code numbers. Cut to width options are possible. Side-indent in SuperGrip versions is 44 mm.

Rubber top is a black elastomere, with a hardness of 40 (XP) or 50 (XLG,WSA) or 60 (WHA) shore A.



1505 SUPERGRIP SIDE-INDENT




1505 SUPERGRIP SIDE-INDENT WITH POSITRACK

1500-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209
---------------	----------	--------------	-----------------	---------------------------	-----------------------------	----------------------	----------------------

SPLIT SPROCKETS 1505 INJECTION MOULDED

ROUND BORES						
NS 1500 T24 R25	614-213-7	24	25	114.9	115.5	40.0
NS 1500 T24 R30	614-213-1	24	30			
NS 1500 T24 R35	614-213-6	24	35			
NS 1500 T24 R40	614-213-4	24	40			
NS 1500 T32 R25	614-212-8	32	25	153.4	154.8	
NS 1500 T32 R30	614-212-1	32	30			
NS 1500 T32 R35	614-212-6	32	35			
NS 1500 T32 R40	614-212-2	32	40			
SQUARE BORES						
NS 1500 T24 S40	614-142-2	24	40	114.9	115.5	40.0
NS 1500 T24 S60	614-142-1	24	60			
NS 1500 T32 S40	614-211-1	32	40	153.4	154.8	
NS 1500 T32 S60	614-211-2	32	60			




Not suitable in combination with FTDP, SGDP, and SGSDP due to the Positrack lugs

Not suitable in combination with FTDP, SGDP, and SGSDP due to the Positrack lugs

SPLIT SPROCKETS 1505 MACHINED

ROUND BORES						
KUS 1500 T24 R25	614-284-5	24	25	114.9	115.5	50.8
KUS 1500 T24 R30	614-284-1	24	30			
KUS 1500 T24 R35	614-284-6	24	35			
KUS 1500 T24 R40	614-284-2	24	40			







CLASSIC SPROCKETS 1505 MACHINED

ROUND BORES						
KU 1500 T12 R30	114-3625-22	12	30	58.1	58.2	24.1
KU 1500 T16 R30	114-3756-28	16	30	77.1	77.7	31.8
KU 1500 T24 R30	114-2727-7	24	30	114.9	115.5	40.0
KU 1500 T24 R40	114-2727-8	24	40			
KU 1500 T32 R30	114-2812-6	32	30	153.4	154.8	40.0
KU 1500 T32 R40	114-2812-12	32	40			
SQUARE BORES						
KU 1500 T24 S25	114-4518-4	24	25	114.9	115.5	40.0
KU 1500 T32 S40	114-2813-10	32	40	153.4	154.8	40.0





Part number	Width	Hole spacing	Plate size	Inserts	
NOSE-OVER BARS					
STANDARD VERSION					
905-655711	6"	3"	-	-	
LOW VERSION					
905-656301	170 mm	85 mm	8 mm	M6	
905-656291	255 mm	85 mm	8 mm	M6	
905-655721	6"	3"	8 mm	M6	
905-655731	6"	3"	1/4"	1/4-20	
Other versions can be supplied upon request.					

8500-SERIES MODULAR BELTS

The 8500-series $\frac{3}{4}$ -inch pitch belt has several strong design features, making it suitable for amongst others beverage, packaging and food industry. The small belt pitch ensures a smooth operation. 8500-Series is available in a closed and an open execution. Mold-to-width executions are available with Tab guides for single line applications. As a standard the belts are supplied in high-performance acetal and in food grade polypropylene.


FEATURES

- Perfect product handling due to the small pitch and superior low friction HP material. The stiffness of the modules results in an optimum belt flatness.
- The small 19.05 mm pitch reduces the chordal action and permits the use of short transfer plates.
- Rounded outside edges for better side transfers and improved product handling.
- Twist-lock™ pin retention by means of a hinged plug prevents plug loss and allows easy pin access for installation and maintenance.
- 8500-Series belt is companioned by FTM 1060, FGM 1050 or FT 1050 chainbelts, to make a perfect match between straight running and sideflexing conveyors.

PROGRAMME	
8505 Solid Top	Closed surface and high strength make it suitable for both glass and PET containers
8506 Perforated Top	22% Open area for optimum water- and airflow; suitable for amongst others can making and can processing environment
DTS	Single module Dynamic Transfer System for left- or right-hand self-clearing transfers to avoid dead plates at 90° transfers; as a standard equipped with Positrack guiding
Belt accessories	Flights, sideguards and hold-down tabs for special applications in food industry




CONVEYOR WITH 8506 BELT AND FLIGHTS READY FOR TRANSPORT




BOLT ELEVATING ON 8505 BELT

8500-SERIES



**SOLID TOP
8505**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HP-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	HP 8505	I8505HPKxx	-40 to +80	-40 to +65	29000	8.89	25
DTS LEFT/POSITRACK	HP 8505 K450 DTS-SX	81415811					
DTS RIGHT/POSITRACK	HP 8505 K450 DTS-DX	81415791					
WHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHT 8505	I8505HTKxx	5 to 105	5 to 105	16000	5.96	25

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 6", with 6" increments up to 120"; special widths begin at 2 1/3" with 1/3" increments. See also page 206.


If you require flights, sideguards or tab guides, please describe the belt by choosing from the options listed in the **2nd** column of the table:

Material	HP or WHT	
Belt type	8505	
Width (A)	K.. (in inches)	Belts with flights have a minimal width of 6"
Flights	F3 or F2 or F1 or H..	Standard height of 3", 2", 1" or special height in mm
Pitch between flights	T..P	Flights on every .. th row; with sideguards it must correspond to an even number of rows
Flight side-indent	N.. (in inches)	Minimal 1 1/3" with 1/3" increments; in case of sideguards indents 1 1/2" or 2 1/4" only
Sideguards	SG2 or SG1	Standard height of 2" or 1"
Tab guides	TAB1 or TAB2	TAB1 is only one row; TAB2 is two rows
Distance between Tabs	D..	Minimal 3" with increments of 2/3"
Pitch between Tabs	D..P	Must correspond to an even number of rows


Example: HP 8505 K16 1/3 F3 T4P N2 1/3 TAB2 D3 D4P is a 8505 Solid Top belt, made of dark grey acetal, width 16 1/3", 3" high flights on every 4th row at 2 1/3" from the sides, no sideguards and 2 rows of tabs with a distance in-between of 3" on every 4th row.



FLIGHT 8500-SERIES FOR INCLINED APPLICATIONS




SIDEGUARDS 8500-SERIES



8500-SERIES



**PERFORATED TOP
8506**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HP-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	HP 8506	I8506HPKxx	-40 to +80	-40 to +65	29000	8.89	25
DTS LEFT/POSITRACK	HP 8505 K450 DTS-SX	81415811					
DTS RIGHT/POSITRACK	HP 8505 K450 DTS-DX	81415791					
WHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHT 8506	I8506WHTKxx	5 to 105	5 to 105	16000	5.96	25

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 6", with 6" increments up to 120"; special widths begin at 2 1/3" with 1/3" increments. See also page 206.


If you require flights, sideguards or tab guides, please describe the belt by choosing from the options listed in the 2nd column of the table:

Material	HP or WHT	
Belt type	8506	
Width (A)	K.. (in inches)	Belts with flights have a minimal width of 6"
Flights	F3 or F2 or F1 or H..	Standard height of 3", 2", 1" or special height in mm
Pitch between flights	T..P	Flights on every .. th row; with sideguards it must correspond to an even number of rows
Flight side-indent	N.. (in inches)	Minimal 1 1/3" with 1/3" increments; in case of sideguards indents 1 1/2" or 2 1/4" only
Sideguards	SG2 or SG1	Standard height of 2" or 1"
Tab guides	TAB1 or TAB2	TAB1 is only one row; TAB2 is two rows
Distance between Tabs	D..	Minimal 3" with increments of 2/3"
Pitch between Tabs	D..P	Must correspond to an even number of rows


Example: WHT 8506 K7.50 SG2 N1 1/2 is a 8506 Perforated Top belt, made of white Polypropylene, width 7.5", 2" high sideguards at 1 1/2" from the sides. No flights, tab guides and DTS.










TAB GUIDE 8500-SERIES



DYNAMIC TRANSFER SYSTEM 8500-SERIES



8500-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A				
							MATERIAL			
							page 209			
SPLIT SPROCKETS										
ROUND BORES								 		
NS 8500 T17 R25	614-176-25	17	25	104.7	105.4	39				
NS 8500 T17 R30	614-176-30	17	30							
NS 8500 T17 R35	614-176-35	17	35							
NS 8500 T21 R25	614-239-1	21	25	129.0	130.0					
NS 8500 T21 R30	614-239-2	21	30							
NS 8500 T21 R35	614-239-3	21	35							
NS 8500 T21 R40	614-239-4	21	40	147.3	148.3					
NS 8500 T24 R25	614-188-25	24	25							
NS 8500 T24 R30	614-188-30	24	30							
NS 8500 T24 R35	614-188-35	24	35	153.4	154.7					
NS 8500 T25 R25	614-192-25	25	25							
NS 8500 T25 R30	614-192-30	25	30							
NS 8500 T25 R35	614-192-35	25	35							
SQUARE BORES								 		
NS 8500 T17 S25	614-177-1	17	25	104.7	105.4	39				
NS 8500 T17 S30	614-177-2	17	30							
NS 8500 T17 S35	614-177-3	17	35							
NS 8500 T21 S25	614-240-1	21	25	129.0	130.0					
NS 8500 T21 S40	614-240-2	21	40							
NS 8500 T21 S60	614-240-3	21	60							
NS 8500 T24 S25	614-189-1	24	25	147.3	148.3					
NS 8500 T24 S30	614-189-5	24	30							
NS 8500 T24 S35	614-189-4	24	35							
NS 8500 T25 S25	614-193-1	25	25	153.4	154.7					
NS 8500 T25 S30	614-193-6	25	30							
NS 8500 T25 S35	614-193-5	25	35							
CLASSIC SPROCKETS										
ROUND BORES								 		
KU 8500 T24 R30	114-3046-8	24	30	147.3	148.3	35				
KU 8500 T25 R50	114-3266-2	25	50	153.4	154.7					
SQUARE BORES										
KU 8500 T17 S40	114-3215-2	17	40	104.7	105.4	35				
KU 8500 T25 S40	114-3216-2	25	40	153.4	154.7					

5930-SERIES MODULAR BELTS

The 5930-series $\frac{3}{4}$ -inch pitch belt is intended for light to medium loads in can manufacturing, can handling and food industry applications. The belts ensure a smooth operation. 5930-Series is available in a closed and an open execution. As a standard the belts are supplied in polypropylene and acetal.


FEATURES

- The 19.05 mm pitch reduces chordal action.
- The small pitch permits the use of short transfer plates.
- Smooth edges and closed hinges ensure perfect product handling.
- Pin retention by means of one plugged end module and one blind end module.
- 5930-Series belts with flights, sideguards and hold-down tabs have been replaced by 8500-series; this series is identical in pitch, thickness and standard widths.

PROGRAMME	
5935 Solid Top	Closed surface; suitable for PET containers and otherwise lightweight products
5936 Perforated Top	16% Open area for optimum water- and airflow; suitable for amongst others can making and can processing
5935 Vacuum Top	Solid Top execution with small holes for amongst others vacuum conveyors in can manufacturing lines



CAN WASHER DISCHARGE WITH 5936 BELT




CAN PROCESSING ON 5935 VACUUM BELT

5930-SERIES




**SOLID TOP
5935**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet	N/m (21°C)	kg/m²	mm
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	HT 5935	I5935HTKxx	5 to 105	5 to 105	7000	4.92	25
LF-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	LF 5935	I5935LFKxx	-40 to +80	-40 to +65	13000	6.35	25

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 9" with 3" increments up to 120"; special widths begin at 3" with 3/4" increments. See also page 206.




**PERFORATED TOP
5936**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	HT 5936	I5936HTKxx	5 to 105	5 to 105	7000	4.49	25
LF-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	LF 5936	I5936LFKxx	-40 to +80	-40 to +65	13000	5.90	25

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 9" with 3" increments up to 120"; special widths begin at 3" with 3/4" increments. See also page 206.

5930-SERIES



VACUUM TOP
5935





page 149


MATERIAL

page 208


Assembly	Belt type	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
		dry	wet			
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS						
STANDARD	HT 5935 VAC	5 to 105	5 to 105	7000	4.92	25
LF-ACETAL WITH POLYPROPYLENE PINS						
STANDARD	LF 5935 VAC	-40 to +80	-40 to +65	13000	6.35	25

As the patterns of the holes will be made to order, these belts will be supplied upon request.


Version E7 (holes in line) Holes diameter: 3,2 - 4 - 5,1 mm.











Version E78 (holes in "diamond" pattern) Holes diameter: 3,2 - 4 - 5,1 mm.



Version E8 (holes in line) Holes diameter: 3,2 - 4 - 5,1 mm.



5930-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore	Pitch diameter	Outside diameter	Hub width	
			B mm	E mm	F mm	A mm	
MATERIAL page 209							
CLASSIC SPROCKETS INJECTION MOULDED							
ROUND BORES							  
N 5936 T10 R25	114-811-8	10	25	62.2	63.5	25	
N 5936 T24 R25	114-699-8	24	25	147.3	149.2		
N 5936 T24 R30	114-699-9	24	30				
N 5936 T24 R35	114-699-10	24	35				
N 5936 T24 R40	114-700-11	24	40				
N 5936 T24 R50	114-700-13	24	50				
SQUARE BORES							  
N 5936 T24 S40	114-696-11	24	40	147.3	149.2	25	
N 5936 T24 S50	114-697-13	24	50				
N 5936 T24 S65	114-698-16	24	65				
N 5936 T25 S40	114-692-11	25	40	153.4	156.2	25	
N 5936 T25 S50	114-692-13	25	50				
N 5936 T25 S65	114-692-16	25	65				
CLASSIC SPROCKETS MACHINED							
ROUND BORES							  
KU 5936 T10 R20	I5936647701	10	20	63.2	63.5	25	
KU 5936 T24 R20	I5936644081	24	20	147.3	149.2		
KU 5936 T31 R20	I5936600402	31	20	190.1	193.3		

1000-SERIES MODULAR BELTS

The 1000-series 1-inch pitch belt combines strong design features with an all-round pitch, making it a versatile belt; it is suitable for amongst others beverage, packaging and food industry. Mold-to-width executions are available with Positrack guiding for single line applications and packaging machines. 1000-Series can be equipped with flights for food industry applications. As a standard the belts are supplied in low friction acetal and polypropylene for beverage and in materials with antibacterial protection, especially for direct food contact and high-risk processing areas.

FEATURES

- Versatile 1-inch pitch and the rigid cross-rib design result in optimum flatness and therefore superior product handling.
- The clip pin retention system in combination with the 2 module system makes the belt very easy to install and maintain.
- Rounded outside edges for better side transfers and improved product handling.
- 1000-Series belt is companioned by FTM 1060 and FGM 1050 or FT 1050 chainbelts, to make a perfect match between straight running and sideflexing conveyors.

PROGRAMME	
1000 Flat Top (FT)	Closed surface; suitable for both glass and PET containers due to high strength. The absence of gaps prevents small (glass) particles to jam in the surface of the belt; the fully closed surface gives maximum support to the products conveyed
1000 Flush Grid (FG)	40% Open area; this guarantees optimum water- and airflow and allows pollution to fall through and maintain a clean contact surface between products and the belt. Suitable for amongst others can making and can processing
1000 Raised Rib (RR)	40% Open area; in combination with the special Click-Comb fingerplates the Raised Rib surface creates smooth transfers on accumulation tables, (de)palletizers and discharge tables
1000 Raised Rib narrow (RR)	13% Open area; suitable for packaging machines
1000 Raised Rib Railtrack (RRR)	1000 RR narrow belts with Railtrack, for optimum guiding and economic conveyor set-up
1000 SuperGrip (SG)	High friction rubber surface to handle packages on inclined and declined conveyors. Standard angles up to 20°
1000 LBP	Low Backline Pressure execution with low noise rollers, securing optimum handling of vulnerable packed products, such as shrink-wrapped trays with and without cardboard bottom
FreeFlow	Dynamic Transfer System for complete elimination of dead plates at 90° transfers, creating self-clearing transfers
Positrack	Lugs for accurate and reliable guiding of mass handling and single track belts, resulting in optimum product handling
Belt accessories	Flights to handle bulk food stuff on inclined and declined conveyors; fingerplates RR 1000 and RR 1000 narrow for precise transfers




PET BOTTLE CONVEYOR WITH 1000 FLAT TOP BELT




CHICKEN ON FREEZER INFEED WITH 1000 FLUSH GRID BELT

1000-SERIES



**FLAT TOP
1000**






Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH POLYPROPYLENE PINS (84 HAS PBT PINS)							
STANDARD	FT 1000 XLG	817.30.xx	4 to 80	4 to 65	22000	6.50	25
DOUBLE POSITRACK	FTDP 1000 XLG	873.27.xx					
POSITRACK 1 SIDE, FREEFLOW 1 SIDE	FFTP 1000 XLG	873.08.xx					
POSITRACK 2 SIDES, FREEFLOW 1 SIDE	FFTP 1000 XLG	873.07.xx					
DOUBLE POSITRACK 84	FTDP 1000 XLG 84	873.21.09	-30 to +80	up to 65			
PS-ACETAL WITH POLYPROPYLENE PINS (84 HAS PBT PINS)							
DOUBLE POSITRACK	FTDP 1000 PS	873.35.xx	4 to 80	4 to 65	22000	6.50	25
DOUBLE POSITRACK 84	FTDP 1000 PS 84	873.35.09	-30 to +80	up to 65			
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	FT 1000 XP	818.30.xx	4 to 104	4 to 104	11000	4.25	25
DOUBLE POSITRACK	FTDP 1000 XP	873.29.xx					
AS-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	FT 1000 AS	814.30.xx	4 to 80	–	13000	6.11	25
DOUBLE POSITRACK	FTDP 1000 AS	873.32.xx					
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 1000 FT	812.60.xx	-70 to +35	-70 to +35	5000	4.60	25
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	BLA 1000 FT	812.80.xx	-70 to +35	-70 to +35	5000	4.60	25
ANTIBACTERIAL WHA-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHA 1000 FT	811.80.xx	4 to 104	4 to 104	11000	4.30	25
ANTIBACTERIAL WSA-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	WSA 1000 FT	815.70.xx	4 to 80	4 to 65	22000	6.50	25
DOUBLE POSITRACK	WSA 1000 FTDP	873.28.xx					

* In code numbers xx corresponds with the belt width (A), starting with 10 for 85 mm, 11 for 170 mm and so on with 85 mm increments, or optionally 5 mm, up to 6120 mm; see also page 206.

If you need flights, describe the belt by choosing from the required options listed in the 2nd column of the table:

Material	WLA or BLA or WHA or WSA	
Belt type	1000 FT or 1000 FTDP	(Double) Positrack not possible for WLA, BLA and WHA
Width (A)	KM-.. (in mm)	Belts with flights have a minimal width of 130 mm with 10 mm increments
Flights	F3 or F2 or F1 or H..	Standard height of 3", 2", 1" or special height in mm
Pitch between flights	T..P	Flights on every .. th row (must correspond to an even number of rows)
Flight side-indent	N.. (in mm)	Minimal 40 mm with 5 mm increments

Example: WSA 1000 FTDP KM-430 H50 T6P N45 is a 1000 Flat Top belt with Double Positrack, made of white acetal with Microban, special width 430 mm, special 50 mm high flights on every 6th row at 45 mm from the sides




FLIGHT 1000-SERIES

1000-SERIES



FLUSH GRID 1000






Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH POLYPROPYLENE PINS (84 HAS PBT PINS)							
STANDARD	FG 1000 XLG	817.40.xx	4 to 80	4 to 65	22000	5.40	25
DOUBLE POSITRACK	FGDP 1000 XLG	874.43.xx					
POSITRACK 1 SIDE, FREEFLOW 1 SIDE	FFGP 1000 XLG	874.08.xx					
POSITRACK 2 SIDES, FREEFLOW 1 SIDE	FFGP 1000 XLG	874.07.xx					
DOUBLE POSITRACK 84	FGDP 1000 XLG 84	874.30.09	-30 to +80	up to 65			
PS-ACETAL WITH POLYPROPYLENE PINS (84 HAS PBT PINS)							
DOUBLE POSITRACK	FGDP 1000 PS	874.57.xx	4 to 80	4 to 65	22000	5.40	25
DOUBLE POSITRACK 84	FGDP 1000 PS 84	874.57.09	-30 to +80				
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	FG 1000 XP	818.40.xx	4 to 104	4 to 104	11000	3.53	25
DOUBLE POSITRACK	FGDP 1000 XP	874.45.xx					
AS-ACETAL WITH POLYPROPYLENE PINS WITH POLYPROPYLENE PINS							
STANDARD	FG 1000 AS	814.40.xx	4 to 80	–	13000	5.08	25
DOUBLE POSITRACK	FGDP 1000 AS	874.48.xx					
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 1000 FG	812.70.xx	-70 to +35	-70 to +35	5000	3.70	25
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	BLA 1000 FG	812.90.xx	-70 to +35	-70 to +35	5000	3.70	25
ANTIBACTERIAL WHA-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHA 1000 FG	811.90.xx	4 to 104	4 to 104	11000	3.50	25
ANTIBACTERIAL BHA-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	BHA 1000 FG	810.08.xx	4 to 104	4 to 104	11000	3.50	25
ANTIBACTERIAL WSA-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	WSA 1000 FG	815.80.xx	4 to 80	4 to 65	22000	5.40	25
DOUBLE POSITRACK	WSA 1000 FGDP	874.44.xx					
ANTIBACTERIAL BSA-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BSA 1000 FG	810.07.xx	4 to 80	4 to 65	22000	5.40	25

* In code numbers xx corresponds with the belt width (A), starting with 10 for 85 mm, 11 for 170 mm and so on with 85 mm increments, or optionally 5 mm, up to 6120 mm; see also page 206.



If you need flights, describe the belt by choosing from the required options listed in the 2nd column of the table:

Material	WLA or BLA or WHA or BHA or WSA or BSA	
Belt type	1000 FG or 1000 FGDP	(Double) Positrack not possible for WLA, BLA, WHA, BHA and BSA
Width (A)	KM-.. (in mm)	Belts with flights have a minimal width of 130 mm with 10 mm increments
Flights	F3 or F2 or F1 or H..	Standard height of 3", 2", 1" or special height in mm
Pitch between flights	T..P	Flights on every .. th row (must correspond to an even number of rows)
Flight side-indent	N.. (in mm)	Minimal 40 mm with 5 mm increments



FREEFLOW 1000-SERIES

1000-SERIES




Assembly	Belt type	Code nr.	Width	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			A	dry	wet			
			mm					
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS								
STANDARD	SG 1000 XP 170	875.00.11	170	4 to 65	4 to 65	11000	5.00	30
	SG 1000 XP 255	875.00.12	255				5.33	
	SG 1000 XP 340	875.00.13	340				5.50	
	SG 1000 XP 425	875.00.14	425				5.60	
	SG 1000 XP 510	875.00.15	510				5.66	
	SG 1000 XP 595	875.00.16	595				5.71	
	SG 1000 XP 680	875.00.17	680				5.75	
DOUBLE POSITRACK	SGDP 1000 XP 170	875.54.11	170				5.00	
	SGDP 1000 XP 255	875.54.12	255				5.33	
	SGDP 1000 XP 340	875.54.13	340				5.50	
	SGDP 1000 XP 425	875.54.14	425				5.60	
	SGDP 1000 XP 510	875.54.15	510				5.66	
	SGDP 1000 XP 595	875.54.16	595				5.71	
	SGDP 1000 XP 680	875.54.17	680				5.75	
XLG-ACETAL WITH POLYPROPYLENE PINS								
STANDARD	SG 1000 XLG 170	875.30.11	170	4 to 65	4 to 65	19000	7.34	30
	SG 1000 XLG 255	875.30.12	255				7.70	
	SG 1000 XLG 340	875.30.13	340				7.88	
	SG 1000 XLG 425	875.30.14	425				7.99	
	SG 1000 XLG 510	875.30.15	510				8.06	
	SG 1000 XLG 595	875.30.16	595				8.12	
	SG 1000 XLG 680	875.30.17	680				8.16	
DOUBLE POSITRACK	SGDP 1000 XLG 170	875.59.11	170				7.34	
	SGDP 1000 XLG 255	875.59.12	255				7.70	
	SGDP 1000 XLG 340	875.59.13	340				7.88	
	SGDP 1000 XLG 425	875.59.14	425				7.99	
	SGDP 1000 XLG 510	875.59.15	510				8.06	
	SGDP 1000 XLG 595	875.59.16	595				8.12	
	SGDP 1000 XLG 680	875.59.17	680				8.16	
ANTIBACTERIAL WHA-POLYPROPYLENE WITH POLYPROPYLENE PINS								
STANDARD	SG 1000 WHA 255	875.25.12	255	4 to 104	4 to 104	11000	5.33	30
	SG 1000 WHA 340	875.25.13	340				5.50	
	SG 1000 WHA 425	875.25.14	425				5.60	
	SG 1000 WHA 510	875.25.15	510				5.66	
	SG 1000 WHA 595	875.25.16	595				5.71	
	SG 1000 WHA 680	875.25.17	680				5.75	

Special widths begin at 85 mm with 5 mm increments. Wider belts are available upon request.


Standard 100% rubber; other percentages can be supplied upon request.

Rubber top is a black elastomere, with a hardness of 40 (XP) or 50 (XLG) or 60 (WHA) shore A

1000-SERIES







**RAISED RIB
1000**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet	N/m (21°C)	kg/m²	mm
XLG-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	RR 1000 XLG	817.10.xx	4 to 80	4 to 65	22000	7.95	50
AS-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	RR 1000 AS	814.10.xx	4 to 80	–	13000	7.47	50

* In code numbers xx corresponds with the belt width (A), starting with 10 for 85 mm, 11 for 170 mm and so on with 85 mm increments, up to 6120 mm; see also page 206. Special widths begin at 85 mm with 5 mm increments.


Type	Code nr.	Weight kg	Width W mm	Length mm		
FINGERPLATES RAISED RIB						
XLG-ACETAL						
1000 XLG 154 x 170	817.12.05	0.14	168	154		
1000 XLG 154 x 85	817.12.04	0.07	83			
AS-ACETAL						
1000 AS 154 x 170	814.12.05	0.13	168	154		
1000 AS 154 x 85	814.12.04	0.06	83			

Code nr.	Number of pitches	Length L	For belt width	Weight	Height H	Pitch X			
		mm	mm	kg	mm	mm	inch		
PROFILES FOR FINGERPLATES									
STAINLESS STEEL									
801.55.10	7	672	0 < W ≤ 595	0.54	18			85.0	3.35
801.55.11	13	1182	595 < W ≤ 1105	0.95					
801.55.13	19	1692	1105 < W ≤ 1615	1.35					
801.55.14	25	2202	1615 < W ≤ 2125	1.76					
801.55.16	31	2712	2125 < W ≤ 2635	2.17					
801.55.19	43	3732	2635 < W ≤ 3655	2.99					
801.55.22	55	4752	3655 < W ≤ 4675	3.80					
801.55.01	70	6027	4675 < W ≤ 5950	4.82					

1000-SERIES



**RAISED RIB 1000
NARROW**




Assembly	Belt type	Code nr.	Width	Temperature range °C		Working load (max.) N (21°C)	Weight kg/m	Backflex radius (min.) mm
			A					
			mm	dry	wet			
XLG-ACETAL WITH PBT PINS								
STANDARD	RR 1000-38 XLG	871.01.00	38	-30 to +80	up to 65	400	0.39	50
	RR 1000-48 XLG	871.01.01	48	-30 to +80	up to 65	600	0.48	
	RR 1000-58 XLG	871.01.02	58	-30 to +80	up to 65	800	0.59	

Standard length: 6.096 m - 20 feet.






**RAISED RIB 1000
RAILTRACK NARROW**




Assembly	Belt type	Code nr.	Width	Temperature range °C		Working load (max.) N (21°C)	Weight kg/m	Backflex radius (min.) mm
			A					
			mm	dry	wet			
XLG-ACETAL WITH PBT PINS								
STANDARD	RRR 1000-28 XLG	871.00.03	28	-30 to +80	up to 65	200	0.33	50
	RRR 1000-38 XLG	871.00.00	38	-30 to +80	up to 65	400	0.43	
	RRR 1000-48 XLG	871.00.01	48	-30 to +80	up to 65	600	0.53	
	RRR 1000-58 XLG	871.00.02	58	-30 to +80	up to 65	800	0.62	


Standard length: 3.048 m - 10 feet.

Type	Code nr.	Weight kg	Width W mm	Length mm	
FINGERPLATES RAISED RIB NARROW					
XLG-ACETAL					
1000 XLG 114 x 23	817.12.13	0.01	23	114	
1000 XLG 114 x 33	817.12.10	0.02	33		
1000 XLG 114 x 43	817.12.11	0.02	43		
1000 XLG 114 x 53	817.12.12	0.03	53		
					
					
					

1000-SERIES




LBP
1000



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH PBT PINS							
DOUBLE POSITRACK	LBPDP 1000 XLG	874.47.xx	4 to 80	4 to 65	19400	5.40	25



* In code numbers xx corresponds with the belt width (A), starting with 11 for 170 mm, 12 for 255 mm and so on with 85 mm increments up to 6120 mm; see also page 206.

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A	MATERIAL page 209
			mm/inch	mm	mm	mm	
SPLIT SPROCKETS WIDE HUB							
ROUND BORES							 
SSW 1000 16-30	899.06.17	16	30 mm	130.2	130.6	39	
SSW 1000 16-35	899.06.10	16	35 mm				
SSW 1000 16-40	899.06.11	16	40 mm				
SSW 1000 18-30	899.08.17	18	30 mm	146.3	146.8		
SSW 1000 18-35	899.08.10	18	35 mm				
SSW 1000 18-40	899.08.11	18	40 mm				
SSW 1000 20-30	899.09.17	20	30 mm	162.4	163.1		
SSW 1000 20-35	899.09.10	20	35 mm				
SSW 1000 20-40	899.09.11	20	40 mm				
SSW 1000 16-1½	899.06.31	16	1.5"	130.2	130.6		
SSW 1000 18-1½	899.08.31	18	1.5"	146.3	146.8		
SSW 1000 20-1½	899.09.31	20	1.5"	162.4	163.1		
SQUARE BORES							
SSW 1000 16-40x40	899.06.21	16	40 mm	130.2	130.6	39	
SSW 1000 18-40x40	899.08.21	18	40 mm	146.3	146.8		
SSW 1000 20-40x40	899.09.21	20	40 mm	162.4	163.1		
SSW 1000 16-1½x1½	899.06.41	16	1.5"	130.2	130.6		
SSW 1000 18-1½x1½	899.08.41	18	1.5"	146.3	146.8		
SSW 1000 20-1½x1½	899.09.41	20	1.5"	162.4	163.1		

For wide hub sprockets with round bore one keyway is sufficient.

For humid, hot applications like pasteurizing, special sprockets are available; see next page.

1000-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209	
CLASSIC SPROCKETS								
ROUND BORES								
CS 1000 12-30	895.02.17	12	30 mm	98.1	96.5	20	 	
CS 1000 12-40	895.02.11	12	40 mm					
CS 1000 12-50	895.02.12	12	50 mm					
CS 1000 18-30	895.08.17	18	30 mm	146.3	145.9			30
CS 1000 18-35	895.08.10	18	35 mm					
CS 1000 18-40	895.08.11	18	40 mm					
CS 1000 18-45	895.08.15	18	45 mm					
CS 1000 18-50	895.08.12	18	50 mm					
CS 1000 18-65	895.08.13	18	65 mm					
CS 1000 20-35	895.09.10	20	35 mm	162.4	161.7	20		
CS 1000 20-40	895.09.11	20	40 mm					
CS 1000 20-50	895.09.12	20	50 mm					
CS 1000 12-1	895.02.46	12	1.0"	98.1	96.5			
CS 1000 18-1	895.08.46	18	1.0"	146.3	145.9			
CS 1000 18-1½	895.08.41	18	1.5"					
CS 1000 18-2	895.08.42	18	2.0"					
CS 1000 20-1	895.09.46	20	1.0"	162.4	161.7			
CS 1000 20-1½	895.09.41	20	1.5"					
SQUARE BORES								
CS 1000 18-40x40	895.08.21	18	40 mm	146.3	145.9	20		
CS 1000 18-60x60	895.08.28	18	60 mm			30		
CS 1000 18-65x65	895.08.23	18	65 mm					
CS 1000 20-40x40	895.09.21	20	40 mm	162.4	161.7	20		
CS 1000 20-60x60	895.09.28	20	60 mm			30		
CS 1000 20-65x65	895.09.23	20	65 mm					
CS 1000 12-1½x1½	895.02.51	12	1.5"	98.1	96.5	20		
CS 1000 18-1½x1½	895.08.51	18	1.5"	146.3	145.9			
CS 1000 20-1½x1½	895.09.51	20	1.5"	162.4	161.7			
CLASSIC SPROCKETS FOR HUMID, HOT APPLICATIONS LIKE PASTEURIZING								
SQUARE BORES								
CS 1000 12-40x40 POM	893.02.21	12	40 mm	98.1	96.5	20		
CS 1000 18-40x40 POM	893.08.21	18	40 mm	146.3	145.9	20		
CS 1000 18-60x60 POM	893.08.28	18	60 mm			30		
CS 1000 20-40x40 POM	893.09.21	20	40 mm	162.4	161.7	20		
CS 1000 20-60x60 POM	893.09.28	20	60 mm			30		
 								

1005-SERIES MODULAR BELTS

The 1005-series 1-inch pitch heavy-duty belt combines a 1/2-inch thickness with a robust belt design and an all-round pitch, making it a versatile belt for amongst others beverage, glass manufacturing and packaging applications. As a standard the belts are supplied in low friction acetel, extremely wear resistant polyamide and polypropylene.

FEATURES

- Robust belt design and high strength to meet the most demanding applications in beverage, glass making and packaging.
- The revolutionary Easy Lock pin retention system in combination with the 2 module system makes the belt very easy to install and maintain.
- Rounded outside edges for better side transfers and improved product handling.
- 85 mm pitched fixed sprocket positions improve the drive properties and contribute to standardization of the conveyor design.
- Equipped with wear resistant polyester (PBT) pins for the best long term performance.
- 1005-Series belts are companioned by FTM 1055 or FT 1055 chainbelts, to make a perfect match between straight running and sideflexing conveyors.

PROGRAMME	
1005 Flat Top (FT)	Closed surface; suitable for heavy duty glass handling applications and other abrasive environments
1005 SuperGrip (SG)	Execution with high friction rubber surface to handle packages on inclined, declined and metering conveyors; standard angles up to 20°. Special design of the rubber profile makes it suitable for crate handling as well
1005 LBP	Low Backline Pressure execution with low noise rollers, securing optimum handling of vulnerable packed products, such as shrink-wrapped trays with and without cardboard bottom
FreeFlow	Dynamic Transfer System allows complete elimination of dead plates at 90° transfers, creating self-clearing transfers
Positrack	Lugs for accurate and reliable guiding of mass handling and single track belts, resulting in optimum product handling



TRAY CONVEYOR WITH 1005 SUPERGRIP BELT




GLASS BOTTLE MANUFACTURING ON 1005 FLAT TOP BELT




BOXES PROCESSED ON 1005 LBP BELT

1005-SERIES




FLAT TOP
1005





Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH PBT PINS							
STANDARD	FT 1005 XLG	877.00.xx	-40 to +80	up to 65	35000	13.50	25
DOUBLE POSITRACK	FTDP 1005 XLG	877.01.xx					
DOUBLE POSITRACK, FREEFLOW	FFDP 1005 XLG	877.02.xx					
MOULD TO WIDTH (MTW)	FT 1005 XLG K450 MTW	877.00.00					
MTW DOUBLE POSITRACK	FTDP 1005 XLG K450 MTW	877.01.00					
PS-ACETAL WITH PBT PINS							
STANDARD	FT 1005 PS	877.16.xx	-40 to +80	up to 65	35000	13.50	25
DOUBLE POSITRACK	FTDP 1005 PS	877.13.xx					
WX-POLYAMIDE COMPOSITE WITH PBT PINS							
STANDARD	FT 1005 WX	877.14.xx	-40 to +80	not recommended	35000	13.50	25
DOUBLE POSITRACK	FTDP 1005 WX	877.15.xx					
MOULD TO WIDTH (MTW)	FT 1005 WX K450 MTW	877.14.00					
MTW DOUBLE POSITRACK	FTDP 1005 WX K450 MTW	877.15.00					
XP-POLYPROPYLENE WITH PBT PINS							
STANDARD	FT 1005 XP	877.05.xx	4 to 65	4 to 65	17500	9.00	25
DOUBLE POSITRACK	FTDP 1005 XP	877.06.xx					


* In code numbers xx corresponds with the belt width (A), starting with 10 for 85 mm, 11 for 170 mm and so on in steps of 85 mm up to 6120 mm. Other sizes upon request. See page 206 for all code numbers.




FLAT TOP 1005 HEAVY DUTY BELT WITH POSITRACK



FLAT TOP 1005 HEAVY DUTY BELT WITH INTEGRATED FREEFLOW




The double Positrac lugs are positioned on one side of the belt for precise transfer possibilities.




1005 BELT MOULD TO WIDTH WITH DOUBLE POSITRACK

1005-SERIES





**SUPERGRIP
1005**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XLG-ACETAL WITH PBT PINS							
STANDARD	SG 1005 XLG	877.50.xx	-40 to +65	up to +65	35000	14.00	25
DOUBLE POSITRACK	SGDP 1005 XLG	877.51.xx					
XP-POLYPROPYLENE WITH PBT PINS							
STANDARD	SG 1005 XP	877.64.xx	4 to 65	4 to 65	17500	10.00	25
DOUBLE POSITRACK	SGDP 1005 XP	877.66.xx					
TCF-TOUGH COMPOSITE FRICTION MATERIAL WITH STAINLESS STEEL PINS							
STANDARD	SG 1005 TCF	877.71.xx	-18 to +82	-18 to + 60	32000	19.30	25
DOUBLE POSITRACK	SGDP 1005 TCF	877.72.xx					


* In code numbers xx corresponds with the belt width (A), starting with 11 for 170 mm, 12 for 255 mm and so on with 85 mm increments up to 6120 mm; see also page 206. Standard 100% rubber; other percentages and sizes on request.

Rubber top is a black elastomere, with a hardness of 40 (XP) or 50 (XLG) or 70 (TCF) shore A.




1005 SUPERGRIP BELT WITH DOUBLE POSITRACK ON ONE SIDE OF THE BELT

1005-SERIES



**SUPERGRIP
SIDE-INDENT
1005**





Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet			
XLG-ACETAL WITH PBT PINS							
STANDARD	SGS 1005 XLG	877.52.xx	-40 to +65	up to 65	35000	14.00	25
DOUBLE POSITRACK	SGSDP 1005 XLG	877.53.xx					
XP-POLYPROPYLENE WITH PBT PINS							
STANDARD	SGS 1005 XP	877.65.xx	4 to 65	4 to 65	17500	10.00	25
DOUBLE POSITRACK	SGSDP 1005 XP	877.67.xx					


* In code numbers xx corresponds with the belt width (A), starting with 12 for 255 mm, 13 for 340 mm and so on with 85 mm increments up to 6120 mm; see also page 206. Standard 100% rubber; other percentages and sizes on request.

Rubber top is a black elastomere, with a hardness of 40 (XP) or 50 (XLG) shore A.


A center indent of 85 mm is possible from 765 mm belt width, with steps of 170 mm. A



1005 SUPERGRIP SIDE-INDENT BELT WITH DOUBLE POSITRACK




LBP
1005




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet	N/m (21°C)	kg/m²	mm
XLA-ACETAL WITH PBT PINS							
STANDARD	LBP 1005SR XLA	877.17.xx	1 to 65	35000	30	120	
DOUBLE POSITRACK	LBPDP 1005SR XLA 877.18.xx	40 to 180					

* In code numbers xx corresponds with the belt width (A), starting with 11 for 170 mm, 12 for 255 mm and so on in steps of 85 mm up to 6120 mm. Other sizes upon request. See page 206 for all code numbers.



1005 HEAVY DUTY LBP BELT WITH DOUBLE POSITRACK ON ONE SIDE OF THE BELT

1005-SERIES

Sprocket Type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	
SPLIT SPROCKETS AND IDLERS							
SPROCKETS WITH ROUND BORES							 
SS 1005 18-30	894.30.67	18	30 mm	146.3	145.3	38	
SS 1005 18-40	894.30.61	18	40 mm				
SS 1005 21-30	894.33.67	21	30 mm	170.4	169.7		
SS 1005 21-40	894.33.61	21	40 mm				
SS 1005 18-1	894.30.86	18	1.0"	146.3	145.3		
SS 1005 18-1 1/2	894.30.81	18	1.5"				
SS 1005 21-1	894.33.86	21	1.0"	170.4	169.7		
SS 1005 21-1 1/2	894.33.81	21	1.5"				
IDLERS							Split sprockets with keyways are 'tight fit' onto the shaft and can be used for belt widths up to 680 mm and temperature differences of max. 30°C. For wider belts or bigger temperature differences, square bores have to be used. Square sprockets can be used on the drive- and on the idler shaft. They 'float' freely on the shaft.
SI 1005 18-30	894.30.77	18	30 mm	146.3	145.3	38	
SI 1005 18-40	894.30.71	18	40 mm				
SI 1005 21-30	894.33.77	21	30 mm	170.4	169.7		
SI 1005 21-40	894.33.71	21	40 mm				
SI 1005 18-1	894.30.96	18	1.0"	146.3	145.3		
SI 1005 18-1 1/2	894.30.91	18	1.5"				
SI 1005 21-1	894.33.96	21	1.0"	170.4	169.7		
SI 1005 21-1 1/2	894.33.91	21	1.5"				
SPROCKETS WITH SQUARE BORES							38
SS 1005 18-40x40	894.30.21	18	40 mm	146.3	145.3		
SS 1005 21-40x40	894.33.21	21	40 mm	170.4	169.7		
SS 1005 18-1 1/2x1 1/2	894.30.51	18	1.5"	146.3	145.3		
SS 1005 21-1 1/2x1 1/2	894.33.51	21	1.5"	170.4	169.7		

MATERIAL

page 209

MATERIAL

page 209

Split sprockets with keyways are 'tight fit' onto the shaft and can be used for belt widths up to 680 mm and temperature differences of max. 30°C. For wider belts or bigger temperature differences, square bores have to be used.

Square sprockets can be used on the drive- and on the idler shaft. They 'float' freely on the shaft.

1010-SERIES MODULAR BELTS

The 1010-series 1-inch pitch belt is designed to meet the increasing demand from food processing industry for improved hygiene and better cleanable products. It is meant for light to medium duty applications, where cleanability and hygiene have got the highest importance. It can handle meat, poultry, seafood, fruits and salads after being cut or processed otherwise. As a standard the belts are supplied in food-grade materials with antibacterial protection, especially for direct food contact and high-risk areas.

FEATURES

- When turning over a small roller the hinges open, exposing a large pin surface, offering excellent cleaning possibilities. The hinge design is extremely open and accessible, so a large surface of the pin and the inside of the hinge can be cleaned directly. The bottom of the module is curved, improving drainage and reducing drying time of the belt after cleaning.
- Using a moulded pin with T-shaped head keeps the pin in a specially designed eccentric outer hinge eye. This makes the belt easy to operate for maintenance and cleaning.
- The belt is supplied mould-to-width up to 24 inch, avoiding adjacent surfaces between the modules. The hinges are 1/2 inch wide, reducing the number of adjacent surfaces in-between.
- Fully closed machined sprockets, ideal for cleaning. Due to the double teeth rows the sprockets are bi-directional and easy to position.
- As a standard antibacterial protection incorporated for direct food contact.

PROGRAMME	
1015 Solid Top	Closed surface; it offers the best support to vulnerable products and prevents loss of small products
Belt accessories	Flights to handle bulk food stuff on inclined and declined conveyors. They are ribbed on both sides, improving the release properties against sticky or frozen products. The flights can be positioned until the side of the belt or with a 1-inch side-indent on any pitch required. Other side-indents on request.





PORK MEAT ON AFTER TRIMMING ON 1015 BELT




FISH FINGER PROCESSING ON 1015 BELT

1010-SERIES



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ANTIBACTERIAL WLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 1015	846.22.xx	-70 to +35	-70 to +35	5000	4.80	40
ANTIBACTERIAL BLA-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	BLA 1015	846.22.xx	-70 to +35	-70 to +35	5000	4.80	40
ANTIBACTERIAL WHA-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHA 1015	849.22.xx	4 to 104	4 to 104	6000	4.40	40
ANTIBACTERIAL BHA-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	BHA 1015	849.22.xx	4 to 104	4 to 104	6000	4.40	40
ANTIBACTERIAL WSA-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	WSA 1015	844.22.xx	-40 to +80	-40 to +65	12000	7.00	40
ANTIBACTERIAL BSA-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BSA 1015	844.22.xx	-40 to +80	-40 to +65	12000	7.00	40

* In code numbers xx corresponds with the belt width (A), for White belts (WLA, WHA, WSA) starting with 00 for 4", 01 for 5", for Blue belts (BLA, BHA, BSA) starting with 50 for 4", 51 for 5" and so on in steps of 1", up to 44". Optionally 1/2" increments are possible up to 24". See also page 206.



If you need flights, describe the belt by choosing the required options listed in the 2nd column of the table

Material	WLA or BLA or WHA or BHA or WSA or BSA	
Belt type	1015	
Width (A)	K.. (in inches)	Belts with flights have minimal width of 6"
Flights	RF3 or RF4 or RH..	Ribbed 3 to 4" high flight or special height in mm
Pitch between flights	T..P	Flight on every .. th row
Flight side-indent	N0 or N1 or N..	Standard 0 or 1"; non-standard increments of 1/2", starting with 1 1/2"

FLIGHT FOR 1010-SERIES

Sprocket Type	Code nr.	Nr. of teeth	Bore	Pitch diameter E	Outside diameter F	Hub width A	
			B mm	mm	mm	mm	

MATERIAL

page 209

CLASSIC SPROCKETS								
ROUND BORES								
KU 1010 T10 R40	897.10.33	10	40	82.2	82.7	25		
KU 1010 T12 R40	897.10.42	12	40	98.1	98.9			
KU 1010 T16 R40	897.10.71	16	40	130.2	131.5			
KU 1010 T18 R40	897.10.86	18	40	146.3	147.8			
KU 1010 T20 R40	897.11.01	20	40	162.4	164.0			
SQUARE BORES								
KU 1010 T10 S40	897.10.35	10	40	82.2	82.7	25		
KU 1010 T12 S40	897.10.44	12	40	98.1	98.9			
KU 1010 T16 S40	897.10.73	16	40	130.2	131.5			
KU 1010 T18 S40	897.10.88	18	40	146.3	147.8			
KU 1010 T20 S40	897.11.03	20	40	162.4	164.0			



7700-SERIES MODULAR BELTS

The 7700-series 1-inch pitch heavy-duty belt is used for a large variety of applications. Because of its robust design these belts are common for glass works and automotive industry. 7700-Series is available in a closed, two open, a rubber top and a LBP execution. For single lane conveying several mold-to-width executions with Tab Guides are available. For applications in glass works and beverage industry the Dynamic Transfer System is a proven solution. As a standard the belts are supplied in high-performance acetal and polypropylene.

FEATURES

- Robust 1/2-inch thick module design means very high strength.
- HP acetal reduces friction, offers excellent wear resistance and creates dry-running possibilities.
- Rounded outside edges for better side transfers and improved product handling.
- Twist-lock™ pin retention by means of a hinged plug prevents plug loss and allows easy pin access for installation and maintenance.
- Dynamic Transfer System (DTS) creates smooth 90° transfers.
- Belt and sprocket design ensure an optimum engagement and a reliable drive.
- 7700-Series belts are companioned by FTM 1055 or FT 1055 chainbelts, to make a perfect match between straight running and sideflexing conveyors; 1055 can also be driven by NS 7700 sprockets.

PROGRAMME	
7705 Solid Top	Closed surface; for heavy-duty glass and PET applications metric version can optionally be equipped with Positrack
7706 Perforated Top	8% Open area; for amongst others can handling
7708 Perforated Top	20% Open area; for amongst others warmers and coolers
7705 Rubber Top	For inclined and declined conveyors up to 20°; available upon request
Positrack	Tabs for accurate guiding of the belt in the conveyor (metric execution and DTS only)
DTS	Single module Dynamic Transfer System for left- or right hand self-clearing transfers to avoid dead plates at 90° transfers; as a standard equipped with Positrack guiding




BOTTLE TRANSFER WITH 7705 BELT




TIRE PROCESSING ON 7708 BELT

7700-SERIES



**SOLID TOP
7705**




Assembly	Belt type	Code nr.*	Temperature range Working Weight °C		Backflex load (max.) (21°C)		radius (min.) mm
			dry	wet			
HP-ACETAL WITH PBT PINS							
STANDARD	HP 7705	I7705HPKxx	-40 to +80	-40 to +65	43000 N/m	13.47 kg/m ²	25
DTS LEFT	HP 7705 K450 DTS-SX	81413921					
POSITRACK	HP 7705 K750 DTS-SX	81413922					
DTS RIGHT	HP 7705 K450 DTS-DX	81413931					
POSITRACK	HP 7705 K750 DTS-DX	81413932					
MOULD TO WIDTH POSITRACK	HP7705PTK325	81415101					
	HP7705PTK450	81415141					
	HP7705PTK750	81415181					
WX-ACETAL WITH PBT PINS							
STANDARD	WX7705	WX7705-xx	-40 to +104	Not recommended	43000 N/m	13.47 kg/m2	25
MOULD TO WIDTH POSITRACK	WX7705PTK325	81430031			3047 N	1.03 kg/m	
	WX7705PTK450	WX7705-4.5			4559 N	1.39 kg/m	
	WX7705PTK750	81430041			7784 N	2.58 kg/m	

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 6" with 3" increments up to 120". Special widths start from 5" with 1/2" increments. see also page 206. Upon request 7705 belts can be supplied in metric versions.



7705 HTF BELT WITH RUBBER TOP




7705 TCF BELT WITH RUBBER TOP

7705 belts are also available with rubber top in HTF and TCF versions. Please contact Customer Service for more details.




SINGLE MODULE DYNAMIC TRANSFER SYSTEM (DTS)



7700-SERIES



**PERFORATED TOP
7706**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
HP-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	HP 7706	I7706HPKxx	-40 to +80	-40 to +65	43000	13.18	25


* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 6" with 3" increments up to 120". Special widths start from 5" with 1/2" increments. See also page 206.

For DTS, modules from page 167 are used.

7706 belts can be supplied in metric versions upon request.






**PERFORATED TOP
7708**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet	N/m (21°C)	kg/m²	mm
HT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	HT 7708	I7708HTKxx	4 to 100	4 to 100	26000	7.81	25
USP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	USP 7708	USP7708Kxx	4 to 100	4 to 100	26000	7.81	25

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 9" with 3" increments up to 120". Special widths start from 5" with 1/2" increments. See also page 206.

7700-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209	
SPLIT SPROCKETS INJECTION MOULDED								
ROUND BORES							 	
NS 7700 T16 R25	614-62-25	16	25	130.2	130.6	51		
NS 7700 T16 R30	614-62-30	16	30					
NS 7700 T16 R35	614-62-35	16	35					
NS 7700 T16 R40	614-62-40	16	40					
NS 7700 T18 R25	614-60-25	18	25	146.3	146.9			
NS 7700 T18 R30	614-60-30	18	30					
NS 7700 T18 R35	614-60-35	18	35					
NS 7700 T18 R40	614-60-40	18	40					
NS 7700 T21 R25	614-63-25	21	25	170.4	170.7			
NS 7700 T21 R30	614-63-30	21	30					
NS 7700 T21 R35	614-63-35	21	35					
NS 7700 T21 R40	614-63-40	21	40					
SPLIT SPROCKETS MACHINED								
SQUARE BORES							 	
KUS 7700 T16 S40	614-370-4	16	40	130.2	130.6	48		
KUS 7700 T18 S40	I7700604166	18	40	146.3	146.9			
KUS 7700 T18 S50	I7700604176	18	50					
KUS 7700 T21 S40	614-383-4	21	40	170.3	170.7			
KUS 7700 T21 S50	614-383-6	21	50					
KUS 7700 T21 S60	614-383-8	21	60					
CLASSIC SPROCKETS MACHINED								
SQUARE BORES							 	
KU 7700 T18 S50	114-3926-10	18	50	146.3	146.9	48		
KU 7700 T18 S60	114-3926-12	18	60					
KU 7700 T21 S50	114-3925-12	21	50	170.3	170.7			
KU 7700 T21 S60	114-3925-14	21	60					
KU 7700 T21 S65	114-3925-15	21	65					
KU 7700 T25 S50	114-3927-13	25	50	202.7	204.2			
Round bores are available upon request.								

6300T-SERIES MODULAR BELTS

The 6300-series 50 mm pitch hybrid belt combines the features of steel and plastic components with the advantages of a real modular system. The new 6300T series offers a brick-layed pattern in combination with a reusable pin retention system. In combination with flights and sideguards this belt is a common choice for the food industry. As a standard the belts are supplied in polypropylene and polyethylene.

FEATURES

- Fully plastic product support surface due to the cleverly positioned tension plates underneath the belt surface.
- 6391 and 6392 belt modules are diamond-shaped, resulting in a minimum contact area with the product, with little risk of product sticking to the belt surface.
- Easy to operate pin retention system.
- 6300T-series is strongly recommended for high-temperature applications, such as cookers and blanchers.
- High strength and good dimensional stability due to stainless steel frame of tension plates and pins; no large pitch elongation occurs because of thermal expansion during operation.
- Completely flush modules and edges.
- Bricklaid pattern improves belt robustness and enables easy maintenance and assembly.
- 6300T-Series belts are a replacement for the original 6300-series offering important advantages with respect to pin retention and product handling. 6300T and 6300-series run on the same sprockets. For replacement purposes 6300-series can still be obtained.

PROGRAMME	
6390T Solid Top	Closed surface; suitable for handling small and large products without product loss and where no drainage is required
6391T Perforated Top	26% Open area and the fine mesh make it suitable for applications with very small products requiring good drainage or airflow capabilities, such as blanchers, cookers and coolers
6392T Perforated Top	48% Open area for optimum water- and airflow; due to the bigger gaps it is intended for larger product particles; also suitable for blanchers, cookers and coolers
Belt accessories	Flights and sideguards can be supplied upon request; contact Technical Support




BEAN BLANCHER WITH 6391 BELT




SPINACH ELEVATED ON 6391 BELT

6390-SERIES



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet	N/m (21°C)	kg/m²	mm
WHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHT 6390T	I6390TWHTKxx	5 to 105		1500 per row tension plates	9.55	50
BHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	BHT 6390T	I6390TBHTKxx	5 to 105		1500 per row tension plates	9.55	50

* In code numbers xx corresponds with the belt width (A), starting with 225 mm with 75 mm increments up to 2475 mm.
Other sizes upon request. See also page 206.



FLIGHT 6390-SERIES FOR INCLINED APPLICATIONS

SIDEGUARDS 6390-SERIES


6390-series belts are equipped with stainless steel pins and with tension plates as shown in this table:

Belt width mm	Standard number tension plates	Max. number tension plates without sideguards	Max. number tension plates with sideguards
225	1	$\frac{\text{Belt width} - 225}{75} + 1$	$\frac{\text{Belt width} - 225}{75}$
300 - 750	2		
825 - 1200	4		
1275 - 1500	6		
1575 - 1800	8		
1875 - 2475	10		

6390-SERIES



PERFORATED TOP
6391T




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
WHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHT 6391T	I6391TWHTKxx	5 to 105		1500 per row tension plates	9.02	50
BHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	BHT 6391T	I6391TBHTKxx	5 to 105		1500 per row tension plates	9.02	50
WLT-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLT 6391T	I6391TWLTxx	-70 to +25		1500 per row tension plates	9.02	50

* In code numbers xx corresponds with the belt width (A). Standard nominal widths of these belts begin at 225 mm with 75 mm increments up to 2475 mm. Other sizes upon request. See also page 206.

6390-SERIES




**PERFORATED TOP
6392T**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
WHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHT 6392T	I6392TWHTKxx	5 to 105		1500 per row tension plates	8.75	50
BHT-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	BHT 6392T	I6392TBHTKxx	5 to 105		1500 per row tension plates	8.75	50
WLT-POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLT 6392T	I6392TWLTxx	-70 to +25		1500 per row tension plates	8.75	50

* In code numbers xx corresponds with the belt width (A). Standard nominal widths of these belts begin at 225 mm with 75 mm increments up to 2475 mm. Other sizes upon request. See also page 206.

Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm		
								MATERIAL page 209
SPLIT SPROCKETS								
ROUND BORES							 	
KUS 6390 T08 R30	I6390630652	8	30	130.6	120.7	60		
KUS 6390 T08 R40	I6390630692	8	40					
KUS 6390 T10 R30	I6390631462	10	30	161.8	153.9			
KUS 6390 T10 R40	I6390631482	10	40					
KUS 6390 T12 R30	I6390631572	12	30	193.1	186.6			
KUS 6390 T12 R40	I6390631592	12	40					
KUS 6390 T16 R30	I6390631682	16	30	256.3	251.4			
KUS 6390 T16 R40	I6390631702	16	40					
SQUARE BORES								
KUS 6390 T08 S40	I6390603836	8	40	130.6	120.7	60		
KUS 6390 T10 S40	I6390630512	10	40	161.8	153.9			
KUS 6390 T12 S40	I6390630532	12	40	193.1	186.6			
KUS 6390 T16 S40	I6390630552	16	40	256.3	251.4			



Other bore sizes upon request.

2000-SERIES MODULAR BELTS

The 2000-series 2-inch pitch belt is typically used in heavy-duty applications, such as pasteurizers, palletizers and accumulation tables. The modules are designed with rigid cross ribs and the multi-angular sprockets support the modules optimally. As a standard the belts are supplied in high-temperature and chemical resistant polypropylene.

FEATURES

- Pin retention by means of clips for easy installation and maintenance.
- Cross rib design creating a high stiffness of the modules to handle huge product loads and taking care of a flat surface for optimum product handling.
- Superb product handling from and onto the belt by using DTS-C transfer system in combination with Raised Rib 2000.



This system consists of a static fingerplate combined with a moving DTS or FreeFlow belt. The belt is positioned in the surface of the DTS-C fingerplate, enabling self-clearing transfers; this is important if changing from one product batch to another in a filling/processing line and if "hot-filled" products should not stay on the infeed transfer of the cooler. The DTS-C transfer eliminates sweepers for better line efficiency. The DTS belt in the system and the chain or belt on the main infeed or outfeed conveyor are supported by the same central wearstrip on the fingerplate, saving installation time and avoiding conveyor height adjustments.

PROGRAMME	
2000 Flat Top (FT)	Closed surface; for large and heavy products
2000 Flush Grid (FG)	31% Open area; this guarantees optimum water- and airflow and allows pollution to fall through; suitable for amongst others food and automotive applications
2000 Raised Rib (RR)	30% Open area; ideal for pasteurizer applications, warmers and coolers. This standard RR execution is meant for can or flat-based PET handling
2000 Raised Rib Heavy Duty (RRHD)	27% Open area; reinforced to deal with the difficult conditions in (one way) glass pasteurizers and dual purpose applications (cans and bottles)
2000 Super Rib (SR)	27% Open area; Full reinforced Super Rib design. Designed to deal with the difficult conditions in Glass pasteurizers and dual purpose applications (cans and bottles). SR 2000 chains are also suitable for PET handling
Positrack	Lugs in Raised Rib executions for reliable and accurate tracking of the belt in pasteurizer tunnels, allowing optimal use of the belt surface
Fingerplates	DTS System for self-clearing transfers, standard click-comb for cans and click-comb for glass applications, resulting in precise transfers




GLASS BOTTLE WARMER WITH 2000 RAISED RIB BELT AND DTS-C TRANSFER




BOTTLE ACCUMULATING ON 2000 BELT

2000-SERIES



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	FT 2000 XP	838.30.xx	4 to 104	4 to 104	29500	8.20	45


* In code numbers xx corresponds with the belt width (A), starting with 10 for 3", 11 for 6" and so on in steps of 3". See also page 206.



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	FG 2000 XP	838.40.xx	4 to 104	4 to 104	29500	7.55	35


* In code numbers xx corresponds with the belt width (A), starting with 10 for 3", 11 for 6" and so on in steps of 3". See also page 206.

2000-SERIES



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
XP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	RR 2000 XP	838.10.xx	4 to 104	4 to 104	29500	10.60	75
POSITRACK	RRP 2000 XP	838.90.xx					


* In code numbers xx corresponds with the belt width (A), starting with 10 for 3", 11 for 6" and so on in steps of 3". 2000 Belts with Positrack start with 12 for 9". See also page 206.




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
USP-POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	RRHD 2000 USP 881.60.xx	4 to 104 881.90.xx	4 to 104	29500	11.20	75	
POSITRACK	RRHDP 2000 USP						

* In code numbers xx corresponds with the belt width (A), starting with 10 for 3", 11 for 6" and so on in steps of 3". 2000 Belts with Positrack start with 12 for 9". See also page 206.

2000-SERIES




SUPER RIB
2000




Assembly	Belt type		Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
				dry	wet			
USP-POLYPROPYLENE WITH POLYPROPYLENE PINS								
STANDARD	SR 2000 USP	881.50.xx	4 to 104	4 to 104	29500	11.20	75	
POSITRACK	SRP 2000 USP	881.80.xx						

* In code numbers xx corresponds with the belt width (A), starting with 10 for 3", 11 for 6" and so on in steps of 3". 2000 Belts with Positrack start with 12 for 9". See also page 206.




RAISED RIB 2000 BELT WITH POSITRACK IN THE CENTER OF THE BELT OR 1.5" OFFSET, DEPENDING ON THE WIDTH

2000-SERIES




**CLICK-COMB FINGERPLATES
STANDARD**




'Click-Comb' fingerplate type	Code nr.	Length	Width W	Weight ≈
		mm	mm	kg
XLG-ACETAL				
2000 XLG 190 x 152	837.12.01	190	151	0.16
2000 XLG 190 x 74	837.12.02	190	74	0.08



**CLICK-COMB FINGERPLATES
FOR GLASS HANDLING**



'Click-Comb' fingerplate type	Code nr.	Length	Width W	Weight ≈
		mm	mm	kg
XLG-ACETAL				
GL 2000 XLG 163 x 152	837.12.09	163.1	151	0.16
GL 2000 XLG 163 x 74	837.12.03	163.1	74	0.08


Code nr.	Number of pitches	Length L	For belt width mm	Weight kg	Pitch X		Height H mm	
		mm			inch			
PROFILES FOR FINGERPLATES								
STAINLESS STEEL								
801.55.28	7	602	0 < W ≤ 533	0.44	76.2	3.00	15	
801.55.29	13	1059	533 < W ≤ 991	0.77				
801.55.31	19	1516	991 < W ≤ 1448	1.11				
801.55.32	25	1973	1448 < W ≤ 1905	1.44				
801.55.34	31	2430	1905 < W ≤ 2362	1.77				
801.55.37	43	3345	2362 < W ≤ 3277	2.44				
801.55.40	55	4259	3277 < W ≤ 4191	3.11				
801.55.43	67	5174	4191 < W ≤ 5105	3.78				
801.55.02	78	6012	5105 < W ≤ 5944	4.39				



2000-SERIES



**DTS-C TRANSFER SYSTEM
FOR PASTEURIZERS**



Product	Code nr.	Length	Width W	Weight ≈
		mm	mm	kg
REINFORCED POLYAMIDE				
DTS-C 2000-1005 190 x 152	834.12.79	190	152	0.25


BLACK UHMWPE			
Wearstrip DTS-C 2000	S0 362 694 341	3	
Wearstrip DTS-C 2000	S0 362 617 26	6	

Sprocket Type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A	
			mm/inch	mm	mm	mm	

SPLIT SPROCKETS

SQUARE BORES


SS 2000 13-90x90 POM	893.73.24	13	90 mm	212.3	209.0	45
SS 2000 16-65x65 POM	893.76.23	16	65 mm	260.4	262.0	
SS 2000 16-90x90 POM	893.76.24	16	90 mm			
SS 2000 16-120x120 POM	893.76.29	16	120 mm			



CLASSIC SPROCKETS

ROUND BORES

CS 2000 10-40 POM	893.10.11	10	40 mm	164.4	163.1	20
CS 2000 10-50 POM	893.10.12	10	50 mm	164.4	163.1	
CS 2000 12-40 POM	893.12.11	12	40 mm	196.3	196.3	
CS 2000 13-65 POM	893.13.13	13	65 mm	212.3	209.0	30
CS 2000 13-90 POM	893.13.14	13	90 mm	212.2	209.0	45
CS 2000 16-90 POM	893.16.14	16	90 mm	260.4	262.0	
CS 2000 16-2 1/2 POM	893.16.43	16	2.5"	260.4	262.0	30



SQUARE BORES

CS 2000 10-40x40 POM	893.10.21	10	40 mm	164.4	163.1	20
CS 2000 10-60x60 POM	893.10.28	10	60 mm	164.4	163.1	30
CS 2000 10-65x65 POM	893.10.23	10	65 mm	164.4	163.1	
CS 2000 12-40x40 POM	893.12.21	12	40 mm	196.3	196.3	20
CS 2000 12-60x60 POM	893.12.28	12	60 mm	196.3	196.3	30
CS 2000 12-65x65 POM	893.12.23	12	65 mm	196.3	196.3	
CS 2000 13-40x40 POM	893.13.21	13	40 mm	212.3	209.0	20
CS 2000 13-65x65 POM	893.13.23	13	65 mm	212.3	209.0	30
CS 2000 13-90x90 POM	893.13.24	13	90 mm	212.3	209.0	45
CS 2000 16-65x65 POM	893.16.23	16	65 mm	260.4	262.0	30
CS 2000 16-90x90 POM	893.16.24	16	90 mm	260.4	262.0	45
CS 2000 16-120x120 POM	893.16.29	16	120 mm	260.4	262.0	

2010-SERIES MODULAR BELTS

The 2010-series 2-inch pitch belts can be used in a large variety of food applications. These belts are used on deboning and trimming lines as well as medium- and heavy-duty elevators. Due to the various executions and the large range of accessories, a tailor-made solution for each food handling application is possible. All 2010-series belt materials are standard equipped with antibacterial protection for direct food contact.

FEATURES

- The modules are flush all around and do not have closed or hidden pockets. Especially the large open area between the rows of hinge eyes underneath the belt offer very good accessibility for cleaning. The rod retention area is very easy to clean and because of the absence of rims or hidden areas there is no risk of dirt and debris accumulating.
- This belt is very easy to assemble or disassemble, due to the integrated locking system. With a screwdriver the rod retention finger can be positioned in either the 'locked' or the 'unlocked' position.
- The extended hinge eyes underneath the belt provide a large footprint, reducing contact pressure and wear. The connection of the hinge eyes with the top plate is very rigid, giving the belt excellent impact resistance. The large rod diameter also means less pressure and wear reduction in the hinges.
- The design of the sprocket and the belt has been optimised to ensure an excellent drive, up to the maximum working load of the belt during its whole life. The machined sprockets have excellent strength and cleanability.
- As a standard equipped with antibacterial protection.

PROGRAMME	
2015 Solid Top	Closed surface; allows cutting and deboning on the belt surface; it offers the best support to vulnerable products and prevents loss of small products
2016 Perforated Top	20% open area; this allows optimum drainage and airflow in combination with good product support due to the rectangular slots
2011 Textured Top	Small nubs prevent sticking of soft and frozen products and sliding on the belt surface
Belt accessories	Straight, curved and bucket flights for elevators and other food applications. These can be combined with conventional sideguards and integrated siderails.



INCLINED CONVEYOR FOR CHIPS FTR2015 BELT



CONFECTIONARY ELEVATING ON 2015 BELT



CHICKEN DEBONING LINE WITH 2015 BELT



INFED OF INCLINED CONVEYOR WITH 2010 ISR6




TOMATO SORTING ON 2015 BELT

2010-SERIES




**SOLID TOP
2015**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.)	Weight	Backflex radius (min.)
			dry	wet			
ANTIBACTERIAL POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 2015	846.04.10	-70 to +35	-70 to +35	7500	9.50	87
STANDARD	BLA 2015	846.05.10	-70 to +35	-70 to +35	7500	9.50	87
ANTIBACTERIAL POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHA 2015	849.04.10	4 to 104	4 to 104	15000	8.90	87
STANDARD	BHA 2015	849.03.600	4 to 104	4 to 104	15000	8.90	87
ANTIBACTERIAL ACETAL WITH POLYPROPYLENE PINS							
STANDARD	WSA 2015	844.03.10	4 to 80	4 to 65	20000	13.60	87
STANDARD	BSA 2015	844.02.510	4 to 80	4 to 65	20000	13.60	87



**PERFORATED TOP
2016**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ANTIBACTERIAL POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 2016	846.07.00	-70 to +35	-70 to +35	7500	9.50	87
STANDARD	BLA 2016	846.09.00	-70 to +35	-70 to +35	7500	9.50	87
ANTIBACTERIAL POLYPROPYLENE WITH POLYPROPYLENE PINS							
STANDARD	WHA 2016	849.06.00	4 to 104	4 to 104	15000	8.90	87
STANDARD	BHA 2016	849.04.60	4 to 104	4 to 104	15000	8.90	87
ANTIBACTERIAL ACETAL WITH POLYPROPYLENE PINS							
MOULD TO ORDER	WSA 2016	844.03.51	4 to 80	4 to 65	20000	13.60	87
MOULD TO ORDER	BSA 2016	844.04.100	4 to 80	4 to 65	20000	13.60	87

* Code numbers in the table correspond with 6" wide belts. Code numbers go up with 1 (e.g. 846.07.01, 846.07.02 etc.) for each standard 2" increment (8", 10" etc.) up to 120". Optionally 2/3" increments possible. See also page 206.

If you require flights, sideguards or integrated siderail (ISR), please describe the belt by choosing from the options listed in the selection table on page 182.

2010-SERIES



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ANTIBACTERIAL POLYETHYLENE WITH POLYETHYLENE PINS							
STANDARD	WLA 2011	846.07.51	-70 to +35	-70 to +35	7500	9.50	87
STANDARD	BLA 2011	846.09.51	-70 to +35	-70 to +35	7500	9.50	87
ANTIBACTERIAL POLYPROPYLENE WITH POLYPROPYLENE PINS							
MOULD TO ORDER	WHA 2011	849.06.51	4 to 104	4 to 104	15000	8.90	87
MOULD TO ORDER	BHA 2011	849.02.60	4 to 104	4 to 104	15000	8.90	87
ANTIBACTERIAL ACETAL WITH POLYPROPYLENE PINS							
MOULD TO ORDER	WSA 2011	844.04.51	4 to 80	4 to 65	20000	13.60	87
MOULD TO ORDER	BSA 2011	844.05.00	4 to 80	4 to 65	20000	13.60	87

* Code numbers in the table correspond with 6" wide belts. Code numbers go up with 1 (e.g. 846.07.52, 846.07.53 etc.) for each standard 2" increment (8", 10" etc.) up to 120". Optionally 2/3" increments possible. See also page 206.

If you require flights or sideguards, please describe the belt by choosing from the options listed in the 2nd column of the table:

Material	WLA or BLA or WHA or BHA	
Belt type	2016	
Width (A)	K.. (in inches)	Belts with flights have a minimal width of 8"; smaller upon request
Flights	F1 or F2 or F3 or F4 or H.. F5 or F6 C4 or C6 RF2 or RF3 or RF4 or RH.. RC4 or RC6 B4 or B6	Straight; standard height 1" to 4" or special in mm; all materials available Straight; standard height 5" or 6" Curved; height 4" or 6" Ribbed straight; height 2", 3" or 4" or special in mm Ribbed curved; height 4" or 6" or special in mm Bucket flight; height 4" or 6"
Pitch between flights	T..P	Flights on every .. th row
Flight side-indent	N.. (in inches)	Minimal 1 1/3" with 2/3" increments; sideguards are situated at 1/3" from the flight, reducing the indent by 2/3"; if side-indent is 1 1/3", sideguards are directly besides the flight, reducing the indent by 1/3"
Sideguards	SG2 or SG3 or SG4	Standard height of 2", 3" or 4"
Integrated Siderail	ISR4 or ISR6	Standard height of 4" or 6" Other sizes up on request. Side Indent in combination with ISR is always 2 2/3" to the flight. Flights are positioned directly against the Integrated Siderail (ISR).

* Flight materials can differ from the belt material in some flight / belt combinations. F5 and F6 are heavy duty flights. Ribbed flights can be double ribbed (both sides) or single rib depending on material and execution.


Example: BLA 2016 K10 SG4 is a 2016 Perforated Top belt, made of blue polyethylene with Microban, width 10", no flights and 4" high sideguards.

Example: BHA2015 K24 C6 T4P ISR6, is a SolidTop belt, made of blue Polyporylene with Microban, width 24", with 6" high curved pushers every 6th row and 6" high Integrated Siderail (and therefore a side indent of 2 2/3")

2010-SERIES

Type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209
CLASSIC SPROCKETS							
SQUARE BORES							
CS 2010-6-40x40	897.20.23	6*	40	101.6	87.0	33	
CS 2010-8-40x40	897.20.04	8	40	132.8	121.0		
CS 2010-10-40x40	897.20.07	10	40	164.4	154.0		
CS 2010-10-60x60	897.20.10	10	60				
CS 2010-12-40x40	897.20.26	12	40	196.3	188.0		
CS 2010-12-60x60	897.20.29	12	60				
* 6 teeth sprockets are not recommended as drive sprockets.							







ACCESSORY INFORMATION:




STRAIGHT FLIGHT FOR 2010-SERIES






CURVED RIBBED FLIGHT FOR 2010-SERIES



SIDEGUARDS FOR 2010-SERIES



BUCKET FLIGHT FOR 2010-SERIES



INTEGRATED SIDERAIL (ISR) FOR 2010-SERIES, 6-INCH AND 4-INCH HIGH

9200-SERIES FORTREX™ STAINLESS STEEL MATTOP® CHAINS

To achieve the industry's highest reliability, Rexnord has designed 2¼-inch pitch Fortrex stainless steel MatTop chain, a breakthrough in tunnel pasteurizing conveying. In pasteurization, long-lasting shelf life and chain life are critically important. Long-lasting shelf life preserves the good taste and quality of beverages and foods. And, long-lasting chain life guarantees uninterrupted productivity as containers move at precise speeds through controlled temperature zones of long pasteurizer tunnels.

FEATURES


- Stainless steel chain design ensures ultimate reliability at reduced total cost of ownership, including glass handling applications.
- Suitable for parallel and chevron stainless steel wearstrips, so significantly reduced retrofit cost.
- Chain rollers reduce tension by 60% over sliding belts and reduce motor power requirements.
- Split sprockets and idlers can accommodate a classic drive shaft construction.
- Superior, extended chain life.
- Elimination of unscheduled tunnel pasteurizer downtime.
- User-friendly riveted-pin retention system eliminates the need for welding during assembly.
- Maximum chain width is 6 meters.
- Maximum conveyor length is 43 meters.
- Open area is 50%.

PROGRAMME	
9217	Equipped with rollers every 3", suitable to run on chevron wearstrips
9227	Equipped with rollers every 6", to run parallel wearstrips spaced at 6"
Positrack	Tracking guides for optimum reliability throughout the length of the pasteurizer tunnel.
Fingerplates	Smooth product transfers at infeed and outfeed with self-clearing DTS® -C.




FORTREX 9227 BELT IN A FOOD TUNNEL PASTEURIZER

9200-SERIES





**FORTREX
9200**





Assembly	Belt type	Code nr.*	Temperature rangeProduct °C		Weight load (max.) kg/m²	Backflex kg/m²	radius (min.) mm
			dry	wet			
FORTREX 9217							
STANDARD	9217	820.05.xx	4 to 100	4 to 100	285	24.5	80
POSITRACK	9217 PT	820.06.xx					
FORTREX 9227							
STANDARD	9227	820.02.xx	4 to 100	4 to 100	285	24.0	80
POSITRACK	9227 PT	820.04.xx					



* In code numbers xx corresponds with the belt width (A), starting with 29 for 90, 30 for 93", and so on in steps of 3", up to 240"; see also page 206.



FORTREX 9217




POSITRACK IN THE CENTER OF THE BELT OR 1.5" OFFSET, DEPENDING ON THE WIDTH



FORTREX 9227



9200-SERIES



Comb fingerplate with M6 screw and caps	Code nr.	Length L	Width W	Weight
		mm	mm	kg
REINFORCED POLYAMID				
Comb 5997/Fortrex	I5997/631183	202	150.6	0.2

*Combs are supplied with 2 * M6 Stainless Steel screws and 2 caps

9200-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B mm/inch	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209
SPLIT SPROCKETS							
SQUARE BORES							
KUS 9200 T14 S120	820.10.00	14	120 mm	256.8	270.8	50.8	
KUS 9200 T14 S3.5	820.10.04	14	3.5"				
ROUND BORES							
KUS 9200 T14 R90	820.10.02	14	90 mm	256.8	270.8	50.8	
SPLIT IDLER DRUMS							
SQUARE BORES							
KSXTS 9200 T14 S120	820.10.01	14	120 mm	256.8	236.0	50.8	
KSXTS 9200 T14 S3.5	820.10.05	14	3.5"				
ROUND BORES							
KSXT 9200 T14 R90	820.10.03	14	90 mm	256.8	236.0	50.8	
KSXT 9200 T14 R3.5	820.10.06	14	3.5"				

* Other bore sizes available upon request

2500-SERIES MODULAR BELTS

The 2500-series 2½-inch pitch belt is intended for heavy-duty pasteurizing. The high working load permits application in heavily loaded glass pasteurisers. The total system, the module design, the transfer fingers, the sprockets and the pin retention system have been designed to cope with the harsh environment of glass pasteurizers. As a standard the belts are made of yellow reinforced polypropylene; the transfer plates are made of the same material in green-blue.

FEATURES

- The surface of the belt is designed to handle broken glass without interference with the long term performance of the belt. The special design optimizes water flow and prevents glass particles from getting stuck. Besides the solid ribs are designed to withstand the high forces that might be generated by broken glass.
- The curved bottom of the slots between the ribs ensures an optimum contact with the finger transfer system, unaffected by the chordal action of the belt. This allows the fingers to push glass particles from the slot bottom to leave the system. If damaged, the fingers can be replaced individually.
- The fingers are grouped in a transfer block which allows them to slide and follow the expansion and contraction of the belt.
- The Easy Lock pin retention allows easy installation and maintenance of the belt.

PROGRAMME	
2500 Solid Rib	The 20% open area combines optimum drainage with perfect support for the bottles. The ribbed design prevents broken glass to jam in the surface of the belt as with conventional Raised Rib designs
Positrack	Guiding lugs beneath the belt for accurate tracking of the belt in pasteurizer tunnels over the full length, allowing optimum use of the belt surface
Fingerplates	Transfer system for easy loading of products from and onto the belt




BOTTLE PASTEURIZER INFEED WITH 2500 BELT




GLASS JARS PASTEURIZING ON 2500 BELT

2500-SERIES




**SOLID RIB
2500**




Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
YPR-REINFORCED POLYPROPYLENE WITH REINFORCED POLYPROPYLENE PINS							
STANDARD	SR 2500 YPR	832.70.xx	4 to 104	4 to 104	47500	18.50	75
POSITRACK	SRP 2500 YPR 832.80.xx						

* In code numbers xx corresponds with the belt width (A), starting with 15 for 18", 16 for 21" and so on in steps of 3" up to 240". Other widths upon request. See also page 206.



SOLID RIB 2500 BELT WITH POSITRACK IN THE CENTER OF THE BELT OR 1.5" OFFSET, ONLY FOR CUT-TO-WIDTH BELTS

Product	Code nr.	Weight	Pitch	Length	
		kg	mm	mm	
FINGER TRANSFER SYSTEM					
BPR-POLYPROPYLENE					
MC 2500 mounting-block incl. 16 fingers	834.72.61	1.71	304.4	255.8	
Mounting-block	801.57.01	0.85	304.4	63.0	
RF 2500 BPR exchange set of 16 fingers	834.72.51	0.54	—	—	




Sprocket Type	Code nr.	Nr. of teeth	Bore	Pitch diameter	Outside diameter	Hub width	
			B	E	F	A	
			mm	mm	mm	mm	



SPLIT SPROCKET

SQUARE BORE						
SS 2500 14-120x120 RPA	899.97.29	14	120	285.4	282.0	36



6990-SERIES MODULAR BELTS

The 6990-series 2¼-inch pitch heavy-duty belt is mainly intended for long and wide conveyors in different segments of the automotive industry. The closed surface of the 6995, the non-skid surface of the 6999 execution and the high load capability of these belts allow the handling of people and cars in assembly lines, water and leak testing and car wash applications. As a standard the belts are supplied in high-performance acetal.

FEATURES

- High load capacity up to 50,000 N/m with standard pins and over 70,000 N/M with PBT Pins.
- Equally divided hinge eyes for higher chain stiffness.
- Long life chain design due to large pin diameter, optimum hinge eye width and proven wear resistant design of the chain underside.
- Easy installation and maintenance in combination with Twist-Lock® pin retention at both sides, which are easy to operate with just a screwdriver and prevent the loss of plugs; self-closing under influence of chain weight.
- Standard available in BSM Acetal and in BYSM with yellow sides for clear moving belt edge safety indication; upon request also available with red sides.
- Superior drive technology also under high loading, due to specific belt pocket and drive sprocket design.
- High strength indented pushers available for car wash and automotive applications.

PROGRAMME	
6995 Solid Top	Closed surface; suitable for automotive and people moving applications
6999 Safety Top	Closed non-skid surface; prevents slipping in humid, greasy or wet environments
Belt accessories	T1-inch and T2-inch DIN style automotive pushers. These pushers meet the requirements of the DIN24446 standard. Pushers can be combined with 40mm high sideguards (sideguards are available exclusively through selected industry channels)




CAR INTERIOR CLEANING (DETAILING) INSTALLATION WITH 6995 BELT




DUAL LANE EXTERIOR CAR WASHING ON 6990-SERIES WITH T1 PUSHERS


6990-SERIES




**SOLIDTOP
6995**



Assembly	Belt type	Code nr.*	Temperature rangeWorking °C		Weight load (max.) N/m (21°C)	Backflex kg/m²	radius (min.) mm
			dry	wet			
BSM-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BSM 6995	I6995BSMKxx	4 to +80	4 to +65	51000	14.65	38
BYSM-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BYSM 6995	I6995BYSMKxx	4 to +80	4 to +65	51000	14.65	38





**SAFETYTOP
6999**



Assembly	Belt type	Code nr.*	Temperature rangeWorking °C		Weight load (max.) N/m (21°C)	Backflex kg/m²	radius (min.) mm
			dry	wet			
BSM-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BSM 6999	I6999BSMKxx	4 to +80	4 to +65	51000	14.65	38
BYSM-ACETAL WITH POLYPROPYLENE PINS							
STANDARD	BYSM 6999	I6999BYSMKxx	4 to +80	4 to +65	51000	14.65	38

* In code numbers xx corresponds with the belt width (A). Standard widths of these belts begin at 9" with 6" increments up to 190"; special widths begin at 5" with 1/2" increments. See also page 206.


6990-SERIES

Sprocket type	Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A		
			mm	mm	mm	mm		
SPLIT SPROCKETS								
SQUARE BORES								
NS 5996 T09 S90	614-91-2	9	90	167.1	164.1	48		
NS 5996 T12 S90	614-97-2	12	90	220.8	221.0			
NS 5996 T14 S90	614-89-2	14	90	256.8	256.5			
NS 5996 T14 S120	614-128-1	14	120					
CLASSIC SPROCKETS								
SQUARE BORES								
N 5996 T07 S40	114-821-11	7	40	131.7	125.5	48		
N 5996 T09 S40 HS	114-2238-1	9	40	167.1	164.1			
N 5996 T09 S50 HS	114-3278-1	9	50					
N 5996 T09 S65 HS	114-1599-16	9	65					
N 5996 T14 S40 HS	114-2239-1	14	40	256.8	256.5			
N 5996 T14 S50 HS	114-2239-2	14	50					
N 5996 T14 S65 HS	114-1101-2	14	65					
N 5996 T14 S90 HS	114-1032-2	14	90					
HS suitable for hot and humid applications.								


ACCESSORY INFORMATION:



DIN STYLE PUSHER 6990




T1 DIMENSIONS



T2 DIMENSIONS



DIN STYLE SIDEGUARD 6990



H40 DIMENSIONS


3120 SERIES MODULAR BELTS

The 3120-series 3-inch pitch belt is Rexnord strongest plastic modular chain, primarily used for industrial-type applications including oil-change conveyors, 2 lane final assembly line conveyors, Skid and pallet handling conveyors, 2-lane water test conveyors and automotive parts handling. The chain has proven itself also in single lane car wash and single lane end-of-line inspection conveyors replacing conventional technology. It is moulded in high performance acetal and utilizes patented Twist-Lock® plugs as well as ½" diameter polyester or stainless steel pins. The chain is available with several accessories like T1-inch and T2-inch automotive pushers and sideguards, all meeting the DIN24446 standard. The pushers are designed to be driven over and ensure a controlled handling of any size vehicles on top of the chain. This bricked chain is available from 4-inch wide with increments of 2-inch. Sprockets are available in solid or split execution and in several materials in robust design to handle increased loads.

FEATURES

- Ultra high load capacity of 115,000 N/m (strongest plastic MatTop chain available). No need for (stainless) steel pins to reach maximum working load reducing overall chain weight and power consumption.
- Equally divided hinges combination with large ½" pin diameter provide very high stiffness.
- Long life design due to large pin diameter, optimum hinge eye width and proven wear resistant design of the chain underside (large contact surface).
- Easy installation and maintenance in combination with Twist-Lock pin retention at both sides, which are easy to operate with just a screwdriver and prevent the loss of plugs; self-closing under influence of chain weight.
- Superior drive technology also under high load and heavy duty circumstances, due to specific belt pocket and sprocket design.
- High strength pushers available intended for automotive and industrial usage.
- Available in SolidTop (3125) and SafetyTop (3129) surface execution to meet any application conditions requirement.
- Standard available in BSM and in BYSM with yellow sides for clear moving belt edge safety indication; upon request also available with other color sides.
- High strength DIN style Automotive T1-inch and T2-inch pushers and H40-mm Sideguards available intended for automotive and industrial usage (sideguards are available exclusively through selected industry channels). Pushers and sideguards both meet the requirements of the DIN24446 standard.

PROGRAMME	
3125 Solid Top	Close Surface, suitable for any kind of industrial and automotive application
3129 SafetyTop	Closed non-skid surface; prevents slipping in wet, greasy or humid environments.
Belt accessories	T2-inch pushers available. Robust pushers designed to be driven over by vehicles




EXTERIOR CARWASH ENTRY 3125 BELT CONVEYOR WITH T2 PUCHERS




3125 END OF LINE INSPECTION BELT CONVEYOR WITH T2 DIN PUSHERS


3120-SERIES




**SOLID TOP
3125**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ACETAL WITH POLYESTER PINS							
STANDARD	BSM 3125	I3125BSMKxx	-30 to +80	up to 65	115000	31.10	76.2
STANDARD	BYSM 3125	I3125BYSMK					




**SAFETYTOP
3129**



Assembly	Belt type	Code nr.*	Temperature range °C		Working load (max.) N/m (21°C)	Weight kg/m²	Backflex radius (min.) mm
			dry	wet			
ACETAL WITH POLYESTER PINS							
STANDARD	BSM 3129	I3125BSMKxx	-30 to +80	up to 65	115000	31.10	76.2
STANDARD	BYSM 3125	I3125BYSMKxx					

- In code numbers xx correspond with the belt width (A). Standard width of these belts begin at 4" with 2" increments up to 190"; 4" and 8" execution are mold-to-width executions.





BSM3125-K4 MTW EXECUTION

Belt can be equipped with T1 or T2 automotive pushers and or sideguards, please indicate pushers with T1 or T2 followed by the spacing of the pushers (e.g T18P means every 18th row). Indicate sideguard with SG40. Side indent to the pusher is minimum ½" with 2" increments.

Chain is standard equipped with Polyester (PBT) pins. On request the chain can be equipped with stainless steel pins and in other chain materials as well.

3120-SERIES


Type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209	
CLASSIC SPROCKETS								
SQUARE BORE								
KU 3120 T09 S60	114-5171-8	9	60	222.8	218.9	47.8		
KU 3120 T09 S90	114-5171-14	9	90					
KU 3120 T10 S60	114-5172-8	10	60	246.6	244.1			
KU 3120 T10 S90	114-5172-14	10	90					
KU 3120 T11 S60	114-5173-8	11	60	270.5	269.1			
KU 3120 T11 S90	114-5173-14	11	90					
SPLIT SPROCKETS								
SQUARE BORE								
KUS 3120 T09 S60	614-731-3	9	60	222.8	218.9	47.8		
KUS 3120 T09 S90	614-731-9	9	90					
KUS 3120 T10 S60	614-732-3	10	60	246.6	244.1			
KUS 3120 T10 S90	614-732-9	10	90					
KUS 3120 T11 S60	614-733-3	11	60	270.5	269.1			
KUS 3120 T11 S90	614-733-9	11	90					

* Other bores sizes (square and round) and number of teeth are available on request. Smallest possible sprocket has 8 teeth.


* Stainless steel sprockets available upon request.



DIN STYLE PUSHER 3120




T1 DIMENSIONS



T2 DIMENSIONS



DIN STYLE SIDEGUARD 3120




H40 DIMENSIONS

SIDEFLEXING MODULAR BELTS


The sideflexing belts range exists of 1/2-inch pitch 505, 1 1/4-inch pitch 1200 and 1 1/4-inch pitch 7956 belts, offering a solution for almost any curved application. As a standard the belts are supplied in low friction acetal for beverage and in acetal or polypropylene with antibacterial protection, especially for direct food contact.

FEATURES


- In compliance with the industry standards, three curve guiding systems are offered:



RBP uses beveled Positrack lugs underneath the belt to guide the belt in the curve. The lugs run against a beveled strip, retaining the belt in the curve. This system enables easy removal of the belt from the conveyor for cleaning or maintenance. The conveyed product can be wider than the belt width as there is no wearstrip on top of the belt to hold it down.



RBT guiding uses Tabs underneath the belt to hold the belt down while running through the curve. Often the tabs can also be used to hang the belt in the return part of the conveyor. Depending on the construction modular belts with tabs are more difficult to remove from the conveyor for cleaning and maintenance.



RB (Flat belt without Tabs or Positrack) is suitable for the conventional guiding method, supporting the belt on its inner radius. The belt is held down in the curve by a wearstrip on top of the belt or by running through a U-channel. This method can also be applied in the return part. In this way it is difficult to remove the belt from the conveyor. The RB executions are also suitable for low-tension spiral applications.

- Belt and curve guiding materials have a PV (Pressure/Velocity)-limit determining the maximum speed or load in a specific application. Rexnord's calculation software and engineering manuals will advise concerning the feasibility of a specific application. For spiral applications it is recommended to discuss with a qualified OEM retrofit or design details, to avoid overload issues or failures.

PROGRAMME	
505-Series	For small packed products and loose foodstuff; combines a small internal radius with minimum inline transfers and an open area of 10%; available in RBP and RB
1200-Series	For food, beverage, packaging and other industries. Combines a 39% open area and cleanable design with a surface optimized for product support. There are several types: • 1255 standard execution; available in RBP and RB; RBT upon request • 1255 SuperGrip with rubber for inclined and declined applications; available in RBP and RB • 1265 combines standard 1255 inner modules with specially designed outer end modules with TAB and special sliding blocks for huge loading, high-speed possibilities; available in RBT on the outer radius, the inner radius can be equipped with RBP, RBT and RB • 1275 combines standard 1255 outer modules with specially designed inner modules, creating a compact radius design from 1.2 collapse factor upwards; available in RBP, RBT and RB • 1285 combines the 1265 outer and 1275 inner modules for high strength, high speed and compact design. RBT guiding on the outer radius, the inner radius can be equipped with RBP, RBT and RB
7956-Series	For large and heavy products in beverage and case handling applications; the inside radius is 2 times the belt width and the 16% open area offers maximum product support; the belt features the same strength rating for straight and curved sections. There are several types: • 7956 NT without tabs • 7956 TAB with original hold down tabs • 7956 GT with high performance tabs with similar dimensions as the bearing option • 7956 B with bearings every second row for high-speed and huge load applications
Belt accessories	Flights on 1255 for inclined and declined applications in food industry



PACK CONVEYOR WITH 505 BELT




1275 BELT




BOXES CONVEYED THROUGH CURVE WITH 1285 BELT

505-SERIES




**RADIUS
505**




Assembly	Belt type	Code nr.*	Width	Sideflex radius inside (min.)	Working load (max.)		Temperature range °C		Weight	Backflex radius (min.)
			A		straight	in curve				
			mm	mm	N/m	N	dry	wet		
WITH SPECIAL REINFORCED PLASTIC PINS										
FLAT	RB 505 XLG 255	867.20.12	255	510	15000	1300	-40 to +80	-40 to +65	9.0	15
	RB 505 XLG 340	867.20.13	340	680						
	RB 505 XLG 425	867.20.14	425	850						
	RB 505 XLG 510	867.20.15	510	1020						
	RB 505 XLG 595	867.20.16	595	1190						
	RB 505 XLG 680	867.20.17	680	1360						
POSITRACK TWO SIDES	RBP 505 XLG 255	867.30.12	255	510	15000	1300	-40 to +80	-40 to +65	9.0	15
	RBP 505 XLG 340	867.30.13	340	680						
	RBP 505 XLG 425	867.30.14	425	850						
	RBP 505 XLG 510	867.30.15	510	1020						
	RBP 505 XLG 595	867.30.16	595	1190						
	RBP 505 XLG 680	867.30.17	680	1360						
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS										
FLAT	WSA 505 RB	868.20.xx	255 to 680	2x belt width	15000	1300	-40 to +80	-40 to +65	9.0	15
POSITRACK	WSA 505 RBP	868.30.xx								
ANTIBACTERIAL BSA-ACETAL WITH PBT PINS										
FLAT	BSA 505 RB	867.10.xx	255 to 680	2x belt width	15000	1300	-40 to +80	-40 to +65	9.0	15
POSITRACK	BSA 505 RBP	868.50.xx								


* In code numbers xx corresponds with the belt width (A), starting with 12 for 255 mm, 13 for 340 mm and so on with 85 mm increments up to 680 mm; wider belts available upon request. See also page 206.



STANDARD POSITRACK LUGS ON BOTH SIDES



CURVE GUIDING PROFILE FOR 505



PIN RETENTION CLIPS FOR EASY (DIS)ASSEMBLY

The curve guiding profile for the 505 has a standard length of 2 meters; it is made of MCC 3500 special polyamide, code nr. 800.00.01, or MCC 3600 polyester for direct food contact, code nr. 800.00.13.

505-SERIES

Sprocket Type	Code nr.	Nr. of teeth	Bore	Pitch diameter	Outside diameter	Hub width	MATERIAL
			B mm/inch	E mm	F mm	A mm	

page 209



SPLIT SPROCKETS MACHINED

ROUND BORES

SS 505 28-25	894.26.16	28	25 mm	113.4	113.4	33.5
SS 505 28-30	894.26.17	28	30 mm			
SS 505 28-35	894.26.10	28	35 mm			
SS 505 28-1	894.26.41	28	1.0"			

SQUARE BORES

SS 505 28-25x25	894.26.26	28	25 mm	113.4	113.4	33.5
SS 505 28-30x30	894.26.27	28	30 mm			
SS 505 28-35x35	894.26.20	28	35 mm			
SS 505 28-1x1	894.26.56	28	1.0"			





SPLIT SPROCKETS INJECTION MOULDED

ROUND BORES

SS 505 28-40	895.54.11	28	40 mm	113.4	113.4	25.5
SS 505 28-1 1/2	895.54.41	28	1.5"			

SQUARE BORES

SS 505 28-40x40	895.54.21	28	40 mm	113.4	113.4	25.5
SS 505 28-1 1/2x1 1/2	895.54.51	28	1.5"			





CLASSIC SPROCKETS

ROUND BORES

CS 505 28-25	894.25.16	28	25 mm	113.4	113.4	16.5
CS 505 28-30	894.25.17	28	30 mm			
CS 505 28-35	894.25.10	28	35 mm			
CS 505 28-40	894.25.11	28	40 mm			
CS 505 28-1	894.25.46	28	1.0"			
CS 505 28-1 1/2	894.25.41	28	1.5"			

SQUARE BORES

CS 505 28-25x25	894.25.26	28	25 mm	113.4	113.4	16.5
CS 505 28-30x30	894.25.27	28	30 mm			
CS 505 28-35x35	894.26.20	28	35 mm			
CS 505 28-40x40	894.25.21	28	40 mm			
CS 505 28-1x1	894.25.56	28	1.0"			
CS 505 28-1 1/2x1 1/2	894.25.51	28	1.5"			



Code nr.	Radius	Belt width	Height	Curve width	Angle	MATERIAL
	R	A		B		
	mm	mm	mm	mm		

page 209


TAB CURVES

FOR 505

804.02.02	510	255	27 + 55	281	90°
804.02.03	680	340	27 + 55	366	
804.02.04	850	425	27 + 55	451	
804.02.05	1020	510	27 + 55	536	
804.02.06	1190	595	27 + 55	621	
804.02.07	1360	680	27 + 55	706	

Other angles and non-standard tab curves on request; these curves include a curve guiding profile.


Including 100 mm long straight sections at upper part.



1200-SERIES



RADIUS
1255



page 203



page 203



MATERIAL

page 208

Assembly	Belt type	Code nr.*	Sideflex radius (min.)	Temperature range °C		Working load (max.)		Weight kg/m²	Backflex radius (min.) mm
			mm	dry	wet	straight	in curve		
						N/m	N		
XLG-ACETAL WITH PBT PINS									
POSITRACK TWO SIDES	RBP 1255 XLG	867.40.xx	2 x belt width	-40 to +80	-40 to +65	22000	2000	8.00	25
FLAT	RB 1255 XLG	867.70.xx		-40 to +65					30
SUPERGRIP POSITRACK	SG 1255 XLG RBP	867.53.xx							
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS									
POSITRACK TWO SIDES	WHA 1255 RBP	869.40.xx	2 x belt width	4 to 80	4 to 65	11000	1200	5.20	25
FLAT	WHA 1255 RB	869.90.xx		4 to 65					30
SUPERGRIP POSITRACK	SG 1255 WHA RBP	869.53.xx							
ANTIBACTERIAL BHA-POLYPROPYLENE WITH PBT PINS									
FLAT	BHA 1255 RB	869.80.xx	2x belt width	4 to 80	4 to 65	11000	1200	5.20	25
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS									
POSITRACK TWO SIDES	WSA 1255 RBP	868.40.xx	2x belt width	-40 to +80	up to 65	22000	2000	8.00	25
FLAT	WSA 1255 RB	869.00.xx		-40 to +65					30
SUPERGRIP POSITRACK	SG 1255 WSA RBP	868.63.xx							
ANTIBACTERIAL BSA-ACETAL WITH PBT PINS									
POSITRACK TWO SIDES	BSA 1255 RBP	868.70.xx	2x belt width	-40 to +80	up to 65	22000	2000	8.00	25
FLAT	BSA 1255 RB	869.10.xx							

* In code numbers xx corresponds with the belt width (A), starting with 12 for 255 mm, 13 for 340 mm.


If you need flights, describe the belt by choosing from the required options listed in the 2nd column of the table:

Material	WHA or BHA or WSA or BSA	
Belt type	1255 RBP or 1255 RBT or 1255 RB	RBP for Positrack (only in WHA, WSA and BSA), RBT for Tabs (only in WSA and BSA), RB for Flat
Width (A)	KM-... (in mm)	
Flights	F3 or H..	Standard height of 3" (76.2 mm) or special height in mm
Pitch between flights	T..P	Flights on every .. th row
Flight side-indent	N.. (in mm)	Minimal 51 mm with 17 mm increments


code nr. for special polyamide MCC3500 profile of 2 meters is 800.00.10, code for FDA approved MCC3600 polyester profile of 2 meters is 800.00.11.




POSITRACK LUGS ON BOTH SIDES



TABS ON BOTH SIDES




FLIGHT FOR ELEVATING




Not for use in the U.S.A.




SUPERGRIP FOR INCLINED CONVEYING; STANDARD 100% RUBBER.



1200-SERIES



**RADIUS 1265
REINFORCED OUTER
MODULES**




Assembly	Belt type	Code nr.	Width	Sideflex radius (min.)	Temperature range °C		Working load (max.)		Weight kg/m ²	Backflex radius (min.) mm
			A			straight	in curve			
			mm	mm	dry	wet	N/m	N		
XLG-ACETAL WITH PBT PINS										
TABS/FLAT	RBT 1265 RB XLG/B 255	864.60.12	255	510	-40 to 80	-40 to +65	22000	3000	8.00	25
	RBT 1265 RB XLG/B 340	864.60.13	340	680						
	RBT 1265 RB XLG/B 425	864.60.14	425	850						
	RBT 1265 RB XLG/B 510	864.60.15	510	1020						
	RBT 1265 RB XLG/B 595	864.60.16	595	1190						
	RBT 1265 RB XLG/B 680	864.60.17	680	1360						
	RBT 1265 RB XLG/B 765	864.60.18	765	1530						
	RBT 1265 RB XLG/B 850	864.60.19	850	1700						
	RBT 1265 RB XLG/B 935	864.60.20	935	1870						
	RBT 1265 RB XLG/B 1020	864.60.21	1020	2040						
TABS/ POSITRACK	RBT 1265 RBP XLG/B255	864.00.12	255	510	-40 to +80	-40 to +65	22000	3000	8.00	25
	RBT 1265 RBP XLG/B340	864.00.13	340	680						
	RBT 1265 RBP XLG/B425	864.00.14	425	850						
	RBT 1265 RBP XLG/B510	864.00.15	510	1020						
	RBT 1265 RBP XLG/B595	864.00.16	595	1190						
	RBT 1265 RBP XLG/B680	864.00.17	680	1360						
	RBT 1265 RBP XLG/B765	864.00.18	765	1530						
	RBT 1265 RBP XLG/B850	864.00.19	850	1700						
	RBT 1265 RBP XLG/B935	864.00.20	935	1870						
	RBT 1265 RBP XLG/B1020	864.00.21	1020	2040						
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS										
TABS/FLAT	WSA/B 1265 RBT RB 255	864.90.12	255	510	-40 to +80	-40 to +65	22000	3000	8.00	25
	WSA/B 1265 RBT RB 340	864.90.13	340	680						
	WSA/B 1265 RBT RB 425	864.90.14	425	850						
	WSA/B 1265 RBT RB 510	864.90.15	510	1020						
	WSA/B 1265 RBT RB 595	864.90.16	595	1190						
	WSA/B 1265 RBT RB 680	864.90.17	680	1360						
	WSA/B 1265 RBT RB 765	864.90.18	765	1530						
	WSA/B 1265 RBT RB 850	864.90.19	850	1700						
	WSA/B 1265 RBT RB 935	864.90.20	935	1870						
		WSA/B 1265 RBT RB 1020	864.90.21	1020						

Other widths (17 mm increments from standard) available upon request.


Code nr. for special polyamide profile of 2 meters is 800.00.10.

Not for use in the U.S.A.

1200-SERIES



**RADIUS 1275
TIGHT FIT
INNER MODULES**



Assembly	Belt type	Code nr.	Width	Sideflex radius	Temperature range		Working load (max.)		Weight	Backflex radius
			A	radius (min.)	°C		straight	in curve		
			mm	mm	dry	wet	N/m	N		
XLG-ACETAL WITH PBT PINS										
FLAT	RB 1275 XLG 255	860.90.12	255	300	-40 to +80	-40 to +65	22000	2000	8.00	25
	RB 1275 XLG 340	860.90.13	340	400						
	RB 1275 XLG 425	860.90.14	425	500						
	RB 1275 XLG 510	860.90.15	510	600						
	RB 1275 XLG 595	860.90.16	595	720						
	RB 1275 XLG 680	860.90.17	680	880						
	RB 1275 XLG 765	860.90.18	765	1040						
ANTIBACTERIAL WHA-POLYPROPYLENE WITH PBT PINS										
FLAT	WHA 1275 RB 255	860.70.12	255	300	4 to 80	4 to 65	11000	1200	5.20	25
	WHA 1275 RB 340	860.70.13	340	400						
	WHA 1275 RB 425	860.70.14	425	500						
	WHA 1275 RB 510	860.70.15	510	600						
	WHA 1275 RB 595	860.70.16	595	720						
	WHA 1275 RB 680	860.70.17	680	880						
	WHA 1275 RB 765	860.70.18	765	1040						
ANTIBACTERIAL BHA-POLYPROPYLENE WITH PBT PINS										
FLAT	BHA 1275 RB 255	860.60.12	255	300	4 to 80	4 to 65	11000	1200	5.20	25
	BHA 1275 RB 340	860.60.13	340	400						
	BHA 1275 RB 425	860.60.14	425	500						
	BHA 1275 RB 510	860.60.15	510	600						
	BHA 1275 RB 595	860.60.16	595	720						
	BHA 1275 RB 680	860.60.17	680	880						
	BHA 1275 RB 765	860.60.18	765	1040						
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS										
FLAT	WSA 1275 RB 255	860.80.12	255	300	-40 to +80	-40 to +65	22000	2000	8.00	25
	WSA 1275 RB 340	860.80.13	340	400						
	WSA 1275 RB 425	860.80.14	425	500						
	WSA 1275 RB 510	860.80.15	510	600						
	WSA 1275 RB 595	860.80.16	595	720						
	WSA 1275 RB 680	860.80.17	680	880						
	WSA 1275 RB 765	860.80.18	765	1040						


Other widths (17 mm increments from standard) available upon request.

For 1275 belts with Positrack or tabs, please contact Customer Service.


Code nr. for special polyamide MCC3500 profile of 2 meters is 800.00.10, code for FDA approved MCC3600 polyester profile of 2 meters is 800.00.11

Not for use in the U.S.A.

1200-SERIES



**RADIUS 1285
REINFORCED OUTER AND
TIGHT FIT INNER MODULES**



Assembly	Belt type	Code nr.	Width	Sideflex radius	Temperature range		Working load (max.)		Weight	Backflex radius (min.)
			A	radius (min.)	°C		straight	in curve		
			mm	mm	dry	wet	N/m	N		
XLG-ACETAL WITH PBT PINS										
TABS/FLAT	RBT 1285 RB XLG/B 425	864.80.14	425	500	-40 to +80	-40 to +65	22000	3000	8.00	25
	RBT 1285 RB XLG/B 510	864.80.15	510	600						
	RBT 1285 RB XLG/B 595	864.80.16	595	720						
	RBT 1285 RB XLG/B 680	864.80.17	680	880						
	RBT 1285 RB XLG/B 765	864.80.18	765	1040						
	RBT 1285 RB XLG/B 850	864.80.19	850	1200						
	RBT 1285 RB XLG/B 935	864.80.20	935	1350						
	RBT 1285 RB XLG/B 1020	864.80.21	1020	1500						
ANTIBACTERIAL WSA-ACETAL WITH PBT PINS										
TABS/FLAT	WSA/B 1285 RBT RB 425	865.10.14	425	500	-40 to +80	-40 to +65	22000	3000	8.00	25
	WSA/B 1285 RBT RB 510	865.10.15	510	600						
	WSA/B 1285 RBT RB 595	865.10.16	595	720						
	WSA/B 1285 RBT RB 680	865.10.17	680	880						
	WSA/B 1285 RBT RB 765	865.10.18	765	1040						
	WSA/B 1285 RBT RB 850	865.10.19	850	1200						
	WSA/B 1285 RBT RB 935	865.10.20	935	1350						
	WSA/B 1285 RBT RB 1020	865.10.21	1020	1500						



Other widths (17 mm increments from standard) available upon request. Code nr. for special polyamide profile of 2 meters is 800.00.21.





For 1285 belts with Positrack, please contact Customer Service.

Not for use in the U.S.A.




1200-SERIES

Code nr.	Radius R	Belt width A	Curve width B	Height	Angle	
	mm	mm	mm	mm		
CURVES						
FOR 1255 RBP						
805.02.02	510	255	281	27 + 55	90°	
805.02.03	680	340	366			
805.02.04	850	425	451			
805.02.05	1020	510	536			
805.02.06	1190	595	621			
805.02.07	1360	680	706			
FOR 1275 RBP						These curves include a curve guiding profile. Including 100 mm long straight sections at upper part. Other angles and non-standard tab curves on request.
805.22.61	300	255	281	27+55	90°	
805.22.62	400	340	366			
805.22.63	500	425	451			
805.22.64	600	510	536			
805.22.65	720	595	621			
805.22.66	880	680	706			
FOR 1265 RBT						
806.40.13	510	255	281	27+55	90°	
806.40.14	680	340	366			
806.40.15	850	425	451			
806.40.16	1020	510	536			
806.40.17	1190	595	621			
806.40.18	1360	680	706			
FOR 1285 RBT						
806.40.19	500	425	451	27+55	90°	
806.40.20	600	510	536			
806.40.21	720	595	621			
806.40.22	880	680	706			


Sprocket Type		Code nr.	Nr. of teeth	Bore B	Pitch diameter E	Outside diameter F	Hub width A	MATERIAL page 209
				mm	mm	mm	mm	
SPLIT SPROCKETS								
ROUND BORES								
SS 1255	10-30	894.60.17	10	30	102.8	106.6	32.5	
SS 1255	13-40	894.64.11	13	40	132.7	137.5		
SS 1255	15-40	894.62.11	15	40	152.7	158.1		
SS 1255	16-40	894.66.11	16	40	162.8	168.3		
SQUARE BORES								
SS 1255	10-30x30	894.60.27	10	30	102.8	106.6	32.5	
SS 1255	13-40x40	894.64.21	13	40	132.7	137.5		
SS 1255	15-40x40	894.62.21	15	40	152.7	158.1		
SS 1255	16-40x40	894.66.21	16	40	162.8	168.3		
CLASSIC SPROCKETS								
ROUND BORES								
CS 1255	8-30	894.67.37	8*	30	83.0	85.4	15.0	
CS 1255	10-30	894.59.37	10	30	102.8	106.6		
CS 1255	13-40	894.63.31	13	40	132.7	137.5		
CS 1255	15-40	894.61.31	15	40	152.7	158.1		
CS 1255	16-40	894.65.31	16	40	162.8	168.3		
SQUARE BORES								
CS 1255	8-25x25	894.67.46	8*	25	83.0	85.4	15.0	
CS 1255	10-40x40	894.59.41	10	40	102.8	106.6		
CS 1255	13-40x40	894.63.41	13	40	132.7	137.5		
CS 1255	15-40x40	894.61.41	15	40	152.7	158.1		
CS 1255	16-40x40	894.65.41	16	40	162.8	168.3		





* 8-teeth sprockets are not applicable for 1265 and 1285.


7956-SERIES



**RADIUS
7956**




Assembly	Belt type		Code nr.	Width	Sideflex radius (min.)	Working load (max.)		Temperature range °C		Weight kg/m ²	Backflex radius (min.) mm	
				A		straight	in curve					
				inch	inch	N	N	dry	wet			
HP-ACETAL WITH POLYPROPYLENE PINS												
FLAT	HP 7956 NT-K6		81417101	6	12	2000	2000	-40 to + 80	-40 to +65	11.7	152	
	HP 7956 NT-K12		81429711	12	24	3560	3560					
	HP 7956 NT-K15		81427901	15	30	4000	4000					
	HP 7956 NT-K18		81427911	18	36	4225	4225					
	HP 7956 NT-K24		81428241	24	48	5300	5300					
	HP 7956 NT-K30		81428631	30	60	5780	5780					
TABS TWO SIDES (HOLD-DOWN)	HP 7956 TAB-K6		81417091	6	12	2000	2000	-40 to + 80	-40 to +65	11.7	152	
	HP 7956 TAB-K12		81429671	12	24	3560	3560					
	HP 7956 TAB-K15		81415631	15	30	4000	4000					
	HP 7956 TAB-K18		81421801	18	36	4225	4225					
	HP 7956 TAB-K24		81419711	24	48	5300	5300					
	HP 7956 TAB-K30		81427261	30	60	5780	5780					
TABS TWO SIDES (GT)	HP7956 GT-K6		81436441	6	12	2000	2000	-40 to + 80	-40 to +65	11.7	152	
	HP7956 GT-K12		81436471	12	24	3560	3560					
	HP7956 GT-K15		81436501	15	30	4000	4000					
	HP7956 GT-K18		81436531	18	36	4225	4225					
	HP7956 GT-K24		81436561	24	48	5300	5300					
	HP7956 GT-K30		81436591	30	60	5780	5780					
BEARING (EVERY 2ND ROW)		HP7956 B-K6	CCW	81437471	6	12	2000	2000	-40 to + 80	-40 to +65	11.7	152
			CW	81437461								
			STURN	81437481								
		HP7956 B-K12	CCW	81437491	12	24	3560	3560				
			CW	81433641								
			STURN	81437501								
		HP7956 B-K15	CCW	81437521	15	30	4000	4000				
			CW	81437511								
			STURN	81437531								
		HP7956 B-K18	CCW	81433441	18	36	4225	4225				
			CW	81433691								
			STURN	81437541								
		HP7956 B-K24	CCW	81433611	24	48	5300	5300				
			CW	81437551								
			STURN	81437561								
		HP7956 B-K30	CCW	81437581	30	60	5780	5780				
			CW	81437571								
			STURN	81437591								





7956-SERIES




HOLD-DOWN TABS



GT TABS



BEARINGS



Code nr.	Radius R	Belt width A	Curve width B	Height	Angle	MATERIAL page 209
	mm	mm	mm	mm		
CURVES						
FOR 7956 B						
808.40.00	305	6	196	27+55	90°	
808.40.01	610	12	366			
808.40.02	762	15	451			
808.40.03	915	18	536			
808.40.04	1220	24	706			
808.40.05	1524	30	791			
FOR 7956 GT						Curves for 7956 GT include a special curve guiding profile. Other angles and non-standard tab curves on request.
808.40.06	305	6	196	27+55	90°	
808.40.07	610	12	366			
808.40.08	762	15	451			
808.40.09	915	18	536			
808.40.10	1220	24	706			
808.40.11	1524	30	791			



Sprocket type	Code nr.	Nr. of teeth	Bore B mm	Pitch diameter E mm	Outside diameter F mm	Hub width A mm	MATERIAL page 209	
SPLIT SPROCKETS								
ROUND BORES								
NS 7956 T16 R25	614-169-4	16	25	162.7	163.2	48		
NS 7956 T16 R30	614-169-1	16	30					
NS 7956 T16 R35	614-169-3	16	35					
NS 7956 T16 R40	614-169-5	16	40					
SQUARE BORES								
NS 7956 T16 S40	614-170-3	16	40	162.7	163.2	48		
NS 7956 T16 S50	614-170-4	16	50					
NS 7956 T16 S60	614-170-2	16	60					
CLASSIC SPROCKETS								
ROUND BORES								
KU 7956 T14 R30	114-4133-66	14	40	142.7	142.4	35		
KU 7956 T14 R40	114-4133-68	14	40					
SQUARE BORE								
KU 7956 T14 S40	114-4102-7	14	40	142.7	142.4	35		

TABLE BELT WIDTHS

Belt series	Standard (uncut)		Non-standard (cut)		MTW
	Minimum belt width	Belt width increments	Minimum belt width	Belt width increments	Moulded to width belts
500	85 mm	85 mm	85 mm	on request	-
515	4"	1"	2"	1/2"*	-
1505 imperial	3"	3"	4 1/2"	3/4"	-
1505 metric	85 mm	85 mm	85 mm	on request	-
1506	3"	3"	4 1/2"	3/4"	-
1505 SG	85 mm	85 mm	85 mm	on request	-
8500	6"	6"	2 1/3"	1/3"	2 1/3" - 3 1/4" - 4 1/2" - 7 1/2" - 85 mm
5935	6"	3"	3"	3/4"	-
5936	6"	3"	2 1/4"	3/4"	-
1000	85 mm	85 mm	55 mm	5 mm	-
1000 SG	85 mm	85 mm	80 mm	10 mm	-
1015	4"	1"	4"	1/2"***	-
1005	85 mm	85 mm	85 mm	17 mm	-
1005 SG	170 mm	85 mm	85 mm	17 mm	-
7705	6"	3"	5"	1/2"	3 1/4" - 4 1/2" - 7 1/2"
7706	6"	3"	5"	1/2"	3 1/4" - 4 1/2" - 7 1/2"
7708	9"	3"	5"	1/2"	-
6300	255 mm	75 mm	225 mm	on request	-
2000	3"	3"	3"	1 1/2"	-
2010	6"	2"	3 1/3"	2/3"	-
6990	9"	3"	5"	1/2"	-
9200	9"	3"	-	-	-
2500	18"	3"	3"	1 1/2"	-
3125	-	-	-	-	12"
505	255 mm	85 mm	153 mm	17 mm	-
1255	255 mm	85 mm	153 mm	17 mm	-
1255 SG	255 mm	85 mm	153 mm	17 mm	-
1265	255 mm	85 mm	255 mm	17 mm	-
1275	255 mm	85 mm	237 mm	17 mm	-
1285	425 mm	85 mm	357 mm	17 mm	-
7956	-	-	-	-	6" - 12" - 15" - 18" - 24" - 30"
*) after 12" belt width increments are 1" **) after 24" belt width increments are 1" ***) smaller sizes on request					

Code nr. ending on	Width mm	Code nr. ending on	Width mm	Code nr. ending on	Width mm	Code nr. ending on	Width mm	Code nr. ending on	Width mm	Code nr. ending on	Width mm	Code nr. ending on	Width mm
CODE NUMBERS FOR 500-, 1000-, 1005-, 505 AND 1200-SERIES													
10	85	21	1020	32	1955	43	2890	54	3825	65	4760	76	5695
11	170	22	1105	33	2040	44	2975	55	3910	66	4845	77	5780
12	255	23	1190	34	2125	45	3060	56	3995	67	4930	78	5865
13	340	24	1275	35	2210	46	3145	57	4080	68	5015	79	5950
14	425	25	1360	36	2295	47	3230	58	4165	69	5100	80	6035
15	510	26	1445	37	2380	48	3315	59	4250	70	5185	81	6120
16	595	27	1530	38	2465	49	3400	60	4335	71	5270		
17	680	28	1615	39	2550	50	3485	61	4420	72	5355		
18	765	29	1700	40	2635	51	3570	62	4505	73	5440		
19	850	30	1785	41	2720	52	3655	63	4590	74	5525		
20	935	31	1870	42	2805	53	3740	64	4675	75	5610		

Code nr. ending on	Width		Code nr. ending on	Width		Code nr. ending on	Width		Code nr. ending on	Width		Code nr. ending on	Width		Code nr. ending on	Width	
	mm	inch		mm	inch		mm	inch		mm	inch		mm	inch		mm	inch
CODE NUMBERS FOR 2000- AND 2500-SERIES																	
10	76	3	22	991	39	34	1905	75	46	2819	111	58	3734	147	70	4648	183
11	152	6	23	1067	42	35	1981	78	47	2896	114	59	3810	150	71	4724	186
12	229	9	24	1143	45	36	2057	81	48	2972	117	60	3886	153	72	4801	189
13	305	12	25	1219	48	37	2134	84	49	3048	120	61	3962	156	73	4877	192
14	381	15	26	1295	51	38	2210	87	50	3124	123	62	4039	159	74	4953	195
15	457	18	27	1372	54	39	2286	90	51	3200	126	63	4115	162	75	5029	198
16	533	21	28	1448	57	40	2362	93	52	3277	129	64	4191	165	76	5105	201
17	610	24	29	1524	60	41	2438	96	53	3353	132	65	4267	168	77	5182	204
18	686	27	30	1600	63	42	2515	99	54	3429	135	66	4343	171	78	5258	207
19	762	30	31	1676	66	43	2591	102	55	3505	138	67	4420	174	79	5334	210
20	838	33	32	1753	69	44	2667	105	56	3581	141	68	4496	177	80	5410	213
21	914	36	33	1829	72	45	2743	108	57	3657	144	69	4572	180	81	5486	216

MATERIALS

Product	Material chain	Material pin
STEEL SLATBAND CHAINS		
10-series	AISI 430 (Werkstoff-Nr. 1.4016) special 17% chrome stainless steel for improved corrosion resistance, wearlife and strength	AISI 431 (Werkstoff-Nr. 1.4057)
60-series	Special chrome-nickel stainless steel for excellent sliding properties, improved corrosion resistance, long wearlife and high strength	AISI 431 (Werkstoff-Nr. 1.4057)
60-series HB	Special chrome-nickel stainless steel for excellent sliding properties, improved corrosion resistance, long wearlife and high strength	AISI 431 (Werkstoff-Nr. 1.4057) hardened
66-series XHB	Special chrome-nickel stainless steel for excellent sliding properties, improved corrosion resistance, long wearlife and high strength	Special alloy Process hardened
SSC SSR	OPTI-Plus patented alloy of ferritic chrome-nickel stainless steel, for high strength and great wear resistance	AISI 431 (Werkstoff-Nr. 1.4057)
SS 805/815/881	Austenitic chrome-nickel stainless steel with properties similar to 18/8 material, offering good chemical resistance	Austenitic stainless steel
SS 802/812	Ferritic chrome stainless steel for mix of good wear life and high strength	AISI 431 (Werkstoff-Nr. 1.4057)
S SC	Thorough hardened carbon steel, for glassworks and other dry, abrasive applications, offering extremely high working loads and superior wear resistance	Hardened carbon steel
SSB 815	Austenitic stainless steel with a very high chemical resistance for corrosive environments where strong acids or bases are present. As nearly non-magnetic it is used in applications where magnetism of the chain can cause malfunctioning of the system	Austenitic stainless steel
Rubber top	Special elastomere with a hardness of 70 Shore A	
PLASTIC SLATBAND CHAINS		
XL	Internally lubricated, extra low friction acetal for improved wearlife and high strength. Colour: light brown	Stainless steel (Werkstoff-Nr. 1.4057)
LF	Low Friction acetal (POM) and special blend of lubricants for reduced wear up to 15% over plain acetal; intended for high-output applications at moderate to high speeds. Colour: light brown	
HP	High Performance internally lubricated acetal (POM), for reduced wear up to 40% over plain acetal; intended for dry running or reduced lubrication and high-speed applications. Colour: grey	
PS	Internally lubricated polyacetal for high-speed applications, improving wear life. Colour: grey	
WX	Polyamide composite for extended wear life in abrasive circumstances up to five times compared to plain acetal; to be used in dry running glass handling applications and when the chain is subjected to sand and dirt. Colour: light green	
D	Acetal with higher friction and wear resistance; economic alternative. Colour: grey	
LBP	Wear resistant, extra low friction XLA-acetal with special selflubricating additives. Colour: anthracite Rollers are made of special wear resistant and sound absorbing plastic; colour: aubergine. Roller shafts: stainless steel AISI 304 (Werkstoff-Nr. 1.4301)	
SuperGrip	Wear resistant polyester. Colour: anthracite. Rubber top material: special elastomere with a hardness of 70 Shore A. Colour: aubergine	
XLG	Internally lubricated, extra low friction acetal for improved wearlife and high strength; FDA approved. Colour: green-blue	
DKA	Aramide reinforced acetal (POM) for wet or dry abrasive conditions, offering enhanced wear properties over plain acetals in combination with the low friction of a lubricated material. This material is available on request for a selected range of TableTop products.	
MULTIFLEX AND CASE CONVEYOR CHAINS		
HP	High Performance internally lubricated acetal (POM), for reduced wear up to 40% over plain acetal. Colour: grey	Stainless steel
LF	Low Friction acetal (POM) and special blend of lubricants for reduced wear up to 15% over plain acetal. Colour: light brown	Stainless steel 1700 K: zinc plated stainless steel
WX	Polyamide composite for extended wear life in abrasive circumstances up to five times compared to plain acetal. Colour: light green	Stainless steel
WLF	Low Friction acetal (POM) and special blend of lubricants for reduced wear up to 15% over plain acetal. Colour: white	Stainless steel 1700 K: zinc plated stainless steel
AC	Armor Clad acetal with hardened steel top plates	Zinc plated
BWX	Polyamide composite for extended wear life in abrasive circumstances up to five times compared to plain acetal; to be used in dry running glass handling applications and when the chain is subjected to sand and dirt. Colour: Black	Stainless steel (Werkstoff-Nr. 1.4057)
Corner disc - hub	Reinforced polyamide HP low friction acetal (ND 1700 FL/TR); brass (880)	
XL	Internally lubricated, extra low friction acetal for improved wearlife and high strength. Colour: light brown	AISI 431 (Werkstoff-Nr. 1.4057)
NC	Wear resistant, special acetal. Colour: white	AISI 301 (Werkstoff-Nr. 1.4310)
BL	Acetal. Colour: blue, RAL 5005	AISI 301 (Werkstoff-Nr. 1.4310)
WPP	Chemical resistant and high temperature water resistant polypropylene with glass fibers. Colour: White	

MATERIALS

Product	Material belt
PLASTIC MODULAR CONVEYOR BELTS	
AS	Acetal with improved electrical conductive properties, reducing the build-up of static electricity. Colour: black
BHA	Polypropylene with Microban antibacterial protection for high temperature
BHT	Polypropylene for high temperature applications. FDA-approved. Colour: blue
BLA	Polyethylene with Microban antibacterial protection for low temperature applications; high impact resistance. FDA-approved. Colour: blue
BSA	Acetal with Microban antibacterial protection for high pressure and high speed, due to the hard surface; good abrasion resistance. FDA-approved. Colour: blue
BSM	Acetal with high resistance against wear and superficial damage. Colour: black
BYSM	Acetal with high resistance against wear and superficial damage. Colour: black with yellow end modules
HP	High Performance internally lubricated acetal (POM), for reduced wear up to 40% over plain acetal; intended for dry running or reduced lubrication and high-speed applications. Colour: grey
HT	Polypropylene for applications with high temperatures; good chemical resistance. Colour: beige
LF	Low Friction acetal (POM) and special blend of lubricants for reduced wear up to 15% over plain acetal; intended for high-output applications at moderate to high speeds. Colour: light brown
PS	Internally lubricated acetal for high-speed applications, improving wear life. Colour: grey
TCF	Tough Composite Friction material with high strength and excellent impact and chemical resistance for high-speed case incline or decline conveyors. Colour: light grey
USP	Ultra Stabilized Polypropylene to increase reliability and prolong wear life in high temperature, chemically-aggressive pasteurizer, warmer and cooler applications.
WHA	Polypropylene with Microban antibacterial protection for high temperature applications. FDA-approved. Colour: white
WHT	Polypropylene for high temperature applications. FDA-approved. Colour: white Colour: green
WLA	Polyethylene with Microban antibacterial protection for low temperature applications; high impact resistance. FDA-approved. Colour: white
WLT	Polyethylene for low temperature applications; high impact resistance. FDA-approved. Colour: white
WSA	Acetal with Microban antibacterial protection for high pressure and high speed, due to the hard surface; good abrasion resistance. FDA-approved. Colour white
WX	Polyamide composite for extended wear life up to five times compared to acetal materials; to be used in dry running glass handling applications where abrasive shards of glass can wear other materials rapidly; it can also be used in applications where the belt is subjected to sand and dirt. Colour: light green
DKA	Aramide reinforced acetal (POM) for wet or dry abrasive conditions, offering enhanced wear properties over plain acetals in combination with the low friction of a lubricated material. This material is available on request for a selected range of TableTop products.
XLA	Internally lubricated, extra low friction acetal for improved wearlife and high strength. Colour: anthracite
XLG	Internally lubricated, extra low friction acetal for improved wearlife and high strength; FDA approved. Colour: green-blue
XP	Wear resistant polypropylene with excellent long term heat stability – up to 104°C – and a very good chemical resistance; FDA approved. Colour: light green
USP	Ultra Stabilized Polypropylene with Superior long term heat stability – up to 104°C – and excellent chemical resistance; FDA approved. Colour dark green
YPR	Wear resistant reinforced polypropylene with excellent long term heat stability – up to 104°C – and a very good chemical resistance. Colour: yellow
DTS-C transfer	Super tough reinforced polyamide, wear and abrasion resistant, extra high strength. Colour: black
Finger transfer 2500	Mounting block: MCC 1001; high grade mix of UHMWPE. Colour: black Fingers: Reinforced BPR-Polypropylene. Colour: green-blue
Profile fingerplates 1000/2000	Stainless steel AISI 304 (Werkstoff Nr. 1.4301)
Wearstrip MCC 3500	Special lubricated polyamide for superior PV-rating. Colour: grey-black
Wearstrip MCC 3600	Polyester based plastic for direct food contact; FDA-approved. Colour: white
PLATE TOP CHAINS	
Base chain	Standard: Carbon steel
	SS: Stainless steel
Top Plate	LF acetal (POM) and special blend of lubricants for reduced wear up to 15% over plain acetal. Colour: light brown
	HP internally lubricated acetal (POM), for reduced wear up to 40% over plain acetal. Colour: grey
	WX Polyamide composite for extended wear life in abrasive circumstances up to five times compared to plain acetal. Colour: light green
	WPC Polycarbonate offering resistance to product dropped onto the chain. Colour: white

MATERIALS

Part	Material
CURVES	
Upper part of Combi-A and CIP-curves	MCC 1200, ultra high molecular weight polyethylene, for optimum wear and abrasion resistance with a molecular weight exceeding 9 million g/mol. Colour: aubergine
Upper part of Combi-G curves	MCC 2000, ultra high molecular weight polyethylene, with specially integrated ceramic additives, for superior abrasion resistance with a molecular weight exceeding 9 million g/mol. Colour: green-yellow
Upper part of Combi-S curves	MCC 3500, special polyamide for optimum wear resistance in dry running lines where plastic chains run at high speeds. Colour: sulphite grey
Upper part of Combi-L curves	MCC 3000, ultra high molecular weight polyethylene, for noise reduction and high PV limits with a molecular weight exceeding 9 million g/mol. Colour: light blue
All return parts	MCC 1002, high grade mix of ultra high molecular weight polyethylene, for good wear and abrasion resistance with a molecular weight exceeding 3-7 million g/mol. Colour: black
Cover plates	Stainless steel AISI 430 (Werkstoff Nr. 1.4016)
Screws	Stainless steel
Inserts (optional)	Brass
Return guide shoe	MCC 1200, ultra high molecular weight polyethylene, for good wear and abrasion resistance with a molecular weight exceeding 9 million g/mol. Colour: black
Tubes in CIP-curves	Stainless steel AISI 303 (Werkstoff Nr. 1.4305)
Nozzles in CIP-curves	Stainless steel AISI 303 (Werkstoff Nr. 1.4305)
Tab curves	MCC 1003, ultra high molecular weight polyethylene, for good wear and abrasion resistance with a molecular weight exceeding 1 million g/mol
- inserts (optional)	Brass

Sprocket	Material
SPROCKETS AND IDLERS FOR TABLETOP CHAINS	
N/NS/SSW/SIW	Super tough reinforced polyamide, wear and abrasion resistant
KU(S)/KXT/NSX(T)/NX(T)/SD/SS/SI	Polyamide
ST	Carbon steel
Bolts	Stainless steel AISI 304 (Werkstoff Nr. 1.4301)
Inserts	Brass
SPROCKETS AND IDLERS FOR MULTIFLEX CHAINS	
KU/KUS/N/NX/NXT	Polyamide
ZN	Zinc plated steel
GG	Cast iron
SPROCKETS FOR CASE CONVEYOR CHAINS	
KU	Polyamide
SR	Super tough reinforced polyamide, wear and abrasion resistant
Hub	Carbon steel with black finish or stainless steel
SPROCKETS FOR MODULAR BELTS	
SSW 500/1000 NS 1500/5996/5700/7700/8500/7956 N 1500 SS 2500 RPA	Reinforced polyamide; extra high strength, wear and abrasion resistant
CS 500/1000/505/1255 KU 1500/3125/5936/7700/8500/7956 KUS 1500/7700/3125	Polyamide; super tough, wear and abrasion resistant
SS 1005/505/1255 SI 1005	Special plastic; super tough, wear and abrasion resistant
KU 1010 CS 2010 KUS 6390	Polyethylene
N 5996/4700/5936 CS/SS 2000 KU 510 KUS/KSXT 9200	POM Acetal; wear resistant
Bolts and nuts	Stainless steel AISI 304 (Werkstoff Nr. 1.4301)
Inserts	Brass

Chain	page	Belt	page	Sprocket	page	Curve/straight track	page
10 M	16	500 FG	133	CH CC	89	505 TAB CURVE	194
10 S	10, 12	500 FGP	133	CS 500	133	1200 TAB CURVE	199
60 M	16, 19	505 RB	197	CS 505	198	C1	107
60 S	10, 12, 14	505 RBP	197	CS 1000	157	C2	107
66 B	24	515	135	CS 1255	203	C3	108
66 M	16, 19, 24, 25	905 Nosebar	141	CS 2000	179	C4	108
66 S	11, 12, 14, 21, 22, 23	1000 CLICK-COMB	154	CS 2010	183	C5A	109
66 ST	23	1000 FFGP	152	GG 1757	83	C5B	109
66 T	25	1000 FFTP	151	KSXTS 9200	187	C5C	110
512	14	1000 FG	152	KU 515	135	C5D	110
581 M	19	1000 FGDP	152	KU 600	89	C6	111
661 S	15	1000 FINGER	155	KU 815	57	C7	111
661 M	20	1000 FT	151	KU 821	63	C14	112
800/802/805	12	1000 FTDP	151	KU 1010	165	C21A	113
810	14	1000 LBP	156	KU 1500	141	C22A	113
812	10, 11, 14	1000 RR	154, 155	KU 1700	82	C42	114
812 TAB	13, 21	1000 RRR	155	KU 3120	195	C43	114
815	11	1000 SG	153	KU 5936	149	C61	115
815 TAB	13	1000 SGDP	153	KU 7700	169	C65	116
820	28	1005 FFTDP	159	KU 7956	205	C66	116
820 HFP	42	1005 FT	159	KU 8500	145	C81	117
820 Vacuum	39	1005 FTDP	159	KUS 815	56	C86	117
821	30	1005 LBP	162	KUS 821	69	C91	118
821 HFP	42, 43	1005 LBPDP	162	KUS 1500	141	C96	118
831	29	1005 SG	160	KUS 2500	83	CB6	121
843	93	1005 SGDP	160	KUS 3120	195	CC6	122
879	33	1005 SGS	161	KUS 6390	173	CC21	122
879 TAB	35	1005 SGSDP	161	KUS 7700	169	CF6	110
879 TAB BO	37	1015	165	KUS 9200	187	CIP4	121
879 TAB BO HFP	46	1255 RB	199	KXT 800	64	KSU	127
879 TAB BO LBP	50	1255 RBP	199	N 800	62	KSU 200	128
880	32	1255 SG	199	N 820	58	KTU	123
880 TAB	34, 40	1265 RBT	200	N 1108	72	KTU 200	124
880 TAB BO	46, 40	1275 RB	201	N 1500	141	KTU 300	125
880 TAB BOT HFP	46	1285 RBT	202	N 1700	82	KTU 500	126
880 TAB HFP	45	1505	137	NSH 880	69	LBP2	119
880 TAB Vacuum	39	1505 DTS	137	N 5936	149	LBP91	120
881/	17	1505 FT	139	N 5996	187	LBP96	120
881 TAB	17	1505 FTDP	139	NS 815	55	LBP861	119
882	33	1505 SG	140	NS 820	58	N 880 BOT	75
882 TAB	38	1505 SGDP	140	NS 821	62	ND 1700	86
882 TAB HFP	45	1505 SGS	140	NS 831	67	ND 1700BC	86
883 TAB LBP	50	1505 SGSDP	140	NS 880	71	ND 1700BO	86
963	92	1506	138	NS 881	61	ND 1700FL	86
1050 FGM/FT	52, 54	2000 CLICK-COMB	177	NS 882	70	NX 880 BOT	75
1055 FT/FTM	53, 54	2000 DTS-C	178	NS 1500	141	NXT 880 BO	75
1060 FTM	53	2000 FG	175	NSH 880	69	SSU	129
1080	41	2000 FT	175	NS 5996	192	STU	129
1108	41	2000 RR	176	NS 7700	169	STU 200	129
1700	78	2000 RRHD	176	NS 7956	205	STU 300	129
1702	79	2000 RRHDP	176	NS 8500	145	STU 500	129
1710	80	2000 RRP	176	NSX 821	62		
1713	81	2000 SR	177	NSX 880	71		
1720	79	2000 SRP	177	NSX 881	61		
1757	77	2011	182	NSX 882	70		
1765 ZeroGap	76	2015	181	NSXT 820	59		
1775 ZeroGap	79	2016	181	NX 800	62		
1843 TAB	93, 98	2500 FINGER	189	NX 881	61		
1864	92	2500 SR	189	NX 1108	72		
2565	77	2500 SRP	189	NX 1700	82		
1873 TAB	97, 98, 100, 95, 96, 101	3125	194	NXT 820	59		
1874 TAB	94, 97	3129	194	NXT 821	69		
3873 TAB	96	5935	147	NXT 1757	83		
8811	16	5935 VAC	148	SD 75	60		
8811 TAB	18, 25	5936	147	SD RH	69		
CC 600	85	6390T	171	SI 75	60		
CC 631 TAB	86	6391T	172	SI 1005	163		
CC 1400	87	6392T	173	SI HD	70		
CC 1431 TAB	88	6995	191	SI RH	71		
HDF	38	6999	191	SIW 1050	72		
HDF LBP	51	7705	167	SR CC 600/1400	89		
HDFM	32	7705 DTS	167	SS 75	60		
HDFM LBP	49	7706	168	SS 505	198		
HDFM SG	44	7708	168	SS 661	66		
HDS	30	7956	204	SS 1005	163		
HDS LBP	48	8505	143	SS 1255	203		
HDS SG	44	8505 DTS	143	SS 2000	179		
RH/RHD	34, 35	8506	144	SS 2500	189		
RHM/RHMD	31	9217	185	SS HD	70		
RHMD LBP	49	9227	185	SS MINI	65		
RHMP/RHMDP	31			SS RH	71		
SH/SHD/SHP	28, 29			SS SH	68		
SHD LBP	47			SSW 500	133		
SRH	36			SSW 1000	156		
SWH	30			SSW 1050	72		
SWH LBP	47			ST 512	65		
SWH SG	43			ST 1080	72		
				ZN 1700	83		

NOTES